

2

USAFETAC/DS-89/226

DTIC FILE COPY



AD-A228 600

SURFACE OBSERVATION CLIMATIC SUMMARIES

FOR

GILA BEND AAF, AZ

Prepared by

OL-A, USAFETAC
ASHEVILLE, NORTH CAROLINA
28801-2723



NOVEMBER 1989

DTIC
ELECTE
NOV 13 1990
S E D

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION IS UNLIMITED

USAF
ENVIRONMENTAL TECHNICAL
APPLICATIONS CENTER


Scott Air Force Base, Illinois, 62225-5438

REVIEW AND APPROVAL STATEMENT

USAFETAC/DS-89/226, SURFACE OBSERVATION CLIMATIC SUMMARIES FOR GILA BEND AAF AZ, NOVEMBER 1989, HAS BEEN REVIEWED AND IS APPROVED FOR PUBLIC RELEASE. THERE IS NO OBJECTION TO UNLIMITED DISTRIBUTION OF THIS DOCUMENT TO THE PUBLIC AT LARGE, OR BY THE DEFENSE TECHNICAL INFORMATION CENTER (DTIC) TO THE NATIONAL TECHNICAL INFORMATION SERVICE (NTIS).

JOSEPH L. BOYTE
CHIEF, CLIMATIC APPLICATIONS, OL-A

FOR THE COMMANDER


WALTER S. BURGMANN
SCIENTIFIC AND TECHNICAL INFORMATION
PROGRAM MANAGER

24 AUG 1990

REPORT DOCUMENTATION PAGE

2. REPORT DATE: NOVEMBER 1989
3. REPORT TYPE AND DATES COVERED: DATA SUMMARY, NOVEMBER 1948 TO MAY 1989
4. TITLE AND SUBTITLE: SURFACE OBSERVATION CLIMATIC SUMMARIES (SOCS) FOR GILA BEND AAF ARIZONA
7. PERFORMING ORGANIZATION NAME AND ADDRESS: OPERATING LOCATION A, USAFETAC, FEDERAL BUILDING, ASHEVILLE, NC 28801-2723
8. PERFORMING ORGANIZATION REPORT NUMBER: USAFETAC/DS-89/226
9. SPONSORING/MONITORING AGENCY NAME AND ADDRESS: USAF ENVIRONMENTAL TECHNICAL APPLICATIONS CENTER (USAFETAC), SCOTT AFB, IL 62225-5438
11. SUPPLEMENTARY NOTES: EFFECTIVE JULY 1 1988, THIS PRODUCT REPLACED TWO USAFETAC DOCUMENTS FORMERLY KNOWN AS THE REVISED UNIFORM SUMMARY OF SURFACE OBSERVATIONS (RUSSWO) AND THE LIMITED SURFACE OBSERVATIONS CLIMATIC SUMMARY (LISOCs). EXISTING RUSSWOS AND LISOCs WILL CONTINUE IN USE, BUT WILL EVENTUALLY BE BY A SOCS.
- 12A. DISTRIBUTION/AVAILABILITY STATEMENT: APPROVED FOR PUBLIC RELEASE, DISTRIBUTION IS UNLIMITED.
13. ABSTRACT: SURFACE OBSERVATION CLIMATIC SUMMARIES (SOCS) PROVIDE STATISTICAL CLIMATIC SUMMARIES OF SURFACE WEATHER OBSERVATIONS TAKEN AND RECORDED AT SPECIFIED USAF, CIVILIAN AND FOREIGN OBSERVING STATIONS. HOURLY OBSERVATIONS ARE SUMMARIZED FROM A 10-YEAR PERIOD OF RECORD (POR). "SUMMARY OF DAY" (SOD) INFORMATION IS SUMMARIZED FROM ALL AVAILABLE DATA IN THE OL-A, USAFETAC CLIMATIC DATABASE.
14. SUBJECT TERMS: CLIMATOLOGY, METEOROLOGICAL DATA, ATMOSPHERIC PHENOMENA, WEATHER, SOCS, GILA BEND AAF ARIZONA, CEILING, CLOUD COVER, SNOW DEPTH, HUMIDITY, PRESSURE, PRECIPITATION, SNOW, TEMPERATURE, VISIBILITY, WIND.
15. NUMBER OF PAGES: 375
17. SECURITY CLASSIFICATION OF REPORT: UNCLASSIFIED
18. SECURITY CLASSIFICATION OF THIS PAGE: UNCLASSIFIED
19. SECURITY CLASSIFICATION OF ABSTRACT: UNCLASSIFIED
20. LIMITATION OF ABSTRACT: UL

DTIC STANDARD FORM 298

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input checked="" type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

PREFACE

EFFECTIVE 1 JULY 1988, THE SURFACE OBSERVATION CLIMATIC SUMMARIES (SOCS) REPLACED TWO OTHER USAFETAC PRODUCTS OF LONG STANDING: THE RUSSWO (REVISED UNIFORM SUMMARY OF SURFACE WEATHER OBSERVATIONS) AND LISOCS (LIMITED SURFACE OBSERVATION CLIMATIC SUMMARY). RUSSWOS AND LISOCS NOW IN EXISTENCE WILL CONTINUE TO BE USED UNTIL THEY ARE EVENTUALLY REPLACED BY SOCS.

THIS PRODUCT HAS BEEN ISSUED IN OTHER FORMS UNDER SEVERAL OTHER NAMES. IT WAS INTRODUCED IN THE EARLY 1940'S AS THE "SFCSUM," OR "SURFACE SUMMARY." THE ORIGINAL "USSWO," OR "UNIFORM SUMMARY OF SURFACE WEATHER OBSERVATIONS," DEBUTED IN 1946. THE USSWO GRADUALLY EVOLVED INTO THE "RUSSWO" AND THE "LISOCS." IT FINALLY BECAME THE NEW "SURFACE OBSERVATION CLIMATIC SUMMARIES" OR "SOCS" IN JULY 1988.

THE SOCS (LIKE ITS PREDECESSORS) IS PREPARED BY USAFETAC'S OPERATING LOCATION A AT ASHEVILLE, NC 28801-2723. HERE, CLIMATOLOGISTS USE STATE-OF-THE-ART COMPUTER TECHNOLOGY TO SUMMARIZE WEATHER OBSERVATIONS COLLECTED FROM SELECTED MILITARY, CIVILIAN, AND FOREIGN REPORTING STATIONS. SUMMARIES ARE PREPARED FROM DATA THAT HAS BEEN COLLECTED, QUALITY-CONTROLLED, AND STORED IN OL-A'S WORLDWIDE SURFACE WEATHER OBSERVATION DATABASE.

ALTHOUGH PREVIOUS VERSIONS OF THIS PRODUCT ONLY OFFERED SIX PARTS, SOCS PROVIDES EIGHT (A-H). THE ADDITIONS ARE THE CROSSWIND AND HEATING-COOLING DEGREE DAY SUMMARIES. PRECEDING EACH PART IS A BRIEF DISCUSSION OF THAT PARTICULAR PART, A DESCRIPTION OF THE DATA, AND AN EXPLANATION OF HOW THE DATA IS PRESENTED.

CONTENTS

INTRODUCTION.....	1
STATION PERIOD OF RECORD.....	1
DATA SOURCES.....	1
TERMS EXPLAINED.....	1
TIME CONVENTIONS.....	2
ABBREVIATIONS.....	2
SUMMARY DESCRIPTIONS.....	2
STATION HISTORY - *** NOTE: NOT AVAILABLE FOR THIS LOCATION ***	3
PART A - ATMOSPHERIC PHENOMENA SUMMARIES.....	A-1-1
SPECIFIED PHENOMENA	
PERCENT OCCURRENCE FREQUENCY (FROM HOURLY OBS).....	A-2-1
PERCENT OCCURRENCE FREQUENCY (FROM SOD DATA).....	A-3-1
PERCENT OCCURRENCE FREQUENCY (THUNDERSTORMS).....	A-4-1
VERSUS WIND DIRECTION--PERCENT OCCURRENCE FREQUENCY.....	A-5-1
PART B - PRECIPITATION, SNOWFALL, AND SNOW DEPTH.....	B-1-1
PRECIPITATION	
PERCENT OCCURRENCE FREQUENCY.....	B-2-1
MONTHLY TOTALS.....	B-2-2
DAILY EXTREMES.....	B-2-3
SNOWFALL	
PERCENT OCCURRENCE FREQUENCY.....	B-3-1
MONTHLY TOTALS.....	B-3-2
DAILY EXTREMES.....	B-3-3
SNOW DEPTH	
PERCENT OCCURRENCE FREQUENCY.....	B-4-1
DAILY EXTREMES.....	B-4-2
SNOWFALL/SNOW DEPTH	
FIRST AND LAST DAYS OF OCCURRENCE BY SNOW-YEAR.....	B-5-1
PART C - SURFACE WIND	
PEAK WINDS (FROM SOD DATA).....	C-2-1
PEAK WINDS--PERCENT OCCURRENCE FREQUENCY (FROM SOD DATA).....	C-3-1
WIND DIRECTION VS WIND SPEED--POF (FROM HOURLY OBS).....	C-4-1
PART D - CEILING, VISIBILITY AND SKY COVER	
CEILING VS VISIBILITY--POF (FROM HOURLY OBS).....	D-2-1
SKY COVER--POF (FROM HOURLY OBS).....	D-3-1

PART E - TEMPERATURE AND RELATIVE HUMIDITY.....	E-1-1
TEMPERATURES--CUMULATIVE POF (FROM SOD DATA)	
MAXIMA.....	E-2-1
MINIMA.....	E-2-2
MEAN.....	E-2-3
MONTHLY TEMPERATURES (FROM SOD DATA)	
MAXIMA.....	E-3-1
MINIMA.....	E-3-2
MEAN.....	E-4-1
DRY BULB, WET BULB, DEW POINT TEMPERATURES (FROM HOURLY OBS)	
DRY BULB.....	E-5-1
WET BULB.....	E-5-2
DEW POINT.....	E-5-3
RELATIVE HUMIDITY (FROM HOURLY OBS)	
CUMULATIVE PERCENT OCCURRENCE FREQUENCY.....	E-6-1
PART F - PRESSURE (FROM HOURLY OBS).....	F-1-1
SEA LEVEL PRESSURE.....	F-2-1
ALTIMETER SETTING.....	F-3-1
STATION PRESSURE.....	F-4-1
PART G - CROSSWIND SUMMARIES (FROM HOURLY OBS).....	G-1-1
PERCENT OCCURRENCE FREQUENCY.....	G-2-1
PART H - DEGREE DAY SUMMARIES (FROM HOURLY OBS).....	H-1-1
HEATING DEGREE DAYS.....	H-2-1
COOLING DEGREE DAYS.....	H-3-1

INTRODUCTION

STATION PERIOD OF RECORD.

HOURLY OBSERVATIONS: JUN 79 - MAY 89 (AIRWAYS).

SUMMARY OF DAY DATA: NOV 48 - FEB 63 (FULL TIME).

SUMMARY OF DAY DATA: MAR 63 - NOV 71, JUL 82 - MAY 89 (PART TIME).

HOURS SUMMARIZED: 00 - 23 LST (4811-6302), 06 - 22 LST (6303-7111, 7906-8905)

DATA SOURCES. THESE SUMMARIES ARE COMPILED FROM "HOURLY OBSERVATIONS" AND/OR SUMMARY OF DAY DATA," DEPENDING ON THE PHENOMENA OR OCCURRENCE BEING SUMMARIZED. THE TWO SOURCES ARE DEFINED IN "TERMS EXPLAINED."

TERMS EXPLAINED:

BIVARIATE DISTRIBUTION: A BIVARIATE DISTRIBUTION GIVES THE JOINT DISTRIBUTIONS OF TWO RELATED VARIABLES. AN EXAMPLE IS THE BIVARIATE DISTRIBUTION OF CEILING AND VISIBILITIES IN PART D. EACH ROW AND EACH COLUMN OF A BIVARIATE DISTRIBUTION IS A FREQUENCY DISTRIBUTION. JOINT FREQUENCIES ARE FOUND AT THE ROW-COLUMN INTERSECTIONS.

HOURLY OBSERVATIONS: ALL RECORD OR RECORD-SPECIAL OBSERVATIONS ON AWS FORMS 10/10A (OR EQUIVALENT) AT SCHEDULED HOURLY INTERVALS.

SUMMARY OF DAY (SOD) DATA: DATA COMPILED FROM ALL AVAILABLE OBSERVATIONAL SOURCES, INCLUDING HOURLY OBSERVATIONS, SPECIAL OBSERVATIONS, REMARKS, AND ACTUAL "SUMMARY OF DAY" DATA RECORDED IN COLUMNS 44-73 OF AWS FORMS 10/10A (OR EQUIVALENT) FOR ANY GIVEN DAY. NOTE: EXTREMES OCCURRING DURING NON-OPERATIONAL HOURS AND/OR DAYS ARE NOT REFLECTED IN THESE SUMMARIES.

MEAN: THE SUM OF ALL THE VALUES DIVIDED BY THE NUMBER OF VALUES.

MEASURABLE AMOUNT: ANY PRECIPITATION OR SNOWFALL AMOUNT GREATER THAN A TRACE.

MEDIAN: THE MIDDLE VALUE WHEN THE VALUES ARE IN ASCENDING ORDER. IF THE NUMBER OF VALUES IS EVEN, THE MEDIAN IS HALFWAY BETWEEN THE TWO MIDDLE VALUES.

PERCENT OCCURRENCE FREQUENCY (POF): IN STATISTICS, FREQUENCY IS THE NUMBER OF TIMES A GIVEN COUNT OR EVENT OCCURS. IN THE SOCS, THIS IS EXPRESSED AS THE PERCENT OCCURRENCE FREQUENCY (POF), WHERE THE FREQUENCY (NUMBER OF OCCURRENCES) IS GIVEN AS A PERCENT OF ALL POSSIBLE OCCURRENCES IN THE SAMPLE (PERIOD SUMMARIZED). FOR EXAMPLE, IF SNOW FELL ON 5 OUT OF 100 DAYS WE COULD EXPRESS THE "PERCENT OCCURRENCE FREQUENCY" OF SNOW AS 5 PERCENT OVER THE 100-DAY PERIOD. MAY BE USED INTERCHANGEABLY WITH "PERCENT FREQUENCY OF OCCURRENCE."

PERIOD OF RECORD: THE SIZE OF THE OBSERVATIONAL DATA SAMPLE, IN YEARS.

PRECIPITATION: A TERM THAT INCLUDES BOTH LIQUID PRECIPITATION AND WATER EQUIVALENT.

STANDARD DEVIATION: A MEASURE OF DISPERSION ON THE VARIABILITY OF THE QUANTITY CONCERNED ABOUT ITS ARITHMETIC MEAN. THE LARGER THE STANDARD DEVIATION, THE GREATER THE VARIABILITY.

TIME CONVENTIONS: ALL TIMES IN THE SOCS ARE EXPRESSED IN LOCAL STANDARD TIME (LST). USERS SHOULD MAKE ADJUSTMENTS FOR DAYLIGHT SAVING TIMES IN THEIR AREAS. IN SUMMARIES THAT SHOW DIURNAL VARIATIONS, THE DATA IS SUMMARIZED USING THE FOLLOWING STANDARD 3-HOUR PERIODS (ALL LST):

0000-0200	1200-1400
0300-0500	1500-1700
0600-0800	1800-2000
0900-1100	2100-2300

NOTE 1. DURING PART TIME PERIODS, THE FIRST AND LAST 3-HOUR PERIODS MAY HAVE SIGNIFICANT SHORTFALLS IN OBSERVATION COUNTS.

ABBREVIATIONS USED:

AMT	AMOUNT	LT	LESS THAN
ANN	ANNUAL	M	METER
BARO	BAROMETER	MB	MILLIBAR
C	CENTIGRADE (CELSIUS)	MPS	METERS PER SECOND
DEG	DEGREE	MSL	MEAN SEA LEVEL
DB	DRY BULB TEMPERATURE	MEAS	MEASURABLE
DP	DEW POINT TEMPERATURE	NO.	NUMBER
EQ	EQUAL	OBS	OBSERVATION
F	FAHRENHEIT	OBST	OBSTRUCTION
FRZG	FREEZING	POF	PERCENT OCCURRENCE FREQUENCY
FT	FEET	PRECIP	PRECIPITATION
GE	GREATER THAN OR EQUAL TO	SD	STANDARD DEVIATION
GMT	GREENWICH MEAN TIME	SOD	SUMMARY OF DAY
GT	GREATER THAN	TEMP	TEMPERATURE
HG	INCHES OF MERCURY	TSTM	THUNDERSTORM
HT	HEIGHT	VSBY	VISIBILITY
KTS	KNOTS	VSN	VISION
LE	LESS THAN OR EQUAL TO	WB	WET BULB TEMPERATURE
LST	LOCAL STANDARD TIME	WBAN	AWS FORM 10/10A
		UTC	*COORDINATED UNIVERSAL TIME

SUMMARY DESCRIPTION: A BRIEF DESCRIPTION OF THE DATA PRECEDES EACH PART IN THE SOCS.

* UTC REPLACED GMT ON 1 AUGUST 1988

STATION NO. ON SUMMARY	STATION NAME	LATITUDE	LONGITUDE	FLD ELEV (FT)	CALL SIGN	MO NMBR
747240	GILA BEND AAF, AZ	N 32 53	W 112 43	858	KGBN	74724

STATION LOCATION AND INSTRUMENTATION HISTORY									
Nmbr of Loc	GEOGRAPHICAL LOCATION & NAME	Type of Station	At This Location		LATITUDE	LONGITUDE	Elev Above MSL		OBS PER DAY
			From	To			FLD (FT)	BARO (FT)	
1	Gila Bend Airport, AZ	CAA	Nov 48	FEB 62	N 32 53	W 112 43	853	857	24
2	SAME	SAME	MAR 63	NOV 71	SAME	SAME	SAME	SAME	12-18
3	Gila Bend Aux AF, AZ	AF	SEP 68	Apr 69	N 32 56	W 112 41	846	Same	12-18
4	Gila Bend AAF, AZ	AAF	May 69	Feb 83	Same	W 112 42	858	Same	12-18
5	Same	AAF	Feb 83	Jan 88	N 32 53	W 112 43	Same	859	12-18

*** HOURLY OBSERVATIONS FOR SOCS (POR: 7906-8905) TAKEN AT GILA BEND AAF BY USAF/AWS. ***

*** SUMMARY OF DAY DATA FOR SOCS DERIVED FROM THE FOLLOWING SOURCES:

4811-6302 (CAA STATION - FULL TIME): MAX/MIN THERMOMETERS, RAIN GAUGE IN USE. NO PEAK WIND EQUIPMENT.

6303-7111 (CAA STATION - PART TIME): MAX/MIN THERMOMETERS, RAIN GAUGE IN USE. NO PEAK WIND EQUIPMENT.

6809-8206 (AAF STATION - PART TIME): MOST OBSERVATION ELEMENTS UNAVAILABLE - POR NOT USED IN SOCS.

8207-8905 (AAF STATION - PART TIME): NO MAX/MIN THERMOMETERS, HOURLY TEMPERATURE DATA AVAILABLE. RAIN GAUGE IN USE. PEAK WIND DATA AVAILABLE 8602-8905.

Nmbr of Loc	Date of Change	SURFACE WIND EQUIPMENT INFORMATION				REMARKS, ADDITIONAL EQUIP- MENT, OR REASON FOR CHANGE
		LOCATION	TYPE OF TRANSMITTER	TYPE OF RECORDER	HT ABOVE GROUND	
1	Nov 48	N/A	N/A	N/A	N/A	
2	May 69	Same	AN/GMQ-20	Same	13 ft	
3	Jan 88	Same	Same	Same	12 ft	

PPPPPPPP	AAAAAA	RRRRRRRR	TTTTTTTTTT	AAAAAA
PPPPPPPP	AAAAAAA	RRRRRRRR	TTTTTTTTTT	AAAAAAA
PP PP	AA AA	RR RR	TT	AA AA
PP PP	AA AA	RR RR	TT	AA AA
PPPPPPPP	AA AA	RRRRRRRR	TT	AA AA
PPPPPPPP	AAAAAAAAA	RRRRRRRR	TT	AAAAAAAAA
PP	AAAAAAAAA	RR RR	TT	AAAAAAAAA
PP	AA AA	RR RR	TT	AA AA
PP	AA AA	RR RR	TT	AA AA
PP	AA AA	RR RR	TT	AA AA

PART A

ATMOSPHERIC PHENOMENA SUMMARIES

THIS PART SUMMARIZES SPECIFIED ATMOSPHERIC PHENOMENA IN CATEGORIES AS FOLLOWS:

THUNDERSTORMS: ALL REPORTED OCCURRENCES OF THUNDERSTORMS, TORNADOES, AND WATERSPOUTS.

LIQUID PRECIPITATION: RAIN OR DRIZZLE FALLING TO THE GROUND BUT NOT FREEZING.

FREEZING PRECIPITATION: FREEZING RAIN OR FREEZING DRIZZLE (GLAZE).

FROZEN PRECIPITATION: SNOW, SNOW PELLETS, SLEET, SNOW GRAINS, ICE CRYSTALS, ICE PELLETS. IN JANUARY 1968, SNOW PELLETS BECAME KNOWN AS SMALL HAIL.

HAIL: ALL OCCURRENCES OF HAIL.

ALL PRECIPITATION: INCLUDES ALL OBSERVATIONS REPORTING PRECIPITATION. BECAUSE MORE THAN ONE TYPE OF PRECIPITATION MAY BE INCLUDED IN THE SAME OBSERVATION, THE SUM OF PERCENTAGES IN THE INDIVIDUAL CATEGORIES MAY EXCEED THE PERCENTAGES IN THIS CATEGORY.

FOG: INCLUDES ALL REPORTED FOG, ICE FOG, AND GROUND FOG.

SMOKE AND/OR HAZE: SMOKE, HAZE, OR COMBINATIONS OF THE TWO.

BLOWING SNOW: ALL REPORTS OF BLOWING SNOW, INCLUDING DRIFTING SNOW, WHEN REPORTED.

DUST AND/OR SAND: DUST, SAND, BLOWING DUST, BLOWING SAND, OR COMBINATIONS OF THESE.

BLOWING SPRAY: THE "ALL OBSTRUCTIONS TO VISION" CATEGORY ACCOUNTS FOR BLOWING SPRAY, IF AND AS REPORTED.

ALL OBSTRUCTIONS TO VISION: THIS CATEGORY INCLUDES ALL REPORTS OF OBSTRUCTIONS TO VISION. SINCE THE OCCURRENCE OF MORE THAN ONE OBSTRUCTION TO VISION MAY BE REPORTED IN THE SAME OBSERVATION, THE SUM OF THE PERCENTAGES IN THE INDIVIDUAL CATEGORIES MAY EXCEED THE PERCENTAGES IN THIS CATEGORY.

SPECIFIED PHENOMENA--PERCENT OCCURRENCE FREQUENCY.

THESE TABLES GIVE THE PERCENT OCCURRENCE FREQUENCY (POF) FOR THE ATMOSPHERIC PHENOMENA SHOWN. THE DATA WAS TAKEN FROM HOURLY OBSERVATIONS ONLY, AND IS SUMMARIZED AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

SPECIFIED PHENOMENA--PERCENT OCCURRENCE FREQUENCY (POF).

THIS TABLE IS THE ONLY ONE IN PART A THAT IS PRODUCED FROM SUMMARY OF DAY DATA. DATA IS SUMMARIZED MONTHLY AND ANNUALLY FOR ALL YEARS COMBINED.

THUNDERSTORMS--PERCENT OCCURRENCE FREQUENCY.

THIS TABLE GIVES THE PERCENT OCCURRENCE FREQUENCY OF THUNDERSTORMS REPORTED ON THE HOURLY OBSERVATION. DATA IS SUMMARIZED SAME AS FOR FIRST TABLE IN THIS PART.

SPECIFIED PHENOMENA VS WIND DIRECTION--PERCENT OCCURRENCE FREQUENCY.

THESE TABLES INCLUDE SUMMARY OF MONTH FOR ALL HOURS AND YEARS COMBINED. WIND DIRECTION CATEGORIES ARE AS SPECIFIED BY THE LOCAL WEATHER STATION.

NOTE 1: REPORTING PRACTICES HAVE CHANGED WITH TIME. METAR AND SYNOPTIC REPORTING STATIONS RECORD (ON AWS FORMS 10/10A) AND TRANSMIT LONGLINE ONLY THE HIGHEST ORDER ATMOSPHERIC PHENOMENA THAT AFFECTS VISIBILITY. METAR STATIONS STARTED THIS PROCEDURE IN JANUARY 1968, BUT SYNOPTIC STATIONS ALWAYS DID IT THAT WAY. IN JANUARY 1970, METAR STATIONS STARTED RECORDING ALL ATMOSPHERIC PHENOMENA THAT AFFECTED VISIBILITY, BUT CONTINUED TO TRANSMIT ONLY THE HIGHEST ORDER. FOR EXAMPLE, IF THE RECORDED OBSERVATION INCLUDED RAIN, FOG AND HAZE, ONLY THE RAIN WAS TRANSMITTED. BECAUSE OF THESE PROCEDURES, THE USAFETAC DATABASE WOULD SHOW ONLY RAIN AS AN OBSTRUCTION. THEREFORE, THE OBSTRUCTION TO VISION (AND TO A LESSER EXTENT, PRECIPITATION) SUMMARIES FOR METAR AND SYNOPTIC STATIONS ARE HIGHLY QUESTIONABLE.

NOTE 2: FOREIGN METAR REPORTING STATIONS FREQUENTLY DO NOT TRANSMIT OBSTRUCTIONS TO VISION WHEN VISIBILITIES EXCEED 1000 METERS.

NOTE 3: A VALUE OF ".0" IN ANY SUMMARY REPRESENTS ONE OR MORE OCCURRENCES THAT, IN AGGREGATE, AMOUNT TO LESS THAN .05 PERCENT.

NOTE 4: DURING PART TIME PERIODS, THESE TABLES MAY NOT ACCURATELY REFLECT NIGHTTIME AND/OR WEEKEND OCCURRENCES OF CERTAIN PHENOMENA.

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL CBST TO VSN	TOTAL NO. OF OBS
00-02												0
03-05												0
06-08		1.6				1.6	.6				2.2	635
09-11	.1	2.4				2.4	1.4	.1		.3	4.2	709
12-14		3.3				3.3	.3	.4			4.0	693
15-17		2.6				2.6					2.6	645
18-20		3.1				3.1	.2				3.3	424
21-23												86
ALL HOURS	.0	2.5				2.5	.5	.1		.1	3.2	3192

MONTH: FEB

00-02												0
03-05												0
06-08		2.2				2.2	.7				2.9	593
09-11		2.9				2.9	.3				3.2	681
12-14		2.6				2.6	.2				2.7	663
15-17		3.7				3.7	.2				3.9	615
18-20		3.1				3.1					3.1	414
21-23		4.4				4.4					4.4	113
ALL HOURS		3.0				3.0	.3				3.2	3079

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR

HOURS (LST)	ISTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
00-02												0
03-05												0
06-08	.1	2.5				2.5	.1				2.7	712
09-11	.2	2.8				2.8	.1				3.0	812
12-14	.3	4.5				4.5				.3	4.8	795
15-17	.3	2.2				2.2				.3	2.5	713
18-20		2.1				2.1				.2	2.3	482
21-23		4.0				4.0					4.0	150
ALL HOURS	.2	3.0				3.0	.1			.1	3.2	3664

MONTH: APR

00-02												0
03-05												0
06-08		.9				.9					.9	639
09-11	.1	1.0				1.0					1.0	718
12-14	.3	1.3				1.3				.3	1.6	708
15-17	.3	1.8				1.8				.2	2.0	666
18-20		1.1				1.1				.2	1.3	470
21-23	.6											179
ALL HOURS	.2	1.2				1.2				.1	1.3	3380

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
00-02												0
03-05												0
06-08	.2	.2				.2					.2	645
09-11								.1			.1	702
12-14												691
15-17	.8	1.0				1.0					1.0	623
18-20	1.1	.4				.4					.4	470
21-23	.8	.8				.8					.8	241
ALL HOURS	.4	.3				.3		.0			.4	3372

MONTH: JUN

00-02												0
03-05												0
06-08	.3	.2				.2					.2	653
09-11		.1				.1					.1	711
12-14												682
15-17	1.0	.5				.5					.5	623
18-20	.6	.8				.8				.2	1.0	488
21-23	.4	1.4				1.4				.7	2.1	281
ALL HOURS	.3	.4				.4				.1	.5	3438

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
00-02												0
03-05												0
06-08	1.4	1.6				1.6					1.6	623
09-11	1.4	2.4				2.4					2.4	665
12-14	1.7	2.1				2.1					2.1	656
15-17	1.9	1.9				1.9					1.9	620
18-20	4.4	2.3				2.3				.2	2.6	427
21-23	2.4	1.9				1.9				.5	2.4	211
ALL HOURS	2.0	2.1				2.1				.1	2.1	3202

MONTH: AUG

00-02												0
03-05												0
06-08	.5	1.8				1.8					1.8	664
09-11	.4	.8				.8					.8	733
12-14	2.4	1.1				1.1					1.1	704
15-17	4.7	2.6				2.6					2.6	655
18-20	8.2	4.9				4.9				.4	5.4	485
21-23	2.2	1.3				1.3					1.3	224
ALL HOURS	2.9	2.0				2.0				.1	2.1	3465

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSM	TOTAL NO. OF OBS
00-02												0
03-05												0
06-08	.8	1.7				1.7				.2	1.8	605
09-11	1.3	2.5				2.5					2.5	682
12-14	.6	2.1				2.1				.3	2.5	652
15-17	2.0	2.2				2.2				.2	2.3	599
18-20	2.0	1.7				1.7					1.7	403
21-23	.7	.7				.7					.7	150
ALL HOURS	1.3	2.0				2.0				.1	2.1	3091

MONTH: OCT

00-02												0
03-05												0
06-08		.9				.9					.9	649
09-11	.3	.3				.3					.3	701
12-14	1.0	1.9				1.9					1.9	694
15-17	.3	1.5				1.5				.2	1.7	653
18-20	.7	.9				.9		.2			1.1	448
21-23												135
ALL HOURS	.4	1.1				1.1		.0		.0	1.1	3280

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF HOURS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV

HOURS (LST)	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
00-02												0
03-05												0
06-08		1.6				1.6	.9				2.4	579
09-11		1.2				1.2	.6				1.8	662
12-14		1.4				1.4		.2		.5	2.0	640
15-17		1.4				1.4				.3	1.7	575
18-20		.8				.8				.3	1.1	371
21-23		1.7				1.7					1.7	59
ALL HOURS		1.3				1.3	.3	.0		.2	1.9	2886

MONTH: DEC

00-02												0
03-05												0
06-08		3.5				3.5	2.4				5.9	622
09-11	.1	3.3				3.3	2.2				5.5	696
12-14	.3	3.8				3.8	1.4	.2			5.3	660
15-17		3.0				3.0	.7	.2		.2	4.0	594
18-20	.3	4.0				4.0	1.5				5.5	329
21-23		1.5				1.5					1.5	67
ALL HOURS	.1	3.4				3.4	1.6	.1		.0	5.2	2968

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF VARIOUS ATMOSPHERIC PHENOMENA
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
HOURS: ALL

MONTH	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
JAN	.0	2.5				2.5	.5	.1		.1	3.2	3192
FEB		3.0				3.0	.3				3.2	3079
MAR	.2	3.0				3.0	.1			.1	3.2	3664
APR	.2	1.2				1.2				.1	1.3	3380
MAY	.4	.3				.3		.0			.4	3372
JUN	.3	.4				.4				.1	.5	3438
JUL	2.0	2.1				2.1				.1	2.1	3202
AUG	2.9	2.0				2.0				.1	2.1	3465
SEP	1.3	2.0				2.0				.1	2.1	3091
OCT	.4	1.1				1.1		.0		.0	1.1	3280
NOV		1.3				1.3	.3	.0		.2	1.9	2886
DEC	.1	3.4				3.4	1.6	.1		.0	5.2	2968
ANNUAL	.7	1.8				1.8	.2	.0		.1	2.2	39017

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF DAYS WITH VARIOUS ATMOSPHERIC PHENOMENA
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4901-7111,8207-8905
MONTH: ALL HOURS: ALL

MONTH	TSTMS	LIQUID PRECIP	FREEZ PRECIP	FROZEN PRECIP	HAIL	ALL PRECIP	FOG	SMOKE &/OR HAZE	BLOWING SNOW	DUST &/OR SAND	ALL OBST TO VSN	TOTAL NO. OF OBS
JAN	.5	13.3				13.3	2.4	.2			14.5	882
FEB	1.1	10.7		.1	.2	10.8	1.0				11.2	812
MAR	1.4	9.9			.2	9.9	.3	.1		.1	10.1	903
APR	1.1	5.3			.1	5.3		.4		.1	5.6	854
MAY	.8	2.9				2.9		.1		.7	3.6	882
JUN	2.8	4.1				4.1		.1		.2	4.3	833
JUL	18.2	18.4			.3	18.4	.1	.1		1.5	18.7	873
AUG	20.6	21.4			.3	21.4	.5	.1		.3	22.0	883
SEP	8.1	10.2			.2	10.2	.2	.1		.4	10.6	852
OCT	3.3	9.4				9.4	.3	.1			9.7	880
NOV	.9	9.0				9.0	1.3	.1		.5	10.2	845
DEC	.9	11.7			.2	11.7	4.0	.1			13.7	855
ANNUAL	5.0	10.6		.0	.1	10.6	.8	.1		.3	11.2	10354

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF THUNDERSTORMS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 MAY 89

HOURS (LST)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
00-02												
03-05												
06-08			.1		.2	.3	1.4	.5	.8			
09-11	.1		.2	.1			1.4	.4	1.3	.3		.1
12-14			.3	.3			1.7	2.4	.6	1.0		.3
15-17			.3	.3	.8	1.0	1.9	4.7	2.0	.3		
18-20					1.1	.6	4.4	8.2	2.0	.7		.3
21-23				.6	.8	.4	2.4	2.2	.7			
ALL HOURS	.0		.2	.2	.4	.3	2.0	2.9	1.3	.4		.1
TOTAL OBS	3192	3079	3664	3380	3372	3438	3202	3465	3091	3280	2886	2968

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: ALL

PHENOMENA	CALM	VARIABLE	330 - 059	060 - 149	150 - 239	240 - 329	NO OF OBS	
TSTMS						100.0	1	
LIQUID PRECIP	24.1		11.4	21.5	19.0	24.1	79	
FREEZING PRECIP								
FROZEN PRECIP								
FOG	52.9		29.4	11.8		5.9	17	
FOG WITH VIS GE 1/2 MILES	52.9		29.4	11.8		5.9	17	
TOTAL OBS	1192	0	906	365	330	396	0	3189

MONTH: FEB HOURS: ALL

TSTMS								
LIQUID PRECIP	18.7		27.5	17.6	19.8	16.5	91	
FREEZING PRECIP								
FROZEN PRECIP								
FOG	75.0		12.5		12.5		8	
FOG WITH VIS GE 1/2 MILES	75.0		12.5		12.5		8	
TOTAL OBS	1044	0	862	294	371	506	0	3077

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: ALL

PHENOMENA	CALM	VARIABLE	330 - 059	060 - 149	150 - 239	240 - 329	NO OF OBS
TSTMS	16.7		33.3	16.7		33.3	6
LIQUID PRECIP	23.3		14.6	10.7	32.0	19.4	103
FREEZING PRECIP							
FROZEN PRECIP							
FOG				50.0	50.0		2
FOG WITH VIS GE 1/2 MILES				50.0	50.0		2
TOTAL OBS	991	0	671	252	692	1056	3662

MONTH: APR HOURS: ALL

TSTMS				16.7	50.0	33.3	6
LIQUID PRECIP	2.6		10.5	13.2	42.1	31.6	38
FREEZING PRECIP							
FROZEN PRECIP							
FOG							
FOG WITH VIS GE 1/2 MILES							
TOTAL OBS	760	0	533	278	725	1082	3378

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: ALL

PHENOMENA	CALM	VARIABLE	330 - 059	060 - 149	150 - 239	240 - 329	NO OF OBS
TSTMS	7.7		7.7	38.5	23.1	23.1	13
LIQUID PRECIP	20.0			20.0	20.0	40.0	5
FREEZING PRECIP							
FROZEN PRECIP							
FOG							
FOG WITH VIS GE 1/2 MILES							
TOTAL OBS	837	0	308	154	953	1119	3371

MONTH: JUN HOURS: ALL

TSTMS			41.7	25.0	25.0	8.3	12
LIQUID PRECIP			12.5	37.5	37.5	12.5	8
FREEZING PRECIP							
FROZEN PRECIP							
FOG							
FOG WITH VIS GE 1/2 MILES							
TOTAL OBS	890	0	336	181	788	1239	3434

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: ALL

PHENOMENA	CALM	VARIABLE	330 - 059	060 - 149	150 - 239	240 - 329	NO OF OBS
TSTMS	12.5		9.4	21.9	39.1	17.2	64
LIQUID PRECIP	21.6		10.8	29.7	29.7	8.1	37
FREEZING PRECIP							
FROZEN PRECIP							
FOG							
FOG WITH VIS GE 1/2 MILES							
TOTAL OBS	900	0	358	214	682	1046	3200

MONTH: AUG HOURS: ALL

TSTMS	9.9		9.9	22.8	29.7	27.7	101
LIQUID PRECIP	21.1		15.8	21.1	36.8	5.3	38
FREEZING PRECIP							
FROZEN PRECIP							
FOG							
FOG WITH VIS GE 1/2 MILES							
TOTAL OBS	1240	0	405	313	677	825	3460

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: ALL

PHENOMENA	CALM	VARIABLE	330 - 059	060 - 149	150 - 239	240 - 329	NO OF OBS
TSTMS	15.0		15.0	25.0	32.5	12.5	40
LIQUID PRECIP	30.4		13.0	17.4	17.4	21.7	46
FREEZING PRECIP							
FROZEN PRECIP							
FOG							
FOG WITH VIS GE 1/2 MILES							
TOTAL OBS	1064	0	509	360	478	679	3090

MONTH: OCT HOURS: ALL

TSTMS	7.1		14.3	42.9	14.3	21.4	14
LIQUID PRECIP	16.0		8.0	16.0	24.0	36.0	25
FREEZING PRECIP							
FROZEN PRECIP							
FOG							
FOG WITH VIS GE 1/2 MILES							
TOTAL OBS	1270	0	644	340	408	614	3276

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: ALL

PHENOMENA	CALM	VARIABLE	330 - 059	060 - 149	150 - 239	240 - 329	NO OF OBS	
TSTMS								
LIQUID PRECIP	31.6			18.4	31.6	18.4	38	
FREEZING PRECIP								
FROZEN PRECIP								
FOG	44.4				33.3	22.2	9	
FOG WITH VIS GE 1/2 MILES	33.3				33.3	33.3	6	
TOTAL OBS	1035	0	772	315	333	429	0	2884

MONTH: DEC HOURS: ALL

TSTMS			25.0			75.0		4
LIQUID PRECIP	24.5		27.6	27.6	8.2			98
FREEZING PRECIP								
FROZEN PRECIP								
FOG	41.7		35.4	10.4	4.2	8.3		48
FOG WITH VIS GE 1/2 MILES	41.7		35.4	10.4	4.2	8.3		48
TOTAL OBS	1085	0	946	343	242	348	0	2964

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCES OF ATMOSPHERIC PHENOMENA
VERSUS WIND DIRECTION FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTHS: ALL

PHENOMENA	CALM	VARIABLE	330 - 059	060 - 149	150 - 239	240 - 329	NO OF OBS
TSTMS	10.3		12.6	24.1	30.3	22.6	261
LIQUID PRECIP	21.8		16.3	19.5	23.9	18.5	606
FREEZING PRECIP							
FROZEN PRECIP							
FOG	46.4		27.4	9.5	8.3	8.3	84
FOG WITH VIS GE 1/2 MILES	45.7		28.4	9.9	7.4	8.6	81
TOTAL OBS	12308	0	7250	3409	6679	9339	0 38985

PPPPPPPP	AAAAAA	RRRRRRRR	TTTTTTTTTT	BBBBBBBBBB
PPPPPPPP	AAAAAAA	RRRRRRRR	TTTTTTTTTT	BBBBBBBBBB
PP PP	AA AA	RR RR	TT	BB BB
PP PP	AA AA	RR RR	TT	BB BB
PPPPPPPP	AA AA	RRRRRRRR	TT	BBBBBBBBBB
PPPPPPPP	AAAAAAAAA	RRRRRRRR	TT	BBBBBBBBBB
PP	AAAAAAAAA	RR RR	TT	BB BB
PP	AA AA	RR RR	TT	BB BB
PP	AA AA	RR RR	TT	BBBBBBBBBB
PP	AA AA	RR RR	TT	BBBBBBBBBB

PART B

PRECIPITATION, SNOWFALL, SNOW DEPTH SUMMARIES

ALL TABLES IN PART B ARE CREATED FROM SUMMARY OF DAY (SOD) DATA.

PERCENT OCCURRENCE FREQUENCY.

THESE TABLES GIVE THE PERCENT OCCURRENCE FREQUENCY OF PRECIPITATION, SNOWFALL AND SNOW DEPTH. DATA IS SUMMARIZED FOR ALL YEARS COMBINED. SUMMARIES INCLUDE THE PERCENT OF DAYS WITH MEASURABLE AMOUNTS, PERCENT OF DAYS WITH NO AMOUNTS, PERCENT OF DAYS WITH TRACES, AND PERCENT OF DAYS WITH SPECIFIED AMOUNTS. SUMMARIES ALSO PROVIDE AN OBSERVATION COUNT. A VALUE OF ".0" INDICATES ONE OR MORE OCCURRENCES THAT, IN AGGREGATE, AMOUNT TO LESS THAN .05 PERCENT.

MONTHLY TOTALS.

THESE TABLES GIVE THE TOTAL MONTHLY PRECIPITATION AND SNOWFALL RESPECTIVELY. THEY ARE SUMMARIZED BY MONTH FOR ALL YEARS. THE TABLES ALSO GIVE THE GREATEST AMOUNTS, LEAST AMOUNTS, MEAN, MEDIAN, STANDARD DEVIATIONS, AND TOTAL AVAILABLE OBSERVATIONS. AN ASTERISK (*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF THE DATA ARE AVAILABLE. AN ASTERISK ALSO DENOTES A YEAR(S) WITH ONE OR MORE MISSING AND/OR INCOMPLETE MONTHS. INCOMPLETE MONTHS/YEARS ARE NOT INCLUDED IN STATISTICAL COMPUTATIONS. NOTE: LEAST AMOUNTS ARE DERIVED FROM COMPLETE MONTHS/YEARS ONLY. ".00" MEANS NO PRECIPITATION FOR THE MONTH, ".0" MEANS NO SNOWFALL FOR THE MONTH.

DAILY EXTREMES.

THESE TABLES GIVE THE MAXIMUM DAILY REPORTED AMOUNTS (BY INDIVIDUAL YEAR-MONTH) FOR PRECIPITATION, SNOWFALL, AND SNOW DEPTH, RESPECTIVELY. THEY SHOW THE GREATEST AMOUNTS FOR EACH MONTH AND THE TOTAL NUMBER OF AVAILABLE OBSERVATIONS FOR EACH MONTH AND YEAR. AN ASTERISK (*) INDICATES A MONTH FOR WHICH LESS THAN 90% OF DATA ARE AVAILABLE. AN ASTERISK ALSO DENOTES A YEAR(S) WITH ONE OR MORE MISSING AND/OR INCOMPLETE MONTHS. ".00" MEANS NO PRECIPITATION FOR THE MONTH, ".0" MEANS NO SNOWFALL FOR THE MONTH, AND "0" MEANS NO SNOW DEPTH FOR THE MONTH.

SNOWFALL/SNOW DEPTH--FIRST AND LAST DAYS OF OCCURRENCE BY SNOW YEAR.

THIS SUMMARY GIVES THE FIRST AND LAST OCCURRENCES OF SNOWFALL AND SNOW DEPTH FOR THE SNOW-YEAR DURING THE PERIOD OF RECORD. FOR THIS SUMMARY, THE SNOW-YEAR IS CONSIDERED TO RUN FROM 1 AUGUST TO 31 JULY. TABLES SUMMARIZE THE DATA BY SNOW-YEAR, BY MONTH, AND BY DAY. THE FIRST (OR LAST) ENTRY IN COLUMN 69 OF AWS FORMS 10/10A (OR EQUIVALENT) AS EITHER A TRACE OR A MEASURABLE AMOUNT DEFINES THE FIRST (OR LAST) SNOWFALL FOR THE YEAR. THE FIRST (OR LAST) ENTRY IN COLUMN 69 OTHER THAN ".0" OR "TRACE" DEFINES THE FIRST (OR LAST) MEASURABLE SNOWFALL. FINALLY, THE 1200 GMT ENTRY COLUMN 70 OF AWS FORM 10/10A (OR EQUIVALENT) DEFINES THE FIRST (OR LAST) OCCURRENCE OF SNOW DEPTH. THE LAST SNOW DEPTH IS CONSIDERED THE LAST SNOW MELT. THIS SUMMARY IS NOT PROVIDED WHEN NO SNOWFALL OCCURS DURING THE GIVEN PER.

NOTE 1. IF THE MINIMUM AMOUNT RECORDED IN THE MONTHLY TOTALS OR DAILY EXTREMES IS A TRACE, THE WORD "TRACE" WILL APPEAR IN THE APPROPRIATE COLUMN.

NOTE 2. TABLES INCLUDE STATISTICAL DATA ONLY WHEN FIVE (5) OR MORE SETS OF COMPLETE MONTHS ARE AVAILABLE.

NOTE 3. THE OBSERVATION COUNTS OR THE STATION HISTORY MIGHT PROVIDE CLUES AS TO WHY CERTAIN DATA ARE MISSING. FOR EXAMPLE, ONLY A FEW MISSING OBSERVATIONS MIGHT IMPLY MISSING DATA BECAUSE OF EQUIPMENT MALFUNCTION, BUT MORE THAN SEVERAL MISSING OBSERVATIONS USUALLY MEANS THE STATION IS (OR HAS BEEN) CLOSED.

NOTE 4. IN DAILY AND MONTHLY AMOUNTS SUMMARIES, THE LAST ENTRY ON THE PAGE GIVES THE GREATEST AMOUNT FOR THE PERIOD OF RECORD.

NOTE 5. BEFORE JANUARY 1956, SNOWFALL OCCURRENCES IN THE SUMMARY OF DAY INCLUDED HAIL.

NOTE 6. SNOW DEPTH REPORTING TIMES FOR USAF, NAVY AND CIVIL STATIONS ARE AS FOLLOWS:

AIR FORCE		NAVY AND NATIONAL WEATHER SERVICE	
THROUGH 1945:	0800 LST	THROUGH JUN 1952:	0030 GMT
JAN 1946 TO MAY 1957:	1230 LST	JUN 1952 TO MAY 1957:	1230 GMT
JUN 1957 TO PRESENT:	1200 GMT	JUN 1957 TO PRESENT:	1200 GMT

NOTE 7. 24-HOUR PRECIPITATION (INCLUDING SNOWFALL AND SNOW DEPTH) VALUES DERIVED FROM PART TIME PERIODS MAY NOT REFLECT TRUE 24-HOUR AMOUNTS. RECORDED AMOUNTS FOLLOWING WEEKENDS AND/OR HOLIDAYS FREQUENTLY REPRESENT AMOUNTS MEASURED FOR PERIODS GREATER THAN 24 HOURS. IN ADDITION, 24-HOUR AMOUNTS MAY NOT REPRESENT THE STANDARD CLIMATOLOGICAL 24-HOUR "MIDNIGHT TO MIDNIGHT" AMOUNT. DATA FROM PART TIME PERIODS MAY NOT ACCURATELY REFLECT NIGHTTIME PRECIPITATION EVENTS.

CONVERSIONS:

- 1 INCH = 25.39998 MILLIMETERS
- 1 MILLIMETER = .03937 INCHES

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF PRECIPITATION IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111, 8207-9905
MONTH: ALL HOURS: ALL

AMOUNTS (INCHES)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
NONE	83.8	86.7	88.5	93.4	96.1	95.7	77.3	73.5	86.9	88.0	89.8	86.5	87.1
TRACE	4.1	4.9	3.1	2.2	2.0	2.2	9.0	9.1	5.0	4.1	3.1	3.5	4.4
.01	1.7	.6	.4	.6	.2	.2	1.5	1.6	.7	.8	.1	.7	.8
.02-.05	3.9	1.4	2.8	1.5	.5	1.0	3.8	4.8	1.9	2.2	2.2	1.7	2.3
.06-.10	1.2	1.1	1.5	.6	.1	.7	2.7	2.9	1.6	1.0	.7	1.1	1.3
.11-.25	2.6	2.2	1.6	.8	.6	.1	2.7	2.8	1.4	1.6	1.8	2.4	1.7
.26-.50	1.5	2.0	1.1	.7	.3		2.1	2.6	.8	.8	1.3	2.5	1.3
.51-1.00	.9	1.0	.7	.2	.1		.7	1.8	1.2	1.0	.8	1.2	.8
1.01-2.50	.3	.1	.2				.2	.8	.4	.1	.2	.3	.2
2.51-5.00								.1	.1				.0
5.01-10.00													
10.01-20.00													
OVER 20.00													
DAYS WITH MEAS AMTS	12.1	8.4	8.4	4.4	1.8	2.1	13.7	17.5	8.1	7.5	7.1	10.0	8.5
TOTAL NO. OF OBSERVATIONS	882	812	913	861	882	809	878	882	853	880	876	882	10410

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

TOTAL MONTHLY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
48											.00	.66*	.66*
49	2.02	.05	.83	.02	.00	.04	.17	.42	2.00	.10	.30	.76	6.71
50	.18	.30	.26	.00	.00	TRACE	1.27	.48	.30	.00	.21	.04	3.04
51	.87	.14	.01	.52	.29	.00	1.10	5.61	.05	.16	.97	.35	10.07
52	.45	.46	2.53	.90	.00	.03	.77	1.76	.08	.00	1.80	.53	9.31
53	.07	.67	.10	.02	TRACE	.00	1.04	1.65	.00	TRACE	.03	TRACE	3.58
54	.06	.53	.81	.00	.21	.33	1.94	.13	.10	.02	.00	TRACE	4.13
55	1.78	TRACE	.00	.00	.00	.00	1.87	1.05	TRACE	.31	TRACE	.15	5.16
56	.22	.22	.00	TRACE	.00	.00	.55	.05	.05	.21	.00	.00	1.30
57	1.45	.05	.32	.28	.05	.01	.80	.33	.00	1.88	.04	.06	5.27
58	TRACE	1.36	.63	.24	TRACE	.01	.18	1.48	.16	.69	.25	.00	5.00
59	.06	.84	.00	.02	.00	TRACE	.05	1.18	.20	1.06	.25	2.64	6.30
60	.89	TRACE	.34	.00	.15	TRACE	.45	.68	.41	.76	.03	TRACE	3.71
61	.33	.00	.22	.00	TRACE	.10	.30	2.68	.40	.18	.05	.60	4.86
62	2.49	.49	.30	.00	.00	.07	TRACE	.03	1.92	TRACE	.06	.55	5.91
63	.03	.18	.28	.01	TRACE	.00	TRACE	1.15	.15	1.26	.43	.00	3.49
64	.18	.07	.08	.04	TRACE	TRACE	1.07	3.02	1.33	.86	.57	1.17	8.39
65	1.33	1.42	.66	1.11	.16	TRACE	.36	.38	.31	.08	.66	3.68	10.15
66	1.05	1.45	.02	.02	.07	.04	.16	1.65	1.23	.97	.36	.07	7.09
67	.18	TRACE	.16	.31	.05	.08	.84	.09	2.31	.40	1.40	2.97	8.79
68	.02	1.09	1.36	.03	.00	.00	.90	2.18	.14	.20	.20	.12	6.24
69	1.51	.78	.21	.02	1.33	.00	.15	1.28	.61	TRACE	1.78	.42	8.09
70	TRACE	.37	2.55	.01	.00	TRACE	.17	.22*	1.36	.06	.07	.00	4.81*
71	.00	.39	.00	.00	TRACE	.00	.27	2.72	.69	.19	TRACE		4.26*
82							1.77	.68*	1.11*	.02*	.71*	.80*	5.09*
83	.54*	1.09	1.03	.17*	.00*	*	.02*	2.65*	2.85*	.29*	.54*	1.38*	10.56*
84	.66*	.00	.00	.53*	.33*	TRACE*	1.51*	2.18*	.95*	TRACE*	.56*	3.81*	10.53*
85	.80	.69*	.29	.08*	TRACE*	.00*	.46*	.61*	.81*	1.27*	2.15*	1.19*	8.35*
86	.16*	1.14*	.88	.04*	.00*	.11*	2.05*	1.05*	.69*	1.22*	.10*	1.00*	8.44*
87	.48*	1.57*	.11	TRACE*	.45*	.11*	.06*	1.99*	.28*	.34*	1.91*	1.65*	8.95*
88	.57*	.41*	.03	.80*	TRACE*	.06*	.02*	1.01*	.00*	.69*	.21*	TRACE*	3.80*
89	1.55*	TRACE*	.18	.00*	.00*								1.73*

TOTAL MONTHLY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

THE GREATEST VALUE OF 5.61 OCCURRED ON 08/51

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

EXTREME DAILY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
48											.00	.43*	.43*
49	.60	.04	.58	.02	.00	.04	.09	.14	1.93	.03	.30	.42	1.93
50	.09	.20	.14	.00	.00	TRACE	.60	.48	.20	.00	.21	.04	.60
51	.56	.13	.01	.28	.26	.00	.56	3.00	.05	.08	.59	.18	3.00
52	.22	.29	.60	.40	.00	.03	.23	1.25	.08	.00	.50	.42	1.25
53	.04	.31	.10	.02	TRACE	.00	.32	.50	.00	TRACE	.02	TRACE	.50
54	.04	.53	.36	.00	.21	.24	1.43	.10	.10	.02	.00	TRACE	1.43
55	.46	TRACE	.00	.00	.00	.00	.90	.83	TRACE	.31	TRACE	.15	.90
56	.19	.22	.00	TRACE	.00	.00	.34	.05	.05	.18	.00	.00	.34
57	.40	.05	.21	.28	.05	.01	.30	.10	.00	.70	.02	.06	.70
58	TRACE	1.35	.39	.20	TRACE	.01	.18	.66	.16	.67	.25	.00	1.35
59	.06	.40	.00	.02	.00	TRACE	.03	.98	.20	.56	.25	.81	.98
60	.75	TRACE	.19	.00	.15	TRACE	.45	.35	.35	.45	.03	TRACE	.75
61	.30	.00	.15	.00	TRACE	.10	.10	.70	.40	.18	.05	.37	.70
62	1.73	.18	.25	.00	.00	.97	TRACE	.03	.99	TRACE	.02	.34	1.73
63	.03	.13	.28	.01	TRACE	.00	TRACE	.62	.13	1.10	.19	.00	1.10
64	.15	.07	.06	.04	TRACE	TRACE	.40	1.30	1.28	.56	.32	.77	1.30
65	.94	.56	.34	.60	.14	TRACE	.21	.16	.15	.07	.27	1.23	1.23
66	1.01	.67	.02	.02	.06	.02	.09	1.13	.91	.96	.31	.02	1.13
67	.18	TRACE	.16	.24	.05	.04	.49	.05	.87	.40	.64	.89	.89
68	.02	.48	1.34	.03	.00	.00	.43	1.50	.14	.70	.13	.12	1.50
69	.70	.21	.09	.02	.93	.00	.09	.44	.28	TRACE	.86	.22	.93
70	TRACE	.37	1.63	.01	.00	TRACE	.10	.12*	1.14	.04	.07	.00	1.63*
71	.00	.36	.00	.00	TRACE	.00	.25	.89	.64	.08	TRACE		.89*
82							1.32	.64*	.60*	.02*	.62*	.49*	1.32*
83	.53*	.54	.52	.17*	.00*	*	.02*	1.58*	2.75*	.21*	.42*	.76*	2.75*
84	.60*	.00	.00	.53*	.33*	TRACE*	.71*	1.77*	.56*	TRACE*	.35*	.70*	1.77*
85	.33	.57*	.12	.08*	TRACE*	.00*	.44*	.61*	.65*	.64*	1.29*	.93*	1.29*
86	.12*	.35*	.48	.04*	.00*	.06*	.86*	.44*	.59*	.79*	.08*	.40*	.86*
87	.25*	.75*	.11	TRACE*	.45*	.06*	.06*	1.27*	.15*	.20*	1.58*	1.01*	1.58*
88	.49*	.41*	.03	.31*	TRACE*	.06*	.02*	.27*	.00*	.59*	.16*	TRACE*	.59*
89	1.18*	TRACE*	.07	.00*	.00*								1.18*

EXTREME DAILY PRECIPITATION AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

GREATEST	1.73	1.35	1.63	.60	.93	.24	1.43	3.00	2.75	1.10	1.58	1.23	3.00
TOTAL OBS	882	812	913	861	882	809	878	882	853	880	876	882	10410

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SNOWFALL IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

AMOUNTS (INCHES)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
NONE	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
TRACE													
0.1-0.4													
0.5-1.4													
1.5-2.4													
2.5-3.4													
3.5-4.4													
4.5-6.4													
6.5-10.4													
10.5-15.4													
15.5-25.4													
25.5-50.4													
OVER 50.4													
DAYS WITH MEAS AMTS													
TOTAL NO. OF OBSERVATIONS	882	812	913	861	882	809	878	882	853	880	875	886	10413

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

TOTAL MONTHLY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
48											.0	.0	.0*
49	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
50	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
51	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
52	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
53	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
54	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
55	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
56	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
57	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
58	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
59	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
60	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
61	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
62	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
63	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
64	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
65	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
66	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
67	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
68	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
69	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
70	.0	.0	.0	.0	.0	.0	.0	.0*	.0	.0	.0	.0	.0*
71	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0		.0*
82							.0	.0*	.0*	.0*	.0*	.0*	.0*
83	.0*	.0	.0	.0*	.0*	*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
84	.0*	.0	.0	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
85	.0	.0*	.0	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
86	.0*	.0*	.0	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
87	.0*	.0*	.0	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
88	.0*	.0*	.0	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
89	.0*	.0*	.0	.0*	.0*								.0*

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

TOTAL MONTHLY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
LEAST	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
GREATEST	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
MEAN	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
MEDIAN	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
SD	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
TOTAL OBS	882	812	913	861	882	809	878	882	853	880	875	886	10413

THE GREATEST VALUE OF .0 OCCURRED ON 11/48

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

EXTREME DAILY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
48											.0	.0	.0*
49	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
50	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
51	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
52	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
53	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
54	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
55	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
56	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
57	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
58	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
59	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
60	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
61	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
62	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
63	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
64	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
65	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
66	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
67	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
68	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
69	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
70	.0	.0	.0	.0	.0	.0	.0	.0*	.0	.0	.0	.0	.0*
71	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0		.0*
82							.0	.0*	.0*	.0*	.0*	.0*	.0*
83	.0*	.0	.0	.0*	.0*	*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
84	.0*	.0	.0	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
85	.0	.0*	.0	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
86	.0*	.0*	.0	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
87	.0*	.0*	.0	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
88	.0*	.0*	.0	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*	.0*
89	.0*	.0*	.0	.0*	.0*								.0*

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

EXTREME DAILY SNOWFALL AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111, 8207-8905

MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
GREATEST	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
TOTAL OBS	882	812	913	861	882	809	878	882	853	880	875	886	10413

THE GREATEST VALUE OF .0 OCCURRED ON 11/01/48

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SNOW DEPTH IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

AMOUNTS (INCHES)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
NONE	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
TRACE													
1													
2													
3													
4-6													
7-12													
13-24													
25-36													
37-48													
49-60													
61-120													
OVER 120													
DAYS WITH MEAS AMTS													
TOTAL NO. OF OBSERVATIONS	882	812	913	861	882	809	878	882	853	880	875	886	10413

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

EXTREME DAILY SNOW DEPTH AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
48											0	0	0*
49	0	0	0	0	0	0	0	0	0	0	0	0	0
50	0	0	0	0	0	0	0	0	0	0	0	0	0
51	0	0	0	0	0	0	0	0	0	0	0	0	0
52	0	0	0	0	0	0	0	0	0	0	0	0	0
53	0	0	0	0	0	0	0	0	0	0	0	0	0
54	0	0	0	0	0	0	0	0	0	0	0	0	0
55	0	0	0	0	0	0	0	0	0	0	0	0	0
56	0	0	0	0	0	0	0	0	0	0	0	0	0
57	0	0	0	0	0	0	0	0	0	0	0	0	0
58	0	0	0	0	0	0	0	0	0	0	0	0	0
59	0	0	0	0	0	0	0	0	0	0	0	0	0
60	0	0	0	0	0	0	0	0	0	0	0	0	0
61	0	0	0	0	0	0	0	0	0	0	0	0	0
62	0	0	0	0	0	0	0	0	0	0	0	0	0
63	0	0	0	0	0	0	0	0	0	0	0	0	0
64	0	0	0	0	0	0	0	0	0	0	0	0	0
65	0	0	0	0	0	0	0	0	0	0	0	0	0
66	0	0	0	0	0	0	0	0	0	0	0	0	0
67	0	0	0	0	0	0	0	0	0	0	0	0	0
68	0	0	0	0	0	0	0	0	0	0	0	0	0
69	0	0	0	0	0	0	0	0	0	0	0	0	0
70	0	0	0	0	0	0	0	0*	0	0	0	0	0*
71	0	0	0	0	0	0	0	0	0	0	0		0*
82							0	0*	0*	0*	0*	0*	0*
83	0*	0	0	0*	0*	0*	0*	0*	0*	0*	0*	0*	0*
84	0*	0	0	0*	0*	0*	0*	0*	0*	0*	0*	0*	0*
85	0	0*	0	0*	0*	0*	0*	0*	0*	0*	0*	0*	0*
86	0*	0*	0	0*	0*	0*	0*	0*	0*	0*	0*	0*	0*
87	0*	0*	0	0*	0*	0*	0*	0*	0*	0*	0*	0*	0*
88	0*	0*	0	0*	0*	0*	0*	0*	0*	0*	0*	0*	0*
89	0*	0*	0	0*	0*								0*

EXTREME DAILY SNOW DEPTH AMOUNTS IN INCHES
FROM SUMMARY OF DAY DATA

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
GREATEST	0	0	0	0	0	0	0	0	0	0	0	0	0
TOTAL OBS	882	812	913	861	882	809	878	882	853	880	875	886	10413

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

PPPPPPPP	AAAAAA	RRRRRRRR	TTTTTTTTTT	CCCCCC
PPPPPPPP	AAAAAAA	RRRRRRRR	TTTTTTTTTT	CCCCCCCC
PP PP	AA AA	RR RR	TT	CC CC
PP PP	AA AA	RR RR	TT	CC
PPPPPPPP	AA AA	RRRRRRRR	TT	CC
PPPPPPPP	AAAAAAAAA	RRRRRRRR	TT	CC
PP	AAAAAAAAA	RR RR	TT	CC
PP	AA AA	RR RR	TT	CC CC
PP	AA AA	RR RR	TT	CCCCCCCC
PP	AA AA	RR RR	TT	CCCCCC

PART C

SURFACE WIND SUMMARIES

PEAK WINDS.

THESE TABLES ARE CREATED FROM SUMMARY OF DAY DATA. SPEEDS ARE IN KNOTS. DIRECTIONS ARE TO 16 COMPASS POINTS FROM THE BEGINNING OF PERIOD OF RECORD THROUGH JUNE 1968, BUT IN JULY 1968, ALL STATIONS EXCEPT THOSE OF THE NATIONAL WEATHER SERVICE STARTED RECORDING DIRECTIONS IN TENS OF DEGREES. DATA IS SUMMARIZED BY MONTH FOR EACH YEAR FOR THE ENTIRE PERIOD OF RECORD AVAILABLE. GIVEN: THE GREATEST MONTHLY VALUE FOR ALL YEARS COMBINED, THE GREATEST YEARLY VALUE FOR ALL YEARS COMBINED, AND THE DATE OF THE ABSOLUTE PEAK WIND RECORDED FOR THE ENTIRE PERIOD OF RECORD. AN ASTERISK (*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF THE DATA ARE AVAILABLE. AN ASTERISK ALSO DENOTES A YEAR(S) WITH ONE OR MORE MISSING AND/OR INCOMPLETE MONTHS.

PEAK WINDS--PERCENT OCCURRENCE FREQUENCY.

ALSO FROM SUMMARY OF DAY DATA. DATA IS SUMMARIZED BY MONTH, FOR ALL YEARS COMBINED, FOR ELEVEN WIND SPEED GROUPS. THE 1-4 KNOT SPEED GROUP INCLUDES CALM WINDS. IF THE PEAK WIND IS REPORTED FOR A PARTICULAR DAY AS "CALM," THAT COUNT GOES INTO THE "1-4 KNOT" CATEGORY. TABLES INCLUDE MEANS, MEDIANS, AND TOTAL OBSERVATION COUNTS. THE VALUES IN THIS SUMMARY ACCOUNT FOR A PEAK WIND BEING RECORDED FOR EACH DAY OF EACH MONTH.

WIND DIRECTION VS WIND SPEED--PERCENT OCCURRENCE FREQUENCY.

THESE TABLES ARE CREATED FROM HOURLY OBSERVATIONS. THEY SUMMARIZE THE DATA AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

THESE TABLES GIVE A BIVARIATE DISTRIBUTION OF THE PERCENT OCCURRENCE FREQUENCY (POF) FOR ELEVEN WIND SPEED GROUPS VERSUS TWELVE WIND DIRECTION SECTORS GIVEN IN 30 DEGREE INCREMENTS. "CALM" AND "VARIABLE" WINDS ARE GIVEN SEPARATELY. CARDINAL WIND DIRECTIONS (N,E,S,W) APPEAR FOR REFERENCE. TOTAL PERCENTAGES, MEANS, AND MEDIANS FOR EACH SECTOR, ALONG WITH TOTAL OBSERVATION COUNTS, ARE PRINTED BELOW EACH SUMMARY.

ALSO PROVIDED: A BIVARIATE DISTRIBUTION OF WIND DIRECTION VERSUS WIND SPEED FOR SPECIFIED CEILING/VISIBILITY CONDITIONS. THESE CONDITIONS ARE:

WHEN THE VISIBILITY IS GREATER THAN OR EQUAL TO 1/2 MILES (0800 METERS) THE CEILING MUST BE GREATER THAN OR EQUAL TO 200 FEET BUT LESS THAN 1500 FEET. IF THIS CONDITION IS NOT MET, THEN THE FOLLOWING CONDITION IS TESTED: WHEN THE CEILING IS GREATER THAN OR EQUAL TO 200 FEET, THE VISIBILITY MUST BE GREATER THAN OR EQUAL TO 1/2 (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS).

CONVERSION: 1 KNOT = .514791 METERS PER SECOND

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

PEAK SURFACE WINDS IN KNOTS
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 8602-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
86		32/*24	25/ 24	22/*32	24/*23	20/*28	12/*37	06/*31	15/*30	18/*34	21/*25	35/*20	12/*37
87	24/*42	21/*30	26/ 36	18/*35	14/*36	26/*24	08/*42	05/*48	08/*34	08/*23	28/*24	13/*20	05/*48
88	36/*20	06/*25	05/*23	18/*32	21/*36	10/*31	03/*46	05/*45	17/*31	21/*33	26/*30	08/*27	03/*46
89	35/*23	19/*30	25/ 35	17/*27	20/*30								25/*35
.....													
GREATEST	24/ 42	21/ 30	26/ 36	18/ 35	14/ 36	10/ 31	03/ 46	05/ 48	08/ 34	18/ 34	26/ 30	08/ 27	05/ 48
.....													
TOTAL OBS	66	84	113	94	92	71	67	73	69	68	63	61	921
.....													

THE PEAK WIND OF 48 FROM 05/ OCCURRED ON 08/04/87

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF DATA AVAILABLE FOR THE MONTH
\$THE VALUE IS 100 OR GREATER WITH LESS THAN 90% OF DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF DAILY PEAK WINDS
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 8602-8905
MONTH: ALL HOURS: ALL

MONTH	WIND SPEEDS IN KNOTS											MEAN MEDIAN		TOTAL OBS
	CALM-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	WIND	WIND	
JAN	1.5	37.9	27.3	21.2	7.6	1.5	1.5	.0	1.5	.0	.0	12.9	10.0	66
FEB	.0	33.3	34.5	17.9	9.5	2.4	2.4	.0	.0	.0	.0	13.3	12.0	84
MAR	.0	8.0	42.5	26.5	19.5	.9	.9	1.8	.0	.0	.0	15.8	14.0	113
APR	.0	2.1	38.3	25.5	24.5	6.4	2.1	1.1	.0	.0	.0	17.2	16.0	94
MAY	.0	1.1	25.0	6.7	17.4	2.2	4.3	3.3	.0	.0	.0	18.1	17.0	92
JUN	.0	.0	25.4	36.6	21.1	15.5	1.4	.0	.0	.0	.0	18.5	18.0	71
JUL	.0	.0	25.4	35.8	22.4	6.0	6.0	1.5	3.0	.0	.0	19.7	18.0	67
AUG	.0	.0	26.0	39.7	17.8	6.8	5.5	1.4	2.7	.0	.0	18.9	17.0	73
SEP	.0	8.7	40.6	31.9	11.6	2.9	4.3	.0	.0	.0	.0	15.5	15.0	69
OCT	.0	30.9	41.2	13.2	7.4	4.4	2.9	.0	.0	.0	.0	13.6	12.0	68
NOV	.0	27.0	41.3	19.0	9.5	1.6	1.6	.0	.0	.0	.0	13.0	11.0	63
DEC	.0	45.9	37.7	9.8	3.3	3.3	.0	.0	.0	.0	.0	11.0	10.0	61
ANNUAL	.1	14.9	34.0	27.6	15.0	4.3	2.7	.9	.5	.0	.0	15.8	15.0	921

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	2.0	.2										2.2	3.4	4.0
020-040	3.8	1.4	.2									5.4	3.9	4.0
050-070	5.2	1.1	.6									6.9	4.5	4.0
(E) 080-100	6.3	.9	.5									7.7	3.6	3.0
110-130	3.9	.5	.2									4.6	3.9	4.0
140-160	8.3	1.6										9.9	3.2	3.0
(S) 170-190	3.9	.8	.5									5.2	4.1	3.0
200-220	3.1	.6										3.8	3.4	3.0
230-250	.9	.2										1.1	3.7	4.0
(W) 260-280		.3										.3	7.0	7.0
290-310	.5											.5	2.7	2.0
320-340	.3											.3	2.5	2.5
VARIABLE														
CALM	////////////////////											52.1	////////////////	
TOTALS	38.2	7.6	2.0									100.0	1.8	3.0

TOTAL NUMBER OF OBSERVATIONS 635

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 09-11

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
(N) 350-010	4.2	3.8	.3	.1								8.5	5.1	4.5
020-040	13.4	9.6	1.1	.1								24.3	5.0	4.0
050-070	4.8	3.1	1.7									9.6	5.7	4.5
(E) 080-100	2.3	1.3	2.3	.1								5.9	7.2	6.5
110-130	1.1	.6										1.7	4.5	4.0
140-160	2.0	.8	.1									3.0	4.7	4.0
(S) 170-190	.8	.6	.6		.1							2.1	7.8	6.0
200-220	1.3	.7	1.1									3.1	7.2	6.0
230-250	1.6	1.3	.3									3.1	5.2	4.5
(W) 260-280	1.1	.7	.3									2.1	5.5	4.0
290-310	.8	.4	.1									1.4	4.7	4.0
320-340	.8	.6	.1									1.6	5.2	4.0
VARIABLE														
CALM	////////////////////////////////////											33.6	////////////////////////////////	
TOTALS	34.2	23.5	8.0	.3	.1							100.0	3.6	4.0

TOTAL NUMBER OF OBSERVATIONS 708

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	7.8	6.6	1.9									16.3	5.5	5.0
020-040	5.5	6.4	2.9	.1								14.9	6.4	6.0
050-070	1.2	2.7	4.5									8.4	8.7	10.0
(E) 080-100	1.2	1.6	2.2	.1								5.1	8.4	8.0
110-130	.1	.3	.1		.1							.7	9.4	7.0
140-160	.1											.1	4.0	4.0
(S) 170-190	.4	.6	.3	.3								1.6	8.1	6.0
200-220	.7	1.0	1.2	.4	.1							3.5	9.7	9.0
230-250	2.3	2.2	1.6									6.1	6.9	6.0
(W) 260-280	3.2	2.6	1.6	.3								7.7	6.5	6.0
290-310	4.6	2.2	.1	.1								7.1	4.6	4.0
320-340	4.5	2.6	.1									7.2	4.8	4.0
VARIABLE														
CALM	////////////////////											21.4	////////	
TOTALS	31.6	28.8	16.5	1.3	.2							100.0	5.1	6.0
TOTAL NUMBER OF OBSERVATIONS 692														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64				GE 65
(N) 350-010	7.0	6.4	1.4	.2								14.9	5.4	5.0
020-040	3.6	7.0	1.6	.2								12.3	6.4	6.0
050-070	1.4	4.2	2.3									7.9	7.3	8.0
(E) 080-100	.3	.9	1.4	.2								2.8	9.5	10.0
110-130			.2									.2	14.0	14.0
140-160	.2	.3										.5	5.3	6.0
(S) 170-190	.6	.6	.2		.2							1.6	7.4	6.5
200-220	.9	1.4	.8	.2								3.3	8.0	8.0
230-250	1.9	4.7	1.7	.3	.5							9.0	7.9	7.5
(W) 260-280	2.8	3.6	1.7									8.1	6.6	6.0
290-310	3.4	2.2	.5									6.1	5.2	4.0
320-340	5.3	2.2										7.5	4.2	4.0
VARIABLE														
CALM	////////////////////////////////////										26.1	////////////////////////////////		
TOTALS	27.4	33.5	11.8	1.1	.7							100.0	4.7	6.0

TOTAL NUMBER OF OBSERVATIONS 644

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.3	.2										3.5	3.3	3.0
020-040	4.2	1.4										5.7	3.9	4.0
050-070	2.4	1.9			.2							4.5	5.2	4.0
(E) 080-100	.9	.5	.2	.5								2.1	7.7	6.0
110-130	.9											.9	3.3	3.0
140-160	1.7	.2										1.9	4.1	4.0
(S) 170-190	3.8	1.2	.2									5.2	4.4	4.0
200-220	3.3	1.4	.2									5.0	4.9	4.0
230-250	2.4	1.7	.2	.2								4.5	5.3	4.0
(W) 260-280	1.7	1.7	.2	.2								3.8	6.1	5.0
290-310	.9	.2										1.2	4.0	4.0
320-340	.2	.2	.5									.9	7.0	7.5
VARIABLE														
CALM	////////////////////////////////////											60.8	////////	
TOTALS	25.7	10.6	1.5	.9	.2							100.0	1.9	4.0
TOTAL NUMBER OF OBSERVATIONS 424														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.2											1.2	4.0	4.0
020-040														
050-070	2.3											2.3	2.5	2.5
(E) 080-100	2.3											2.3	2.5	2.5
110-130	1.2											1.2	2.0	2.0
140-160	11.6	1.2										12.8	3.8	4.0
(S) 170-190	9.3	4.7										14.0	4.0	4.0
200-220														
230-250	3.5	2.3										5.8	5.0	4.0
(W) 260-280														
290-310	1.2											1.2	4.0	4.0
320-340	2.3											2.3	4.0	4.0
VARIABLE														
CALM	////////////////////											57.0	////////	
TOTALS	34.9	8.2										100.0	1.7	4.0

TOTAL NUMBER OF OBSERVATIONS 86

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	4.9	3.6	.8	.1								9.4	5.2	4.0
020-040	6.2	5.4	1.2	.1								12.9	5.5	5.0
050-070	3.0	2.6	1.9		.0							7.6	6.5	6.0
(E) 080-100	2.3	1.1	1.4	.2								4.9	6.6	6.0
110-130	1.2	.3	.1		.0							1.6	4.7	4.0
140-160	2.7	.6	.0									3.4	3.7	4.0
(S) 170-190	1.9	.8	.3	.1	.1							3.2	5.4	4.0
200-220	1.7	1.0	.7	.1	.0							3.5	6.6	5.0
230-250	1.8	2.0	.8	.1	.1							4.8	6.6	6.0
(W) 260-280	1.7	1.7	.8	.1								4.3	6.4	6.0
290-310	2.1	1.0	.2	.0								3.4	4.8	4.0
320-340	2.4	1.2	.1									3.7	4.6	4.0
VARIABLE														
CALM	////////////////////											37.4	////////	
TOTALS	31.9	21.3	8.3	.8	.2							100.0	3.5	4.0
TOTAL NUMBER OF OBSERVATIONS 3189														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	MEAN	MEDIAN
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65		
(N) 350-010													
020-040													
050-070													
(E) 080-100													
110-130													
140-160													
(S) 170-190		25.0									25.0	6.0	6.0
200-220													
230-250													
(W) 260-280													
290-310		25.0	25.0								50.0	9.0	9.0
320-340													
VARIABLE													
CALM	////////////////////										25.0	////////	
TOTALS		50.0	25.0								100.0	6.0	8.0
TOTAL NUMBER OF OBSERVATIONS 4													

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.0	.8	.2									2.0	4.8	4.5
020-040	3.5	1.0	.2									4.7	4.2	4.0
050-070	2.9	.7	.2	.3								4.1	5.0	3.5
(E) 080-100	6.9	.3	.2									7.4	3.2	3.0
110-130	5.1	.3										5.4	3.2	3.0
140-160	11.5	1.2	.5	.2								13.3	3.8	4.0
(S) 170-190	3.9	.8	.3									5.1	4.2	4.0
200-220	2.5	1.0	.7									4.2	5.2	4.0
230-250	1.2	.5	.3									2.0	5.2	4.0
(W) 260-280	.5	.3										.8	4.0	4.0
290-310														
320-340		.3										.3	5.0	5.0
VARIABLE														
CALM	////////////////////////////////////											50.5	////////	
TOTALS	39.0	7.2	2.6	.5								100.0	2.0	4.0

TOTAL NUMBER OF OBSERVATIONS 592

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEN AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	5.9	6.3	1.0									13.2	5.3	5.0
020-040	15.1	6.6	.4	.1								22.3	4.6	4.0
050-070	4.4	1.9	1.3	.3								7.9	6.2	4.0
(E) 080-100	1.2	.9	.6									2.6	6.4	6.0
110-130	1.3	.6										1.9	3.5	4.0
140-160	1.6	.6	.1									2.3	4.6	4.0
(S) 170-190	1.9	.3	.3	.1								2.6	4.9	4.0
200-220	1.0	1.3	1.0									3.4	7.0	6.0
230-250	1.2	2.2	.4									3.8	6.2	6.0
(W) 260-280	1.9	1.5	.9									4.3	5.9	5.0
290-310	1.6	.9	.1									2.6	4.6	4.0
320-340	3.2	.7										4.0	3.9	4.0
VARIABLE														
CALM	////////////////////											28.9	////////	
TOTALS	40.3	23.8	6.1	.5								100.0	3.7	4.0

TOTAL NUMBER OF OBSERVATIONS 681

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	6.0	7.1	.9									14.0	5.4	5.0
020-040	5.7	7.4	2.1	.5								15.7	6.2	6.0
050-070	2.3	2.7	2.3	.5								7.7	7.9	8.0
(E) 080-100	.8	.8	1.2									2.7	8.2	8.0
110-130	.3	.5										.8	4.2	5.0
140-160	.6	.2										.8	3.8	4.0
(S) 170-190	.6	.2	.9									1.7	8.2	10.0
200-220	1.1	1.1	1.5	.5								4.1	8.9	9.0
230-250	3.0	2.3	.8	.2								6.2	5.9	5.0
(W) 260-280	3.8	3.0	.6	.2								7.5	5.9	4.5
290-310	5.6	2.6	.6									8.7	4.5	4.0
320-340	6.6	2.4	.6									9.7	4.5	4.0
VARIABLE														
CALM	////////////////////											20.5	////////	
TOTALS	36.4	30.3	11.5	1.9								100.0	4.8	5.0
TOTAL NUMBER OF OBSERVATIONS 663														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	6.7	5.2	.8									12.7	5.2	4.0
020-040	2.3	6.2	2.4									10.9	7.0	7.0
050-070	1.5	2.6	2.0									6.0	7.1	8.0
(E) 080-100	.2	.2	.5									.8	9.0	10.0
110-130	.2	.5	.3	.2								1.1	7.9	6.0
140-160	.7	.7		.2								1.5	6.9	6.0
(S) 170-190		.7	.3									1.0	8.7	8.5
200-220	1.0	1.6	1.6	.5	.3							5.0	9.7	9.0
230-250	4.1	4.1	1.3	.3								9.8	6.2	5.0
(W) 260-280	4.6	5.2	1.3	.2								11.2	6.0	5.0
290-310	5.7	2.0	.7									8.3	4.8	4.0
320-340	6.5	3.7	.3									10.6	4.8	4.0
VARIABLE														
CALM	////////////////////////////////////											21.0	////////	
TOTALS	33.5	32.7	11.5	1.4	.3							100.0	4.9	5.0

TOTAL NUMBER OF OBSERVATIONS 614

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 18-20

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
(N) 350-010	2.4	.7										3.1	3.6	3.0
020-040	1.7	1.4	.2									3.4	5.0	4.5
050-070	1.2	.2	.2									1.7	4.9	4.0
(E) 080-100	1.2	.2										1.4	3.7	3.5
110-130	1.0	.2										1.2	3.4	3.0
140-160	1.2	.5										1.7	4.3	4.0
(S) 170-190	2.4	.5	1.0	.5								4.3	7.3	4.0
200-220	2.7	2.2	.7									5.6	6.1	6.0
230-250	4.6	1.4	1.0									7.0	5.1	4.0
(W) 260-280	4.6	2.7	.2									7.5	4.4	4.0
290-310	3.1	1.2	.2									4.6	4.8	4.0
320-340	2.4	1.2										3.6	4.4	4.0
VARIABLE														
CALM	////////////////////////////////////											54.8	////////////////////////////////	
TOTALS	28.5	12.4	3.5	.5								100.0	2.3	4.0
TOTAL NUMBER OF OBSERVATIONS 414														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 21-23

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
(N) 350-010	.9	1.8										2.7	5.3	6.0
020-040	.9	.9										1.8	4.5	4.5
050-070	.9											.9	2.0	2.0
(E) 080-100	.9											.9	4.0	4.0
110-130	2.7	1.8										4.4	4.0	4.0
140-160	10.6	1.8										12.4	3.8	4.0
(S) 170-190	8.8	.9	.9									10.6	4.1	4.0
200-220	5.3											5.3	2.8	2.5
230-250	5.3	1.8	.9									8.0	4.9	4.0
(W) 260-280	1.8		.9									2.7	6.3	4.0
290-310		.9										.9	7.0	7.0
320-340														
VARIABLE														
CALM	////////////////////////////////////											49.6	////////////////////////////////	
TOTALS	38.1	9.9	2.7									100.0	2.1	4.0

TOTAL NUMBER OF OBSERVATIONS 113

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL	MEAN	MEDIAN
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	4.5	4.3	.6									9.4	5.2	5.0
020-040	6.0	4.7	1.1	.1								11.9	5.4	4.0
050-070	2.5	1.7	1.2	.2								5.7	6.6	5.5
(E) 080-100	2.0	.5	.5									3.0	5.2	4.0
110-130	1.6	.5	.1	.0								2.2	3.9	3.0
140-160	3.4	.6	.1	.1								4.2	4.2	4.0
(S) 170-190	1.9	.5	.6	.1								3.1	5.6	4.0
200-220	1.7	1.3	1.1	.2	.1							4.4	7.3	7.0
230-250	2.8	2.1	.7	.1								5.8	5.8	5.0
(W) 260-280	2.9	2.4	.6	.1								6.1	5.6	5.0
290-310	3.1	1.3	.3									4.8	4.7	4.0
320-340	3.8	1.7	.2									5.6	4.5	4.0
VARIABLE														
CALM	////////////////////////////////////											33.9	////////	
TOTALS	36.2	21.6	7.1	.9	.1							100.0	3.6	4.0
TOTAL NUMBER OF OBSERVATIONS 3077														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).
AND/OR
VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS														
DIRECTION	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
(DEGREES)												%	WIND	WIND
(N) 350-010														
020-040														
050-070														
(E) 080-100														
110-130														
140-160														
(S) 170-190														
200-220	10.0											10.0	4.0	4.0
230-250														
(W) 260-280	10.0											10.0	4.0	4.0
290-310	10.0											10.0	2.0	2.0
320-340			10.0									10.0	10.0	10.0
VARIABLE														
CALM	////////////////////////////////////											60.0	////////	
TOTALS	30.0		10.0									100.0	2.0	4.0

TOTAL NUMBER OF OBSERVATIONS 10

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	.8	.7										1.5	4.7	4.0
020-040	2.5	.6										3.1	3.8	4.0
050-070	3.7	1.0	.1									4.8	3.8	4.0
(E) 080-100	3.2	.1										3.4	3.0	3.0
110-130	4.9	.4										5.3	3.1	3.0
140-160	15.0	2.4										17.4	3.4	3.0
(S) 170-190	7.6	2.4	.1									10.1	3.9	4.0
200-220	2.7	3.1	.6	.1								6.5	5.6	5.0
230-250	1.0	2.0	.3									3.2	5.7	5.0
(W) 260-280	.6	.7	.6									1.8	6.3	6.0
290-310	.8	.1										1.0	3.6	4.0
320-340	.8	.3										1.1	4.3	4.0
VARIABLE														
CALM	////////////////////											40.7	////////	
TOTALS	43.6	13.8	1.7	.1								100.0	2.4	4.0
TOTAL NUMBER OF OBSERVATIONS 712														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	7.2	3.9	.7									11.8	4.6	4.0
020-040	8.4	5.4	.7									14.5	4.8	4.0
050-070	2.0	1.1	.9	.1								4.1	6.1	5.0
(E) 080-100	1.4	.9	.7									3.0	6.1	5.5
110-130	.6	.5										1.1	4.4	4.0
140-160	1.2	1.2	.4		.1							3.0	5.9	5.0
(S) 170-190	.6	.9	.5									2.0	6.8	7.0
200-220	2.1	2.8	1.7									6.7	6.8	6.0
230-250	2.3	4.6	3.7	.5								11.1	7.8	8.0
(W) 260-280	3.2	3.3	.9	.2								7.6	6.2	5.5
290-310	2.7	.7	.2	.1								3.8	4.9	4.0
320-340	2.1	1.2	.2									3.6	4.8	4.0
VARIABLE														
CALM	////////////////////////////////////											27.7	////////////////////////////////	
TOTALS	33.8	26.5	10.6	.9	.1							100.0	4.2	5.0

TOTAL NUMBER OF OBSERVATIONS 811

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	4.2	4.5	.4									9.1	5.2	5.0
020-040	2.8	4.2	1.4									8.3	6.2	6.0
050-070	1.5	2.0	1.1									4.7	6.7	7.0
(E) 080-100	.6	.8	.3									1.6	6.5	7.0
110-130	.3	.3										.5	4.5	4.5
140-160	.5	.3	.1									.9	5.4	4.0
(S) 170-190	1.3	1.3	.6	.1								3.3	6.9	7.0
200-220	1.5	2.9	2.1	.1	.1							6.8	7.8	8.0
230-250	2.8	6.4	5.2	.4	.1							14.8	8.1	8.0
(W) 260-280	4.2	6.2	4.8	.1	.1							15.3	7.4	7.0
290-310	4.8	3.3	1.6	.1	.1							9.9	5.8	5.0
320-340	4.8	2.8	.6									8.2	4.6	4.0
VARIABLE														
CALM	////////////////////											16.6	////////	
TOTALS	29.3	35.0	18.2	.8	.4							100.0	5.5	6.0

TOTAL NUMBER OF OBSERVATIONS 795

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64				GE 65
(N) 350-010	2.9	3.1										6.0	5.3	5.0
020-040	1.7	2.9	.4									5.1	6.2	6.0
050-070	1.0	1.5										2.5	5.4	5.0
(E) 080-100	.3	.1										.4	5.0	4.0
110-130	.4	.3										.7	4.6	4.0
140-160		.3										.3	7.0	7.0
(S) 170-190	.7	1.0	1.3	.1	.1							3.2	9.1	9.0
200-220	2.0	2.8	2.8	.1								7.7	7.8	8.0
230-250	4.1	9.4	5.8	1.1	.1							20.5	8.0	8.0
(W) 260-280	4.8	6.9	5.5	.3	.1							17.6	7.5	7.0
290-310	5.1	5.1	2.9	.1								13.2	6.4	6.0
320-340	4.2	3.5	1.3									9.0	5.8	5.0
VARIABLE														
CALM	////////////////////////////////////										13.8	////////////////////////////////		
TOTALS	27.2	36.9	20.0	1.7	.3							100.0	6.1	6.0

TOTAL NUMBER OF OBSERVATIONS 712

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GLA BEND AAF A7
EST TO UTC: +7

PERIOD OF RECORD: JUN 79 MAY 89
MONTH: MAR HOURS: 18 20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS																TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	65	66	67	68	69	70			
(N) 550-010	2.5	1.0															3.5	4.5	4.0
020-040	1.9	.4	.2														2.5	5.8	5.0
050-070	1.0	.2															1.2	5.7	4.0
(E) 080-100	.6	.2															.8	4.0	4.0
110-130		.2															.2	6.0	6.0
140-160	.6	.2	.2														1.0	5.4	4.0
(S) 170-190	1.2	1.5	1.0		.2												3.9	7.4	6.0
200-220	5.1	5.1	5.1	.2	.2												9.8	7.8	7.0
230-250	4.8	4.6	5.5														12.9	6.7	6.0
(W) 260-280	5.4	5.8	1.5	.6	.4												13.7	6.9	6.0
290-310	2.9	2.7	2.1		.2												7.9	7.1	6.0
320-340	2.9	2.1	.4														5.4	5.0	4.0
VARIABLE																			
CALM	////////////////////																57.5	////////	
TOTALS	26.7	22.0	12.0	.8	1.0												100.0	4.1	5.0

TOTAL NUMBER OF OBSERVATIONS: 482

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	.7	.7										1.3	4.5	4.5
020-040	.7	.7										1.3	4.5	4.5
050-070														
(E) 080-100	.7	.7										1.3	6.5	6.5
110-130	2.7	.7										3.3	3.8	4.0
140-160	2.0	2.7										4.7	5.0	5.0
(S) 170-190	12.7	2.7	.7									16.0	4.6	4.0
200-220	7.3	3.3	1.3	.7								12.7	6.0	4.0
230-250	4.7	2.7				.7						8.0	6.1	4.0
(W) 260-280	2.7	1.3			1.3							5.3	8.1	5.0
290-310														
320-340		2.0										2.0	8.0	8.0
VARIABLE														
CALM	////////////////////											44.0	////////	
TOTALS	34.2	17.5	2.0	.7	2.0							100.0	3.1	4.0

TOTAL NUMBER OF OBSERVATIONS 150

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.5	2.8	.2									6.6	4.9	4.0
020-040	3.5	2.9	.6									7.0	5.2	4.0
050-070	1.8	1.2	.5	.0								3.5	5.4	4.0
(E) 080-100	1.2	.5	.2									1.9	5.0	4.0
110-130	1.3	.4										1.7	3.6	3.0
140-160	3.5	1.0	.1		.0							4.6	4.0	4.0
(S) 170-190	2.7	1.4	.7	.1	.1							4.9	5.7	4.0
200-220	2.4	2.9	2.0	.1	.1							7.5	7.1	6.0
230-250	2.9	5.3	3.6	.4	.1							12.3	7.7	7.0
(W) 260-280	3.5	4.4	2.6	.2	.2							10.8	7.1	6.0
290-310	3.2	2.2	1.3	.1	.1							6.8	6.1	5.0
320-340	2.9	2.0	.5									5.3	5.1	4.0
VARIABLE														
CALM	////////////////////											27.1	////////	
TOTALS	32.4	27.0	12.3	.9	.6							100.0	4.4	5.0

TOTAL NUMBER OF OBSERVATIONS 3662

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

		WIND SPEED IN KNOTS										TOTAL	MEAN	MEDIAN
DIPECTION	(DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65		
												%	WIND	WIND
(N)	350-010													
	020-040													
	050-070													
(E)	080-100													
	110-130													
	140-160													
(S)	170-190													
	200-220		20.0			20.0						40.0	14.0	14.0
	230-250		20.0		20.0							40.0	12.0	12.0
(W)	260-280			20.0								20.0	10.0	10.0
	290-310													
	320-340													
VARIABLE														
	CALM	////////////////////										.0	////////////////	
TOTALS			40.0	20.0	20.0	20.0						100.0	12.4	10.0

TOTAL NUMBER OF OBSERVATIONS 5

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.1	.9										1.6	3.5	3.0
020-040	3.6	.5										4.1	3.2	3.0
050-070	3.3	.6										3.9	3.5	3.0
(E) 080-100	2.5	.8	.6									3.9	5.1	4.0
110-130	5.8	.9										6.7	3.3	3.0
140-160	11.3	3.1	.3									14.7	4.0	4.0
(S) 170-190	7.1	2.7	.5									10.2	4.4	4.0
200-220	2.7	2.4	.9									6.0	5.9	5.0
230-250	1.9	2.2	.3	.2								4.5	6.0	6.0
(W) 260-280	1.3	.8	.5									2.5	5.8	5.0
290-310	.5	.3										.8	4.2	3.0
320-340	.9	.3										1.3	3.5	3.0
VARIABLE														
CALM	////////////////////											39.8	////////	
TOTALS	42.0	15.1	3.1	.2								100.0	2.6	4.0
TOTAL NUMBER OF OBSERVATIONS 638														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64				GE 65
(N) 350-010	6.1	1.9	.4									8.5	4.4	4.0
020-040	7.1	3.8	.8									11.7	4.7	4.0
050-070	.7	2.2	1.5	.3								4.7	8.8	8.0
(E) 080-100	.3	.8	1.3	.1								2.5	9.7	10.0
110-130	.4	.7										1.1	4.9	5.5
140-160	.4	.7	.1									1.3	6.1	6.0
(S) 170-190	.8	1.8	.6									3.2	7.0	8.0
200-220	1.7	3.3	1.9									7.0	7.6	8.0
230-250	2.4	4.5	4.5	.4								11.7	8.2	8.0
(W) 260-280	3.6	3.2	1.4	.3								8.5	6.4	6.0
290-310	4.3	1.9	.6									6.8	5.0	4.0
320-340	4.3	1.9	.1									6.4	4.0	4.0
VARIABLE														
CALM	////////////////////////////////////										26.6	////////////////////////////////		
TOTALS	32.1	26.7	13.2	1.1								100.0	4.6	6.0

TOTAL NUMBER OF OBSERVATIONS 718

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.1	2.4	.6									6.1	5.3	4.0
020-040	2.0	2.4	.6									5.0	5.9	6.0
050-070	2.0	1.6	1.6	.1								5.2	7.1	8.0
(E) 080-100	1.3	1.4	1.1									3.8	6.8	7.0
110-130	.6											.6	3.8	4.0
140-160	1.0	.4	.3									1.7	5.6	4.0
(S) 170-190	1.1	1.4	1.3	.1	.3							4.2	8.9	8.0
200-220	2.4	3.5	3.1	.7								9.8	8.2	7.0
230-250	3.3	6.5	4.5	.6	.3							15.1	8.1	8.0
(W) 260-280	4.0	7.5	2.1	.8	.1							14.6	7.2	6.0
290-310	6.1	5.0	1.6	.3								12.9	5.9	5.0
320-340	5.0	3.4	.7									9.1	5.0	4.0
VARIABLE														
CALM	////////////////////////////////////											12.0	////////////////////////////////	
TOTALS	31.9	35.5	17.5	2.6	.7							100.0	6.0	6.0
TOTAL NUMBER OF OBSERVATIONS 707														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.3	2.6										5.9	5.1	4.0
020-040	1.7	1.5	.6									3.8	5.8	6.0
050-070	.6	.9	.6									2.1	7.4	7.0
(E) 080-100	.9	.8	.2									1.8	5.1	4.5
110-130	.3	.3										.6	4.8	4.5
140-160	.6	.5										1.1	4.6	4.0
(S) 170-190	.6	1.2	1.8	.6								4.2	9.6	10.0
200-220	1.4	3.6	4.1	1.8	.3	.2						11.3	10.2	10.0
230-250	3.6	8.0	6.9	1.7	.3							20.4	8.7	8.0
(W) 260-280	4.1	8.9	5.7	.3	.3							19.2	7.6	6.0
290-310	3.8	6.5	1.8	.2								12.2	6.3	6.0
320-340	2.9	5.1	.9		.3							9.2	6.6	6.0
VARIABLE														
CALM	////////////////////											8.4	////////	
TOTALS	23.8	39.9	22.6	4.6	1.2	.2						100.0	7.0	6.0
TOTAL NUMBER OF OBSERVATIONS 666														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF A7
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	2.1	.6	.6									3.4	5.4	4.0
020-040	1.1	1.1										2.1	4.8	4.5
050-070	.9	.9	.2									1.9	6.0	6.0
(E) 080-100	.6	1.9	.4									3.0	6.8	6.5
110-130	.2											.2	3.0	3.0
140-160	.9	.6										1.5	4.9	4.0
(S) 170-190	1.1	1.5	2.3	.2								5.1	8.6	9.5
200-220	1.9	3.0	4.5	.4								9.8	8.6	9.5
230-250	7.0	9.4	5.3	.4	.2							22.3	7.0	6.0
(W) 260-280	7.4	6.2	2.3	.6								16.6	6.4	6.0
290-310	3.2	4.3	1.1	.2								8.7	6.1	6.0
320-340	4.3	.6										4.9	3.9	4.0
VARIABLE														
CALM	////////////////////////////////////											20.4	////////	
TOTALS	30.7	30.1	16.7	1.8	.2							100.0	5.3	6.0
TOTAL NUMBER OF OBSERVATIONS 470														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010		.6										.6	6.0	6.0
020-040	1.1	.6		.6								2.2	7.8	4.5
050-070	.6											.6	2.0	2.0
(E) 080-100	.6	.6										1.1	4.0	4.0
110-130	.6		.6									1.1	6.5	6.5
140-160	1.1	1.1	1.1									3.4	7.5	7.0
(S) 170-190	3.9	3.4	1.1									8.4	5.9	5.0
200-220	9.5	7.3	4.5									21.2	5.8	5.5
230-250	4.5	4.5	2.2	.6								11.7	6.8	6.0
(W) 260-280	2.2	1.1	1.1									4.5	6.4	5.0
290-310	1.7											1.7	3.0	3.0
320-340														
VARIABLE														
CALM	////////////////////											43.6	////////	
TOTALS	25.8	19.2	10.6	1.2								100.0	3.4	5.0

TOTAL NUMBER OF OBSERVATIONS 179

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.1	1.6	.3									5.0	4.8	4.0
020-040	3.1	1.9	.4	.0								5.4	4.9	4.0
050-070	1.5	1.2	.8	.1								3.6	6.7	6.0
(E) 080-100	1.1	1.1	.7	.0								2.9	6.6	6.0
110-130	1.4	.4	.0									1.8	3.7	4.0
140-160	2.7	1.1	.2									4.0	4.5	4.0
(S) 170-190	2.2	1.8	1.2	.2	.1							5.5	6.9	6.0
200-220	2.4	3.4	2.9	.6	.1	.0						9.4	8.1	8.0
230-250	3.5	5.8	4.2	.7	.1							14.3	7.9	8.0
(W) 260-280	3.8	5.1	2.3	.4	.1							11.7	7.0	6.0
290-310	3.6	3.4	.9	.1								8.0	5.8	6.0
320-340	3.3	2.3	.4		.1							6.0	5.1	4.0
VARIABLE														
CALM	////////////////////											22.5	////////	
TOTALS	31.7	29.1	14.3	2.1	.5							100.0	5.0	6.0
TOTAL NUMBER OF OBSERVATIONS 3378														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS												
DIRECTION	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL
(DEGREES)												%
												WIND
(N) 350-010												
020-040												
050-070												
(E) 080-100												
110-130												
140-160												
(S) 170-190												
200-220												
230-250												
(W) 260-280												
290-310												
320-340												
VARIABLE												
CALM	////////////////////											.0
TOTALS												.0

TOTAL NUMBER OF OBSERVATIONS 0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	.8											.8	3.0	3.0
020-040	1.9	.6										2.5	3.5	3.5
050-070	1.7	.2	.2									2.0	4.2	4.0
(E) 080-100	1.2	.2	.5									1.9	5.3	4.0
110-130	4.0	.8										4.8	3.3	3.0
140-160	9.0	2.9	.2									12.1	3.9	4.0
(S) 170-190	6.0	1.6	.3									7.9	4.2	4.0
200-220	3.9	1.7	.9	.2								6.7	5.4	4.0
230-250	1.7	1.1	.6									3.4	6.0	4.5
(W) 260-280	.9	.6	.3									1.9	5.1	4.5
290-310	.2	.2										.3	3.5	3.5
320-340	.8	.3										1.1	3.9	4.0
VARIABLE														
CALM	////////////////////											54.7	////////	
TOTALS	32.1	10.2	3.0	.2								100.0	2.0	4.0
TOTAL NUMBER OF OBSERVATIONS 645														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.7	1.0	.1									4.8	4.1	4.0
020-040	3.0	2.0										5.0	4.7	4.0
050-070	1.4	1.3	1.4									4.1	7.0	7.0
(E) 080-100	.7	.3	.7									1.7	6.0	6.5
110-130	.7	.4	.3									1.4	5.5	5.0
140-160	.9	.6	.3									1.7	5.8	4.5
(S) 170-190	1.6	1.4	1.1									4.1	6.7	6.0
200-220	2.0	4.1	1.9									8.0	7.1	7.0
230-250	5.0	6.0	1.3	.3								12.5	6.1	6.0
(W) 260-280	6.0	3.0	1.0	.3								10.3	5.4	4.0
290-310	4.8	1.6										6.4	4.0	4.0
320-340	3.8	1.0										4.8	3.8	4.0
VARIABLE														
CALM	////////////////////////////////////											35.0	////////	
TOTALS	33.6	22.7	8.1	.6								100.0	3.6	4.0

TOTAL NUMBER OF OBSERVATIONS 702

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.2	2.0										3.2	5.5	5.0
020-040	1.9	1.4	.3									3.6	5.4	4.0
050-070	.3	1.4	.1									1.9	6.8	6.0
(E) 080-100	.7	.6										1.3	5.2	4.0
110-130	.1											.1	2.0	2.0
140-160	1.0	1.0	.6									2.6	6.3	6.0
(S) 170-190	1.7	2.5	1.3	.1								5.6	7.1	6.0
200-220	3.0	6.1	5.5	.7								15.3	8.3	8.0
230-250	4.9	9.4	4.9	.4								19.7	7.4	7.0
(W) 260-280	5.1	2.8	1.6									16.5	6.2	6.0
290-310	4.9	4.6	.3									9.8	5.0	4.5
320-340	3.8	4.2	.4									8.4	5.3	5.0
VARIABLE														
CALM	////////////////////											11.9	////////	
TOTALS	28.6	43.0	15.0	1.2								100.0	5.8	6.0
TOTAL NUMBER OF OBSERVATIONS 691														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.1	1.9										3.0	5.4	5.0
020-040	.2	1.0										1.1	6.4	6.0
050-070	.3	.8										1.1	5.9	6.0
(E) 080-100	.2	.3	.2									.6	7.3	7.5
110-130	.3		.3									.6	7.3	7.0
140-160	.2	.5	.2									.8	7.0	8.0
(S) 170-190	1.3	2.6	1.3	.8	.5							6.4	9.4	8.0
200-220	1.8	5.6	8.7	1.4	.5							18.0	9.9	10.0
230-250	1.8	11.7	10.4	1.4	.5							25.8	9.2	9.0
(W) 260-280	3.5	9.6	5.6	.6								19.4	7.6	7.0
290-310	2.6	6.9	1.1									10.6	6.5	6.0
320-340	1.1	3.0	1.3									5.5	7.2	8.0
VARIABLE														
CALM	////////////////////											6.9	////////	
TOTALS	14.4	43.9	29.1	4.2	1.5							100.0	7.8	8.0

TOTAL NUMBER OF OBSERVATIONS 623

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.3	.6										1.9	4.7	4.0
020-040														
050-070	.2	.2										.4	5.0	5.0
(E) 080-100														
110-130		.9										.9	7.3	7.0
140-160	.2	.2		.2	.2							.9	11.8	12.0
(S) 170-190	.2	1.1	3.2	.6								5.1	10.8	10.0
200-220	1.5	7.9	10.0	1.7	.2							21.3	9.8	10.0
230-250	4.1	11.3	9.4	1.3								26.0	8.3	8.0
(W) 260-280	3.8	10.9	4.5	.2								19.4	7.1	6.0
290-310	3.0	4.9	1.1									9.0	5.9	6.0
320-340	.9	2.6	.4									3.8	6.4	6.0
VARIABLE														
CALM	////////////////////											11.3	////////	
TOTALS	15.2	40.6	28.6	4.0	.4							100.0	7.2	8.0
TOTAL NUMBER OF OBSERVATIONS 469														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	.4											.4	4.0	4.0
020-040	.4											.4	4.0	4.0
050-070														
(E) 080-100														
110-130	.8	.4										1.2	3.3	4.0
140-160	.4	1.7										2.1	5.8	5.0
(S) 170-190	4.1	5.8	3.7									13.7	6.7	6.0
200-220	8.7	17.0	5.0									30.7	6.5	6.0
230-250	8.7	11.6	1.7									22.0	5.7	6.0
(W) 260-280	2.1	.4										2.5	4.0	3.5
290-310	.8		.4									1.2	6.0	4.0
320-340	.4	.4										.8	6.0	6.0
VARIABLE														
CALM	////////////////////////////////////											24.9	////////////////////////////////	
TOTALS	26.8	37.3	10.8									100.0	4.6	6.0

TOTAL NUMBER OF OBSERVATIONS 241

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.6	1.1	.0									2.7	4.7	4.0
020-040	1.4	1.0	.1									2.5	4.8	4.0
050-070	.8	.8	.4									1.9	6.2	6.0
(E) 080-100	.6	.3	.3									1.1	6.0	4.0
110-130	1.1	.4	.1									1.6	4.3	4.0
140-160	2.2	1.1	.2	.0	.0							3.6	4.9	4.0
(S) 170-190	2.4	2.1	1.5	.3	.1							6.4	7.1	6.0
200-220	2.9	5.8	5.0	.7	.1							14.6	8.3	8.0
230-250	3.9	8.0	4.7	.6	.1							17.3	7.7	8.0
(W) 260-280	3.8	6.1	2.3	.2								12.3	6.6	6.0
290-310	3.0	3.3	.4									6.7	5.4	5.0
320-340	2.1	2.1	.4									4.5	5.5	5.0
VARIABLE														
CALM	////////////////////											24.8	////////	
TOTALS	25.8	32.1	15.4	1.8	.3							100.0	5.1	6.0
TOTAL NUMBER OF OBSERVATIONS 3371														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	MEAN	MEDIAN
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65		
(N) 350-010													
020-040													
050-070													
(E) 080-100													
110-130													
140-160													
(S) 170-190													
200-220													
230-250													
(W) 260-280													
290-310													
320-340													
VARIABLE													
CALM	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	////////////////////	.0	////////////////////	
TOTALS												.0	.0

TOTAL NUMBER OF OBSERVATIONS 0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.2	.3										1.5	3.7	4.0
020-040	2.3	.3	.3									2.9	4.6	4.0
050-070	1.1	.5	.2									1.7	4.6	4.0
(E) 080-100	1.1	.6	1.1									2.8	7.0	6.0
110-130	4.0	.6	.2									4.8	3.5	3.0
140-160	8.4	2.5	.2									11.0	3.8	4.0
(S) 170-190	3.5	1.1										4.6	3.8	4.0
200-220	2.6	.8	.2									3.5	3.9	3.0
230-250	1.4	.3	.2									1.8	4.1	3.0
(W) 260-280	.6	.5										1.1	5.3	4.0
290-310	1.5											1.5	2.9	3.0
320-340	1.5	.2										1.7	3.1	3.0
VARIABLE														
CALM	////////////////////											61.0	////////	
TOTALS	29.2	7.7	2.4									100.0	1.6	4.0

TOTAL NUMBER OF OBSERVATIONS 652

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.8	1.1										3.0	4.3	4.0
020-040	3.4	1.0	.1									4.5	4.1	4.0
050-070	.6	.7	1.4									2.7	8.4	10.0
(E) 080-100	.7	1.8	.7		.1							3.4	7.4	7.0
110-130	1.0	.3										1.3	3.6	3.0
140-160	1.1	1.0										2.1	5.1	4.0
(S) 170-190	1.7	1.3	.4									3.4	5.6	4.5
200-220	1.8	3.1	1.1		.1							6.2	6.8	6.0
230-250	3.4	4.8	.8									9.0	5.8	6.0
(W) 260-280	6.9	3.5	.3									10.7	4.4	4.0
290-310	6.5	2.5										9.0	4.0	4.0
320-340	6.3	2.4										8.7	4.0	4.0
VARIABLE														
CALM	////////////////////////////////////											36.1	////////	
TOTALS	35.2	23.5	4.8		.2							100.0	3.2	4.0
TOTAL NUMBER OF OBSERVATIONS 711														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.1	1.5	.1									4.7	4.8	4.0
020-040	1.3	1.3	.4									3.1	5.4	5.0
050-070	.9	.7	.3									1.9	6.2	6.0
(E) 080-100		.6	.3	.1								1.0	9.3	9.0
110-130	1.2	.3	.3									1.8	4.9	4.0
140-160	.1	1.0										1.2	6.4	6.0
(S) 170-190	1.0	2.2	1.9									5.2	7.7	8.0
200-220	2.8	5.3	3.4	.3								11.8	7.4	7.0
230-250	2.5	8.1	4.4	.3								15.3	7.8	8.0
(W) 260-280	6.2	8.0	2.1									16.2	5.8	6.0
290-310	7.5	8.0	.7									16.2	5.3	5.0
320-340	4.4	4.1	.3	.1								9.0	5.1	5.0
VARIABLE														
CALM	////////////////////											12.7	////////	
TOTALS	31.0	41.1	14.2	.8								100.0	5.5	6.0
TOTAL NUMBER OF OBSERVATIONS 679														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.8	.5	.8									3.0	6.1	4.0
020-040	1.3	1.0	.2									2.4	5.4	4.0
050-070		.6	.2									.8	7.8	8.0
(E) 080-100	.5	.3	.2									1.0	5.8	4.5
110-130				.2								.2	19.0	19.0
140-160	.2	.6	.2									1.0	7.2	7.0
(S) 170-190	.8	2.2	2.2	.2								5.5	8.5	8.5
200-220	.6	4.5	6.6	.5	.3							12.5	9.8	10.0
230-250	1.4	10.3	10.4	1.3								23.4	9.2	9.5
(W) 260-280	2.6	13.0	5.3	.3								21.2	7.6	7.0
290-310	4.5	9.1	1.1									14.8	6.0	6.0
320-340	2.7	4.2	.8									7.7	5.9	6.0
VARIABLE														
CALM	////////////////////////////////////											6.6	////////////////////////////////	
TOTALS	16.4	46.3	28.0	2.5	.3							100.0	7.3	8.0

TOTAL NUMBER OF OBSERVATIONS 623

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	.4	.4	.2	.2								1.2	8.0	7.0
020-040	.6	.6										1.2	5.3	5.0
050-070	.2		.4									.6	8.3	10.0
(E) 080-100		.2	.6		.2							1.0	12.4	10.0
110-130			.2	.2								.4	14.0	14.0
140-160		.4	.4									.8	9.5	9.0
(S) 170-190	.2	1.0	1.6	.4								3.3	10.3	10.0
200-220	.4	8.8	7.4	.8								17.4	9.2	9.0
230-250	2.0	15.4	8.4	.4								26.2	8.3	8.0
(W) 260-280	5.5	11.5	3.9	.2								21.1	6.6	6.0
290-310	3.9	8.6	.4									12.9	5.7	6.0
320-340	.8	2.7	.2									3.7	6.1	6.0
VARIABLE														
CALM	////////////////////////////////////											10.0	////////////////////////////////	
TOTALS	14.0	49.6	23.7	2.2	.2							100.0	6.9	8.0

TOTAL NUMBER OF OBSERVATIONS 488

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 21-23

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
(N) 350-010				.4								.4	16.0	16.0
020-040	1.1											1.1	3.0	3.0
050-070	.4	.4										.7	5.0	5.0
(E) 080-100	.4	.7	.4									1.4	7.0	7.5
110-130	.4	.7										1.1	5.3	5.0
140-160	.7	.4	.4									1.4	6.5	5.5
(S) 170-190	4.3	1.8	1.4									7.5	5.7	4.0
200-220	13.9	16.0	3.6	.4								33.8	5.9	6.0
230-250	12.5	11.7	1.1									25.3	5.1	5.0
(W) 260-280	2.8	1.8	.4									5.0	5.8	4.0
290-310	1.4											1.4	3.3	3.5
320-340														
VARIABLE														
CALM	////////////////////////////////////											21.0	//////////	
TOTALS	37.9	33.5	7.3	.8								100.0	4.4	5.0

TOTAL NUMBER OF OBSERVATIONS 281

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL	MEAN	MEDIAN
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.6	.7	.2	.1								2.6	5.2	4.0
020-040	1.8	.8	.2									2.8	4.7	4.0
050-070	.6	.5	.5									1.5	6.9	7.0
(E) 080-100	.5	.8	.6	.0	.1							1.9	7.7	7.5
110-130	1.2	.3	.1	.1								1.7	4.5	4.0
140-160	2.0	1.1	.1									3.2	4.6	4.0
(S) 170-190	1.7	1.6	1.2	.1								4.7	6.8	6.0
200-220	2.7	5.2	3.5	.3	.1							11.8	7.6	8.0
230-250	3.0	7.7	4.3	.3								15.3	7.6	8.0
(W) 260-280	4.3	6.5	2.0	.1								12.9	6.3	6.0
290-310	4.6	5.0	.4									10.0	5.2	5.0
320-340	3.1	2.5	.2	.0								5.8	4.9	4.0
VARIABLE														
CALM	////////////////////											25.9	////////	
TOTALS	27.1	32.7	13.3	1.0	.2							100.0	4.7	6.0
TOTAL NUMBER OF OBSERVATIONS 3434														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS												
DIRECTION	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL
(DEGREES)												% WIND
(N) 350-010												
020-040												
050-070												
(E) 080-100												
110-130												
140-160												
(S) 170-190												
200-220												
230-250												
(W) 260-280												
290-310												
320-340												
VARIABLE												
CALM	////////////////////											.0
TOTALS												.0

TOTAL NUMBER OF OBSERVATIONS 0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.3	.5	.2									1.9	4.4	4.0
020-040	2.1	1.4										3.5	4.5	4.0
050-070	2.6	.6	.3									3.5	4.4	3.5
(E) 080-100	1.9	1.4	.3									3.7	5.3	4.0
110-130	3.0											3.0	3.1	3.0
140-160	5.5	4.8	.2									10.4	4.8	4.0
(S) 170-190	5.8	2.1	.3									8.2	4.0	4.0
200-220	3.0	2.2	.6									5.9	5.5	4.0
230-250	1.1	1.6										2.7	4.9	5.0
(W) 260-280	.6	.3										1.0	4.2	4.0
290-310	.3	.3										.6	5.0	5.0
320-340	.3	.8										1.1	5.6	5.0
VARIABLE														
CALM	////////////////////											54.3	////////	
TOTALS	27.5	16.0	1.9									100.0	2.1	4.0
TOTAL NUMBER OF OBSERVATIONS 623														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 09-11

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-2	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
(N) 350-010	2.7	1.4										4.1	4.2	4.0
020-040	3.5	1.4	.2									5.0	4.2	4.0
050-070	2.4	1.4										3.8	4.5	4.0
(E) 080-100	1.4	1.1		.3								2.7	6.6	5.0
110-130	1.1	.3										1.4	4.0	3.0
140-160	1.8	2.7										4.5	5.0	5.5
(S) 170-190	1.8	3.6	.8	.2								6.3	6.1	6.0
200-220	2.3	3.6	1.1									6.9	6.1	6.0
230-250	3.6	4.8	1.1									9.5	5.7	6.0
(W) 260-280	4.4	2.9	.6									7.8	5.0	4.0
290-310	3.5	2.0	.3									5.7	4.6	4.0
320-340	3.8	.5	.2									4.4	3.5	3.0
VARIABLE														
CALM	////////////////////////////////////											38.0	////////////////////////////////	
TOTALS	32.3	25.7	4.3	.3								100.0	3.2	4.0

TOTAL NUMBER OF OBSERVATIONS 665

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	2.0	2.4	.5									4.9	5.5	5.0
020-040	2.1	3.0	.3									5.5	5.5	5.0
050-070	1.5	1.1	.5									3.0	5.4	4.5
(E) 080-100	1.1	1.2	.2									2.4	5.1	5.0
110-130	.9	.6	.2									1.7	4.5	4.0
140-160	1.5	.5										2.0	4.0	4.0
(S) 170-190	2.0	2.6	.8									5.3	5.9	6.0
200-220	2.0	2.7	2.7									7.5	7.7	7.0
230-250	3.0	7.3	2.4									12.8	6.7	6.0
(W) 260-280	5.3	7.2	1.2									13.7	5.8	6.0
290-310	6.3	5.5	1.1									12.8	5.3	5.0
320-340	4.4	4.6	.3									9.3	5.1	5.0
VARIABLE														
CALM	////////////////////////////////////											19.1	////////	
TOTALS	32.1	38.7	10.2									100.0	4.7	5.0
TOTAL NUMBER OF OBSERVATIONS 656														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 15-17

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
(N) 350-010	2.4	1.6	.3									4.4	5.1	4.0
020-040	.8	1.9	.2									2.9	6.1	6.0
050-070	.2	1.0	.2									1.3	6.9	7.5
(E) 080-100	.8	.8	.8									2.4	6.7	6.0
110-130	.5	.2										.6	4.8	4.0
140-160	.6	.3	.5			.2						1.6	8.6	7.0
(S) 170-190	.6	1.9	.8		.2							3.6	7.4	7.0
200-220	1.3	4.8	3.9	.5								10.5	8.5	8.0
230-250	2.6	10.5	4.4									17.4	7.5	8.0
(W) 260-280	4.4	8.6	3.1									16.0	6.7	7.0
290-310	4.2	14.9	2.7									21.8	6.7	6.0
320-340	1.8	4.7	.5									6.9	6.0	6.0
VARIABLE														
CALM	////////////////////////////////////											10.5	////////////////////////////////	
TOTALS	20.2	51.2	17.4	.5	.2	.2						100.0	6.2	6.0

TOTAL NUMBER OF OBSERVATIONS 619

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.2	.9	.2									2.3	5.2	4.5
020-040	.5											.5	4.0	4.0
050-070	.2	.2	.2		.2							.9	10.0	9.0
(E) 080-100	.2	1.6	.2				.2					2.3	10.0	8.0
110-130		.2	.2	.5								.9	12.0	12.5
140-160	.5	.7	1.6	.2								3.1	10.2	10.0
(S) 170-190	.5	.7	2.3	.2								3.8	9.8	10.0
200-220	.5	5.2	7.0									12.7	9.2	10.0
230-250	3.5	14.8	4.0			.2						22.5	7.3	7.5
(W) 260-280	5.9	11.7	3.1	.2								20.9	6.3	6.0
290-310	5.2	7.0	.7									12.9	5.6	5.0
320-340	1.4	1.6	.9									4.0	6.2	5.0
VARIABLE														
CALM	////////////////////////////////////											13.1	////////	
TOTALS	19.6	44.6	20.4	1.1	.2	.2	.2					100.0	6.4	7.0
TOTAL NUMBER OF OBSERVATIONS 426														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010		.5										.5	8.0	8.0
020-040		.5	.9									1.4	9.3	10.0
050-070		.5										.5	6.0	6.0
(E) 080-100	.5	.9										1.4	6.0	8.0
110-130	.5	1.4	.5									2.4	6.6	8.0
140-160		4.3	.9	.9								6.2	9.6	8.0
(S) 170-190	3.3	1.9	1.4		.5							7.1	6.9	6.0
200-220	6.6	10.9	1.9		.5							19.9	6.3	6.0
230-250	7.6	11.8	5.2									24.6	6.4	6.0
(W) 260-280	1.4	3.8	.5									5.7	5.8	6.0
290-310														
320-340		.5										.5	6.0	6.0
VARIABLE														
CALM	////////////////////											29.9	////////	
TOTALS	19.9	37.0	11.3	.9	1.0							100.0	4.7	6.0

TOTAL NUMBER OF OBSERVATIONS 211

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.8	1.3	.2									3.4	5.0	4.0
020-040	1.8	1.6	.2									3.6	5.1	4.5
050-070	1.4	.9	.2		.0							2.5	5.2	4.0
(E) 080-100	1.1	1.2	.3	.1			.0					2.7	6.4	5.0
110-130	1.1	.3	.1	.1								1.6	4.7	4.0
140-160	1.9	2.0	.4	.1		.0						4.5	5.9	5.0
(S) 170-190	2.3	2.3	.9	.1	.1							5.7	6.0	5.0
200-220	2.2	4.1	2.7	.1	.0							9.2	7.4	7.0
230-250	3.1	7.6	2.4			.0						13.1	6.8	6.0
(W) 260-280	3.8	5.6	1.4	.0								10.9	6.1	6.0
290-310	3.6	5.4	.9									9.9	5.9	6.0
320-340	2.3	2.3	.3									4.9	5.2	5.0
VARIABLE														
CALM	////////////////////											28.1	////////	
TOTALS	26.4	34.6	10.0	.5	.1							100.0	4.4	6.0

TOTAL NUMBER OF OBSERVATIONS 3200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											OTAL	MEAN	MEDIAN
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010			100.0									100.0	12.0	12.0
020-040														
050-070														
(E) 080-100														
110-130														
140-160														
(S) 170-190														
200-220														
230-250														
(W) 260-280														
290-310														
320-340														
VARIABLE														
CALM	////////////////////											.0	////////////////	
TOTALS			100.0									100.0	12.0	12.0

TOTAL NUMBER OF OBSERVATIONS 1

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND	
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64				GE 65
(N) 350-010	.6	.9										1.5	5.1	5.0
020-040	1.4	.3										1.7	3.8	4.0
050-070	2.1	1.2	.2									3.5	4.5	4.0
(E) 080-100	3.9	2.3	.6									6.8	5.1	4.0
110-130	2.7	.6	.2									3.5	3.9	4.0
140-160	4.2	2.7	1.1	.3								8.3	5.5	4.0
(S) 170-190	6.2	2.1		.2								8.4	4.1	4.0
200-220	1.7	.9	.5									3.0	5.4	4.0
230-250	.5	.2	.2									.8	5.4	4.0
(W) 260-280														
290-310	.2	.2										.	4.0	4.0
320-340	.5	.3										.8	4.6	4.0
VARIABLE														
CALM	////////////////////////////////////											61.6	////////////////////////////////	
TOTALS	24.0	11.7	2.8	.5								100.0	1.8	4.0

TOTAL NUMBER OF OBSERVATIONS 664

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	2.9	1.0										3.8	4.3	4.0
020-040	2.7	1.6	.4									4.8	4.9	4.0
050-070	3.0	1.9	.4									5.3	4.9	4.0
(E) 080-100	2.2	1.8	.5									4.5	5.5	5.0
110-130	1.9	1.1	.1									3.1	4.6	4.0
140-160	2.0	1.5	.1									3.7	4.9	4.0
(S) 170-190	2.2	1.2	.7									4.1	5.6	4.0
200-220	2.3	2.7	.7	.1								5.9	6.4	6.0
230-250	3.8	2.9	.4									7.1	4.9	4.0
(W) 260-280	3.1	2.2										5.3	4.3	4.0
290-310	3.6	.3										3.8	3.4	3.5
320-340	2.2	1.1										3.3	4.4	4.0
VARIABLE														
CALM	////////////////////////////////////											45.2	////////////////////////////////	
TOTALS	31.9	19.3	3.3	.1								100.0	2.7	4.0

TOTAL NUMBER OF OBSERVATIONS 732

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.0	2.0	.1	.1								5.3	5.2	4.0
020-040	3.4	2.4	.4	.1								6.4	5.0	4.0
050-070	1.7	1.4										3.1	4.6	4.0
(E) 080-100	1.1	1.6	.3	.1								3.1	6.5	6.5
110-130	.9	1.4	.6									2.8	6.2	5.5
140-160	1.0	.7	.4									2.1	6.3	5.0
(S) 170-190	1.6	3.3	.6									5.4	6.5	6.0
200-220	2.8	2.4	1.1	.1								6.6	6.3	6.0
230-250	5.1	6.0	.9	.4								12.4	5.9	5.0
(W) 260-280	4.3	4.1	.4									8.8	5.3	5.0
290-310	5.3	5.8	.3									11.4	5.1	5.0
320-340	3.4	5.3	.4									9.1	5.2	5.0
VARIABLE														
CALM	////////////////////											23.4	////////	
TOTALS	33.6	36.4	5.5	.8								100.0	4.3	5.0

TOTAL NUMBER OF OBSERVATIONS 702

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 15-17

DIRECTION (DEGREES)	SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.8	1.1	.3									3.2	5.0	4.0
020-040	1.2	1.5	.6									3.4	5.6	5.0
050-070	1.2	1.1	.2									2.4	5.3	4.5
(E) 080-100	.5	.5	.8									1.7	8.5	8.0
110-130	.8	.6	.3									1.7	6.5	6.0
140-160	.3	1.2	1.7	.2								3.4	9.0	10.0
(S) 170-190	1.7	1.8	.8	.5	.2							4.9	7.7	7.0
200-220	2.1	3.5	2.7	.2	.2							8.7	7.6	6.0
230-250	2.1	8.1	2.7	.3	.2							13.4	7.6	8.0
(W) 260-280	3.4	7.3	2.1									12.8	6.4	6.0
290-310	5.2	7.8	1.7									14.7	6.2	6.0
320-340	5.6	5.0	1.5									12.2	5.7	5.0
VARIABLE														
CAL	////////////////////////////////////											17.6	////////////////////////////////	
TOTALS	25.9	39.5	15.4	1.2	.6							100.0	5.5	6.0

TOTAL NUMBER OF OBSERVATIONS 655

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.4	.6	.2									2.3	4.6	4.0
020-040	.4	1.4	.2									2.1	5.4	5.0
050-070		.4										.4	7.0	7.0
(E) 080-100	.8	.8	.8	.2								2.7	8.4	7.0
110-130	.6	.8	.2		.2							1.9	8.0	8.0
140-160	1.0	2.7	1.2									5.0	7.5	7.5
(S) 170-190	1.9	2.9	.6		.2							5.6	6.7	6.0
200-220	1.4	6.2	2.7	.2	.6							11.2	8.3	8.0
230-250	3.5	7.2	1.9									12.6	6.3	6.0
(W) 260-280	4.8	5.6	1.4									11.8	6.0	6.0
290-310	5.2	6.8										12.0	5.1	5.0
320-340	2.5	2.5	.8									5.8	5.6	5.0
VARIABLE														
CALM	////////////////////											26.9	////////	
TOTALS	23.5	37.9	10.0	.4	1.0							100.0	4.7	6.0
TOTAL NUMBER OF OBSERVATIONS 484														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65		
(N) 350-010													
020-040	.4											.4	2.0
050-070		1.3			.4							1.8	10.0
(E) 080-100		1.3										1.3	7.7
110-130	.9	.9										1.8	5.3
140-160	1.3	4.9	1.3		.4							8.0	7.9
(S) 170-190	5.4	4.0	1.3									10.7	5.5
200-220	5.8	10.7	1.8									18.3	6.2
230-250	7.6	3.6	1.3	.4								12.9	5.4
(W) 260-280	2.7											2.7	2.3
290-310	.4	.4										.9	4.0
320-340		.4										.4	6.0
VARIABLE													
CALM	////////////////////										40.6	////////////////	
TOTALS	24.5	27.5	5.7	.4	.8							100.0	3.6

TOTAL NUMBER OF OBSERVATIONS 224

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.9	1.1	.1	.0								3.1	4.8	4.0
020-040	1.8	1.4	.3	.0								3.6	5.0	4.0
050-070	1.6	1.3	.1		.0							3.1	5.1	4.0
(E) 080-100	1.6	1.4	.5	.1								3.7	6.1	5.0
110-130	1.4	.9	.3		.0							2.6	5.4	4.0
140-160	1.7	1.9	.9	.1	.0							4.7	6.5	6.0
(S) 170-190	2.9	2.3	.6	.1	.1							6.0	5.8	5.0
200-220	2.4	3.5	1.5	.1	.1							7.5	6.9	6.0
230-250	3.3	4.6	1.2	.2	.0							9.3	6.2	6.0
(W) 260-280	3.0	3.5	.7									7.2	5.6	5.5
290-310	3.6	3.7	.4									7.7	5.3	5.0
320-340	2.7	2.7	.5									5.8	5.4	5.0
VARIABLE														
CALM	////////////////////////////////////											35.8	////////////////////////////////	
TOTALS	27.9	28.3	7.1	.6	.2							100.0	3.7	5.0
TOTAL NUMBER OF OBSERVATIONS 3461														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

WIND SPEED IN KNOTS

DIRECTION	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL	MEAN	MEDIAN
(DEGREES)												%	WIND	WIND
(N) 350-010														
020-040														
050-070														
(E) 080-100														
110-130														
140-160														
(S) 170-190												100.0	20.0	20.0
200-220														
230-250														
(W) 260-280														
290-310														
320-340														
VARIABLE														
CALM	////////////////////											.0	////////////////	
TOTALS												100.0	20.0	20.0

TOTAL NUMBER OF OBSERVATIONS 1

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	.7											.7	2.8	2.5
020-040	2.1	.8										3.0	3.9	4.0
050-070	2.1	.8	.5									3.5	5.1	4.0
(E) 080-100	1.5	2.1	2.3									6.0	7.2	7.0
110-130	2.8	.8	.2									3.8	4.0	4.0
140-160	11.2	3.6			.2							15.0	4.0	4.0
(S) 170-190	3.3	2.3	.2	.2								6.0	5.0	4.0
200-220	.8	1.2										2.0	5.0	5.0
230-250	.3	.5	.3									1.2	6.7	6.0
(W) 260-280	.7	.3										1.0	4.5	4.0
290-310	.2											.2	4.0	4.0
320-340	.2	.3										.5	5.7	5.0
VARIABLE														
CALM	////////////////////////////////////											57.4	////////////////////////////////	
TOTALS	25.9	12.7	3.5	.2	.2							100.0	2.0	4.0
TOTAL NUMBER OF OBSERVATIONS 605														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 09-11

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
(N) 350-010	7.2	2.1	.1									9.4	4.0	4.0
020-040	6.5	1.8	.3									8.5	3.9	4.0
050-070	1.5	2.6	1.6									5.7	7.1	8.0
(E) 080-100	2.3	2.3	3.2	.1								8.1	7.7	8.0
110-130	.6		1.0									1.6	7.8	10.0
140-160	1.5	.9	.7									3.1	6.1	5.0
(S) 170-190	2.1	1.5	.9									4.4	6.3	5.5
200-220	1.0	1.2	.4									2.6	6.5	6.0
230-250	1.5	2.1	1.3									4.8	7.1	6.0
(W) 260-280	2.5	1.5	.3									4.3	4.6	4.0
290-310	2.9	.9										3.8	3.8	4.0
320-340	3.5	1.0										4.5	3.9	4.0
VARIABLE														
CALM	////////////////////////////////////											39.1	////////	
TOTALS	33.1	17.9	9.8	.1								100.0	3.4	4.0

TOTAL NUMBER OF OBSERVATIONS 682

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	4.1	4.0	.5									8.6	5.2	5.0
020-040	3.7	3.2	.8									7.7	5.5	5.0
050-070	1.4	2.9	1.8	.2								6.3	7.7	8.0
(E) 080-100	1.4	1.7	1.1	.3								4.4	7.1	6.0
110-130	.6	.6	.2									1.4	5.8	5.0
140-160	.3	.9	.3	.2								1.7	7.4	7.0
(S) 170-190	.9	3.2	1.8	.8								6.7	8.8	8.0
200-220	.8	2.1	2.3									5.2	8.3	8.5
230-250	2.1	3.1	1.4	.3								6.9	7.1	8.0
(W) 260-280	5.4	2.1	1.2									8.7	5.4	4.0
290-310	7.1	5.7	.2									12.9	4.7	4.0
320-340	6.4	3.8	.8	.2								11.2	5.0	4.0
VARIABLE														
CALM	////////////////////											18.3	////////	
TOTALS	34.2	33.3	12.4	2.0								100.0	5.0	5.0

TOTAL NUMBER OF OBSERVATIONS 652

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.7	2.7	.3	.3								7.0	5.5	4.0
020-040	1.8	1.2	.8									3.8	5.9	5.0
050-070	1.7	1.8	1.7									5.2	7.0	7.0
(E) 080-100	1.2	1.7	1.0									3.8	6.6	6.0
110-130	.2	.7										.8	5.6	5.0
140-160	.2	.7	.5	.3								1.7	9.6	9.0
(S) 170-190	.5	.7	1.3	.2								2.7	8.8	10.0
200-220	.8	4.2	3.8	.2								9.0	8.7	9.0
230-250	2.3	3.8	2.7	.3								9.2	7.6	7.0
(W) 260-280	6.0	7.0	2.0	.5								15.5	6.4	6.0
290-310	6.8	6.8	1.0									14.7	5.4	5.0
320-340	6.0	5.5	.5									12.0	5.1	4.5
VARIABLE														
CALM	////////////////////////////////////											14.5	////////	
TOTALS	31.2	36.8	15.6	1.8								100.0	5.5	6.0

TOTAL NUMBER OF OBSERVATIONS 599

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.2	2.0	.7									4.0	6.6	6.0
020-040	.5	1.0										1.5	5.5	5.5
050-070	1.2	2.0										3.2	5.8	6.0
(E) 080-100	1.5	1.7										3.2	5.0	5.0
110-130	.2	.5	.2									1.0	6.5	7.0
140-160	.2	.7	.5		.2							1.7	9.7	8.0
(S) 170-190	.5	2.5	2.0	.2								5.2	8.1	7.0
200-220	2.0	4.2	2.2									8.4	7.5	8.0
230-250	4.5	4.7	.5									9.7	5.3	5.0
(W) 260-280	6.0	4.5	1.2									11.7	5.6	4.0
290-310	6.0	2.5										8.4	4.3	4.0
320-340	2.7	1.5	.2									4.5	4.9	4.0
VARIABLE														
CALM	////////////////////											37.5	////////	
TOTALS	26.5	27.8	7.5	.2	.2							100.0	3.7	5.0
TOTAL NUMBER OF OBSERVATIONS 403														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 21-23

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND

(N) 350-010														
020-040	1.3											1.3	2.5	2.5
050-070	2.0		.7									2.7	5.5	4.0
(E) 080-100		.7										.7	8.0	8.0
110-130	1.3		1.3	.7								3.4	9.4	10.0
140-160	2.0	.7	1.3									4.0	6.8	4.5
(S) 170-190	6.0	2.7	.7									9.4	4.8	4.0
200-220	4.7	2.7										7.4	4.1	4.0
230-250	2.0	4.7										6.7	5.5	6.0
(W) 260-280	2.0											2.0	2.7	2.0
290-310														
320-340														

VARIABLE														
CALM	////////////////////////////////////											62.4	//////////	
TOTALS	21.3	11.5	4.0	.7								100.0	2.0	4.0

TOTAL NUMBER OF OBSERVATIONS 149

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65		
(N) 350-010	3.5	2.1	.3	.1							5.9	4.9	4.0
020-040	3.1	1.6	.4								5.1	4.8	4.0
050-070	1.6	2.0	1.2	.0							4.8	6.8	6.0
(E) 080-100	1.5	1.9	1.6	.1							5.1	7.1	7.0
110-130	.9	.5	.4	.0							1.8	5.8	4.0
140-160	2.8	1.4	.5	.1	.1						4.7	5.3	4.0
(S) 170-190	1.7	2.0	1.2	.3							5.2	7.0	6.0
200-220	1.2	2.4	1.6	.0							5.3	7.5	8.0
230-250	2.0	2.8	1.2	.1							6.1	6.8	6.0
(W) 260-280	3.9	2.8	.9	.1							7.6	5.7	4.0
290-310	4.3	3.0	.2								7.5	4.8	4.0
320-340	3.7	2.4	.3	.0							6.4	4.9	4.0
VARIABLE													
CALM	////////////////////////////////////										34.4	////////////////////////////////	
TOTALS	30.2	24.9	9.8	.8	.1						100.0	3.9	5.0
TOTAL NUMBER OF OBSERVATIONS 3090													

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL	MEAN %	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010														
020-040														
050-070														
(E) 080-100														
110-130														
140-160														
(S) 170-190														
200-220														
230-250														
(W) 260-280														
290-310														
320-340														
VARIABLE														
CALM	////////////////////											.0	////////////////	
TOTALS													.0	.0

TOTAL NUMBER OF OBSERVATIONS 0

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	.6	.3	.2									1.1	5.3	4.0
020-040	3.4	.3										3.7	3.5	3.5
050-070	3.2	1.5	.2									4.9	4.4	4.0
(E) 080-100	3.2	1.4	.2									4.8	4.4	4.0
110-130	2.3	.8	.2									3.2	4.4	4.0
140-160	8.3	1.7										10.0	3.7	4.0
(S) 170-190	3.4	.3		.2								3.9	3.5	3.0
200-220	1.5	1.1	.2									2.8	4.8	4.0
230-250	.3	.6	.5									1.4	7.2	6.0
(W) 260-280	.2	.2										.3	4.5	4.5
290-310	.2											.2	4.0	4.0
320-340	.3											.3	3.0	3.0
VARIABLE														
CALM	////////////////////											63.4	////////	
TOTALS	26.9	8.2	1.5	.2								100.0	1.5	4.0
TOTAL NUMBER OF OBSERVATIONS 648														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	7.7	3.3										11.0	4.2	4.0
020-040	9.6	5.8	.9									16.3	4.6	4.0
050-070	3.1	2.9	2.4		.1							8.6	7.0	6.0
(E) 080-100	1.1	.9	2.1	.1	.1							4.4	9.1	10.0
110-130	.4	.3	.1									.9	5.0	4.5
140-160	.6	1.1	.3									2.0	6.8	8.0
(S) 170-190	1.0	.9	.3	.3								2.4	6.9	6.0
200-220	.9	.4	.6	.3								2.1	8.0	8.0
230-250	1.3	1.0	1.1	.3								3.7	8.0	8.0
(W) 260-280	1.6	.9	.3									2.7	4.8	4.0
290-310	2.0	.9	.3	.1								3.3	5.0	4.0
320-340	2.6	1.7	.1									4.4	4.8	4.0
VARIABLE														
CALM	////////////////////											38.2	////////	
TOTALS	31.9	20.1	8.5	1.1	.2							100.0	3.5	4.0

TOTAL NUMBER OF OBSERVATIONS 701

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	5.1	3.8	.3									9.1	4.9	4.0
020-040	2.6	2.7	.9									6.2	5.9	6.0
050-070	1.9	4.0	2.7	.1	.4							9.2	8.4	8.0
(E) 080-100	1.0	1.7	1.4	.1								4.3	8.0	7.0
110-130	.7	.4	.1									1.3	5.2	4.0
140-160	.7	.6										1.3	4.4	4.0
(S) 170-190	.4	.9	.6	.3								2.2	8.3	7.0
200-220	.7	1.9	2.6	.4	.1							5.8	9.7	10.0
230-250	2.3	2.7	2.2	.1								7.4	7.1	6.0
(W) 260-280	4.0	2.7	1.2		.1							8.1	6.1	4.5
290-310	5.2	2.6	.6	.1								8.5	4.9	4.0
320-340	7.6	3.6	.6									11.8	4.4	4.0
VARIABLE														
CALM	////////////////////											24.8	////////	
TOTALS	32.2	27.6	13.2	1.1	.6							100.0	4.8	5.0
TOTAL NUMBER OF OBSERVATIONS 693														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 80
MONTH: OCT HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.4	3.2	.2									6.7	4.9	4.5
020-040	1.5	2.9	.6									5.1	5.9	6.0
050-070	1.4	3.2	2.6	.2								7.4	7.6	8.0
(E) 080-100	.5	1.1	.6	.2								2.3	7.9	8.0
110-130	.5	.2										.6	4.3	4.0
140-160		.3	.2									.5	8.3	8.0
(S) 170-190	.5	.9	.5	.3								2.1	9.0	8.0
200-220	.9	4.6	2.0	.5								8.0	8.3	8.0
230-250	2.5	4.7	3.7	.3	.2							11.3	7.9	7.0
(W) 260-280	5.8	5.5	2.0	.2	.3							13.8	6.1	5.0
290-310	8.6	4.6	.3	.2								13.6	4.7	4.0
320-340	6.6	4.3	.3	.2								11.3	4.9	4.0
VARIABLE														
CALM	////////////////////											17.3	////////	
TOTALS	32.2	35.5	13.0	2.1	.5							100.0	5.2	6.0

TOTAL NUMBER OF OBSERVATIONS 653

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.3	.4										1.8	3.6	4.0
020-040	1.1	.7										1.8	4.0	4.0
050-070	2.2	1.1										3.4	4.7	4.0
(E) 080-100	.7	.7	.2									1.6	5.9	5.0
110-130	.4	.9	.2									1.6	6.3	6.0
140-160	1.1	.4										1.6	4.0	4.0
(S) 170-190	1.1	.9	.9									2.9	6.8	6.0
200-220	3.4	3.1	1.3		.2							8.1	6.5	6.5
230-250	4.9	2.2	.4									7.6	4.5	4.0
(W) 260-280	6.1	2.0	.9									9.0	4.8	4.0
290-310	3.6	2.5	.4									6.5	4.6	4.0
320-340	1.3	.2										1.6	3.3	3.0
VARIABLE														
CALM	////////////////////											52.7	////////	
TOTALS	27.2	15.1	4.3		.2							100.0	2.4	4.0
TOTAL NUMBER OF OBSERVATIONS 446														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010														
020-040	.7											.7	3.0	3.0
050-070	1.5											1.5	3.0	3.0
(E) 080-100	2.2	1.5										3.7	4.4	.0
110-130	2.2											2.2	3.3	4.0
140-160	8.1											8.1	3.5	4.0
(S) 170-190	13.3	3.0										16.3	3.7	3.5
200-220	3.7	2.2										5.9	4.5	4.0
230-250	3.7	.7	.7									5.2	4.7	4.0
(W) 260-280	2.2											2.2	2.7	2.0
290-310	.7											.7	3.0	3.0
320-340		.7										.7	6.0	6.0
VARIABLE														
CALM	////////////////////////////////////											52.6	////////////////////////////////	
TOTALS	38.3	8.1	.7									100.0	1.8	4.0

TOTAL NUMBER OF OBSERVATIONS 135

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	3.7	2.3	.1									6.1	4.6	4.0
020-040	3.8	2.6	.5									6.8	4.9	4.0
050-070	2.4	2.6	1.6	.1	.1							6.7	7.0	6.0
(E) 080-100	1.4	1.2	.9	.1	.0							3.6	7.1	6.0
110-130	.9	.5	.1									1.5	4.8	4.0
140-160	2.4	.8	.1									3.3	4.3	4.0
(S) 170-190	1.8	.9	.4	.2								3.2	5.9	4.0
200-220	1.4	2.1	1.3	.2	.1							5.2	7.7	8.0
230-250	2.1	2.2	1.6	.2	.0							6.1	7.0	6.0
(W) 260-280	3.3	2.2	.8	.0	.1							6.4	5.7	4.0
290-310	3.8	2.0	.3	.1								6.2	4.8	4.0
320-340	3.7	2.0	.2	.0								6.0	4.6	4.0
VARIABLE														
CALM	////////////////////											38.8	////////////////	
TOTALS	30.7	21.4	7.9	.9	.3							100.0	3.5	4.0
TOTAL NUMBER OF OBSERVATIONS 3276														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL	MEAN	MEDIAN
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010														
020-040														
050-070														
(E) 080-100														
110-130														
140-160														
(S) 170-190														
200-220														
230-250														
(W) 260-280														
290-310		100.0										100.0	6.0	6.0
320-340														
VARIABLE														
CALM	////////////////////////////////////											.0	////////////////////////////////	
TOTALS		100.0										100.0	6.0	6.0

TOTAL NUMBER OF OBSERVATIONS 1

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.7	.2										1.9	3.1	3.0
020-040	4.5	.5										5.0	3.5	4.0
050-070	5.7	1.4	.3									7.4	3.8	3.0
(E) 080-100	4.5	1.4	.5									6.4	4.4	4.0
110-130	4.8	.3										5.2	2.9	2.5
140-160	11.2	1.2										12.4	3.3	3.0
(S) 170-190	2.9	.3	.2									3.5	3.4	3.0
200-220	1.9	1.4										3.3	4.4	4.0
230-250	.3	1.0	.2									1.6	6.1	5.0
(W) 260-280	.5	.2										.7	3.8	3.5
290-310	.7	.3										1.0	4.0	4.0
320-340	.7											.7	2.5	2.0
VARIABLE														
CALM	////////////////////////////////////											50.9	////////////////////////////////	
TOTALS	39.4	8.2	1.2									100.0	1.8	3.0

TOTAL NUMBER OF OBSERVATIONS 579

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 09-11

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	8.5	5.6										14.0	4.6	4.0
020-040	11.5	5.1	1.7	.2								18.4	4.9	4.0
050-070	4.5	1.2	3.8	.2								9.7	7.0	6.0
(E) 080-100	1.1	.8	1.7									3.5	7.8	8.0
110-130	.3	.3										.6	5.3	5.0
140-160	1.8	.5	.3									2.6	4.7	4.0
(S) 170-190	.6	1.2	.3	.2								2.3	6.8	6.0
200-220	.9	1.1	.5									2.4	6.4	6.0
230-250	1.1	2.3	.6									3.9	6.8	6.5
(W) 260-280	.9	1.2	.8									2.9	6.8	6.0
290-310	.9	.2		.2								1.2	4.8	3.5
320-340	3.2	.9	.2									4.2	4.0	4.0
VARIABLE														
CALM	////////////////////////////////////											34.3	////////////////////////////////	
TOTALS	35.3	20.4	9.9	.8								100.0	3.6	4.0

TOTAL NUMBER OF OBSERVATIONS 662

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	5.9	5.6	1.3									12.8	5.4	5.0
020-040	5.3	7.7	2.2	.3								15.5	6.2	6.0
050-070	1.4	3.0	4.5	.5								9.4	9.1	10.0
(E) 080-100	.8	1.4	1.6									3.8	8.2	8.0
110-130		.2	.2									.3	9.0	9.0
140-160		.2	.5									.6	10.8	11.0
(S) 170-190	.5	.9	.3			.2						1.9	8.1	6.0
200-220	.5	1.3	1.3	.3		.3						3.6	10.8	10.0
230-250	1.7	4.1	1.7									7.5	7.1	6.0
(W) 260-280	2.8	3.4	1.9									8.1	6.5	6.0
290-310	5.0	1.3	1.1	.2								7.5	5.2	4.0
320-340	4.4	2.7										7.0	4.4	4.0
VARIABLE														
CALM	////////////////////////////////////											22.0	////////	
TOTALS	28.3	31.8	16.6	1.3		.5						100.0	5.2	6.0
TOTAL NUMBER OF OBSERVATIONS 640														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 15-17

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
(N) 350-010	5.9	5.7	.9									12.5	5.0	5.0
020-040	3.5	6.3	1.6									11.3	6.4	6.0
050-070	1.2	4.7	1.4	.5								7.8	8.2	8.0
(E) 080-100	.2	1.4	.3									1.9	7.5	7.0
110-130	.2	.3	.2									.7	6.5	6.0
140-160	.2											.2	4.0	4.0
(S) 170-190		.7	.5			.2						1.4	11.8	9.5
200-220	.7	1.7	1.2	.2								3.8	8.0	7.0
230-250	2.6	3.3	1.9	.5								8.4	7.1	7.0
(W) 260-280	6.4	5.4	1.7	.3								13.9	6.0	5.0
290-310	3.8	1.9	1.0	.2								7.0	5.5	4.0
320-340	5.9	2.6	.2									8.7	4.4	4.0
VARIABLE														
CALM	////////////////////////////////////											22.3	////////////////////////////////	
TOTALS	30.6	34.0	10.9	1.7		.2						100.0	4.9	6.0
TOTAL NUMBER OF OBSERVATIONS 574														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.9											1.9	3.1	3.0
020-040	4.1	1.1	.5									5.7	4.3	3.0
050-070	1.9	.8	.3									3.0	4.5	4.0
(E) 080-100	.8											.8	3.7	4.0
110-130	1.1	.3										1.4	4.0	4.0
140-160	1.6	.3	.3									2.2	4.0	3.5
(S) 170-190	3.8	.5	.3									4.6	4.4	4.0
200-220	3.5	.8	.3									4.6	4.2	3.0
230-250	5.7	3.2	.3	.3								9.5	4.9	4.0
(W) 260-280	2.7	1.6										4.3	4.2	4.0
290-310	1.9	.3										2.2	3.1	3.0
320-340	1.4		.3									1.6	4.2	3.5
VARIABLE														
CALM	////////////////////											58.4	////////	
TOTALS	30.4	8.9	2.3	.3								100.0	1.8	4.0

TOTAL NUMBER OF OBSERVATIONS 370

OPERATING LOCATION: "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 21-23

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
(N) 350-010														
020-040			1.7									1.7	10.0	10.0
050-070														
(E) 080-100														
110-130	1.7											1.7	3.0	3.0
140-160	13.6	8.5										22.0	4.2	4.0
(S) 170-190	16.9											16.9	3.5	4.0
200-220	5.1											5.1	3.7	4.0
230-250	3.4											3.4	3.0	3.0
(W) 260-280	1.7											1.7	4.0	4.0
290-310														
320-340														
VARIABLE														
CALM	////////////////////////////////////											47.5	////////	
TOTALS	42.4	8.5	1.7									100.0	2.1	4.0

TOTAL NUMBER OF OBSERVATIONS 59

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	5.0	3.7	.5									9.2	4.8	4.0
020-040	5.9	4.4	1.3	.1								11.7	5.4	4.0
050-070	3.0	2.3	2.3	.2								7.7	7.1	7.0
(E) 080-100	1.5	1.0	.9									3.4	6.5	6.0
110-130	1.2	.3	.1									1.6	3.8	3.0
140-160	3.2	.6	.2									4.0	3.9	4.0
(S) 170-190	1.7	.8	.3	.0		.1						2.8	5.8	4.0
200-220	1.4	1.2	.7	.1		.1						3.5	6.9	6.0
230-250	2.0	2.7	1.0	.1								5.8	6.5	6.0
(W) 260-280	2.6	2.4	.9	.1								6.0	6.0	5.0
290-310	2.5	.8	.5	.1								3.8	5.0	4.0
320-340	3.2	1.3	.1									4.6	4.3	4.0
VARIABLE														
CALM	////////////////////////////////////											35.9	////////////////////////////////	
TOTALS	33.2	21.5	8.8	.7		.2						100.0	3.6	4.0
TOTAL NUMBER OF OBSERVATIONS 2884														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL	MEAN	MEDIAN
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010														
020-040														
050-070														
(E) 080-100														
110-130														
140-160														
(S) 170-190						12.5						12.5	28.0	25.0
200-220	12.5					25.0						37.5	19.7	25.0
230-250	12.5	12.5										25.0	6.0	6.0
(W) 260-280														
290-310														
320-340														
VARIABLE														
CALM	////////////////////											25.0	////////	
TOTALS	25.0	12.5				37.5						100.0	12.4	16.5

TOTAL NUMBER OF OBSERVATIONS 8

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 06-08

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.9	.5										2.4	3.5	3.0
020-040	6.1	1.8	.3									8.2	3.9	4.0
050-070	5.0	1.4	.6	.2								7.2	4.8	4.0
(E) 080-100	7.7	1.6	.8		.2							10.3	4.3	3.0
110-130	4.2	.3										4.5	3.0	3.0
140-160	6.6	.3										6.9	3.2	3.0
(S) 170-190	3.2	.3										3.5	3.2	3.0
200-220	.8	1.4	.2	.2								2.6	6.3	5.0
230-250	.8	.2										1.0	3.3	3.0
(W) 260-280	1.1	.2	.2	.2								1.6	5.1	3.0
290-310	.3	.2										.5	3.7	3.0
320-340	.5	.2										.6	4.0	4.0
VARIABLE														
CALM	////////////////////////////////////											50.6	////////	
TOTALS	38.2	8.4	2.1	.6	.2							100.0	2.0	3.0
TOTAL NUMBER OF OBSERVATIONS 621														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 09-11

WIND SPEED IN KNOTS														
DIRECTION (DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65	TOTAL %	MEAN WIND	MEDIAN WIND
(N) 350-010	7.3	5.9	.3									13.5	4.8	4.0
020-040	14.6	7.8	.9	.3								23.5	4.7	4.0
050-070	4.6	1.9	2.4	.3								9.2	6.5	4.5
(E) 080-100	2.9	.6	.4	.4								4.3	5.8	4.0
110-130	1.4	.4	.1									2.0	4.8	4.0
140-160	1.4		.1									1.6	3.5	3.0
(S) 170-190	1.3	.4	.1									1.9	4.2	3.0
200-220	1.7	.9	.9									3.5	5.8	4.5
230-250	1.4	.9	.6	.1								3.0	6.7	5.0
(W) 260-280	1.0	.9	.3									2.2	5.5	5.0
290-310	1.0											1.0	2.9	3.0
320-340	2.3	1.3										3.6	4.2	4.0
VARIABLE														
CALM	////////////////////////////////////											30.7	////////	
TOTALS	40.9	21.0	6.1	1.1								100.0	3.5	4.0

TOTAL NUMBER OF OBSERVATIONS 694

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAFAPZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 12-14

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	10.0	11.1	2.0									23.1	5.5	5.0
020-040	6.5	5.5	2.4									14.4	5.8	5.0
050-070	2.1	1.5	2.1	.3	.3							6.4	8.6	8.0
(E) 080-100	.8	.5	1.8									3.0	9.1	10.5
110-130	.5											.5	3.0	3.0
140-160	.3	.3										.6	4.5	4.0
(S) 170-190	.2	.8										.9	7.2	7.5
200-220	.2	1.1	.2	.3								1.7	8.5	7.0
230-250	1.5	2.1	1.7									5.3	7.2	8.0
(W) 260-280	3.3	2.4	.3	.6								6.7	6.0	4.5
290-310	3.8	1.5	.2									5.5	4.4	4.0
320-340	5.9	4.7	.3									10.9	4.7	4.0
VARIABLE														
CALM	////////////////////////////////////											21.1	////////////////////////////////	
TOTALS	35.1	31.5	11.0	1.2	.3							100.0	4.7	5.0

TOTAL NUMBER OF OBSERVATIONS 659

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 15-17

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	8.4	8.4	.3									17.2	4.9	5.0
020-040	2.7	4.7	1.5									8.9	6.2	6.0
050-070	1.3	2.4	1.5	.7								5.9	8.3	8.0
(E) 080-100	.3	1.0	1.3									2.7	8.5	9.5
110-130		.3										.3	7.0	7.0
140-160		.5										.5	6.3	6.0
(S) 170-190	.5	.5										1.0	4.7	5.0
200-220	.8	.8	.5									2.2	6.5	6.0
230-250	1.5	2.2	.8									4.5	6.4	6.0
(W) 260-280	5.1	2.4	.7		.3							8.4	5.6	4.0
290-310	5.6	2.0	.7									8.2	4.5	4.0
320-340	8.4	2.4	.7	.2								11.6	4.4	4.0
VARIABLE														
CALM	////////////////////											28.5	////////	
TOTALS	34.0	27.6	8.0	.9	.3							100.0	4.0	5.0

TOTAL NUMBER OF OBSERVATIONS 594

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 18-20

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	.9	.3										1.2	3.8	4.0
020-040	2.7	.6										3.3	3.6	4.0
050-070	1.5	1.2		.3								3.0	6.2	4.5
(E) 080-100	1.2	.9	.6	.3								3.0	7.7	6.5
110-130	1.8	.3	.3									2.4	4.5	4.0
140-160	6.7	.3										7.0	3.1	3.0
(S) 170-190	3.3											3.3	3.4	4.0
200-220	1.8											1.8	3.2	3.5
230-250	1.5	.3										1.8	4.0	4.0
(W) 260-280	1.8	1.5	.3									3.6	4.7	4.5
290-310	1.5	1.8										3.3	4.7	5.0
320-340	1.5	.6										2.1	4.3	3.0
VARIABLE														
CALM	////////////////////											63.8	////////	
TOTALS	26.2	7.8	1.2	.6								100.0	1.6	4.0

TOTAL NUMBER OF OBSERVATIONS 329

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 21-23

DIRECTION (DEGREES)	WIND SPEED IN KNOTS										TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65		
(N) 350-010													
020-040													
050-070		1.5										1.5	8.0 8.0
(E) 080-100	1.5	3.0										4.5	5.3 6.0
110-130	3.0											3.0	4.0 4.0
140-160	16.4											16.4	3.1 4.0
(S) 170-190	11.9	1.5										13.4	4.0 4.0
200-220	1.5											1.5	2.0 2.0
230-250													
(W) 260-280													
290-310													
320-340													
VARIABLE													
CALM	////////////////////										59.7	////////////////	
TOTALS	34.3	6.0										100.0	1.6 4.0

TOTAL NUMBER OF OBSERVATIONS 67

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	6.1	5.7	.6									12.4	5.0	5.0
020-040	7.0	4.4	1.1	.1								12.6	5.0	4.0
050-070	3.0	1.7	1.5	.3	.1							6.6	6.9	5.0
(E) 080-100	2.7	.9	1.0	.1	.0							4.8	6.0	4.0
110-130	1.6	.3	.1									1.9	3.8	3.0
140-160	2.9	.3	.0									3.2	3.3	3.0
(S) 170-190	1.8	.5	.0									2.3	4.0	4.0
200-220	1.0	.9	.4	.1								2.4	6.1	5.0
230-250	1.3	1.2	.7	.0								3.2	6.4	6.0
(W) 260-280	2.4	1.4	.3	.2	.1							4.4	5.6	4.0
290-310	2.4	1.0	.2									3.6	4.3	4.0
320-340	3.8	1.9	.2	.0								6.0	4.5	4.0
VARIABLE														
CALM	////////////////////											36.6	////////	
TOTALS	36.0	20.2	6.1	.8	.2							100.0	3.3	4.0

TOTAL NUMBER OF OBSERVATIONS 2964

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

		WIND SPEED IN KNOTS										TOTAL	MEAN	MEDIAN
DIRECTION	(DEGREES)	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65		
(N) 350-010		4.2	8.3									12.5	5.3	6.0
020-040		16.7										16.7	3.8	4.0
050-070				12.5								12.5	5.0	5.0
(E) 080-100		8.3	4.2									12.5	4.7	4.0
110-130		4.2										4.2	4.0	4.0
140-160														
(S) 170-190														
200-220														
230-250														
(W) 260-280			4.2			4.2						8.3	15.5	15.5
290-310														
320-340														
VARIABLE														
CALM		////////////////////////////////////										33.3	////////////////////////////////	
TOTALS		33.4	29.2			4.2						100.0	4.0	4.5

TOTAL NUMBER OF OBSERVATIONS 24

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: ALL HOURS: ALL

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	5.4	2.5	.3	.0								6.2	5.0	4.0
020-040	3.7	2.7	.6	.0								7.0	5.2	4.0
050-070	1.9	1.5	1.0	.1	.0							4.5	6.5	6.0
(E) 080-100	1.4	1.0	.7	.1	.0		.0					3.2	6.4	6.0
110-130	1.3	.4	.1	.0	.0							1.8	4.4	4.0
140-160	2.6	1.1	.3	.0	.0	.0						4.0	4.7	4.0
(S) 170-190	2.1	1.4	.8	.1	.0	.0						4.5	6.2	5.0
200-220	2.0	2.9	2.0	.2	.1	.0						7.2	7.5	7.0
230-250	2.7	4.4	2.3	.2	.0	.0						9.7	7.2	6.0
(W) 260-280	3.3	3.7	1.3	.1	.0							8.5	6.3	6.0
290-310	3.3	2.7	.5	.0	.0							6.6	5.3	4.0
320-340	3.1	2.0	.3	.0	.0							5.4	4.9	4.0
VARIABLE														
CALM	////////////////////////////////////											31.6	////////	
TOTALS	30.8	26.3	10.2	.8	.1							100.0	4.1	5.0
TOTAL NUMBER OF OBSERVATIONS: 38986														

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE SURFACE WIND DIRECTION VERSUS WIND SPEED
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: ALL HOURS: ALL

CATEGORY A: CEILING GE 200 BUT LESS THAN 1500 FEET WITH VISIBILITY GE 1/2 MILE (0800 METERS).

AND/OR

VISIBILITY GE 1/2 MILE (0800 METERS) BUT LESS THAN 3 MILES (4800 METERS) WITH CEILING GE 200 FEET.

DIRECTION (DEGREES)	WIND SPEED IN KNOTS											TOTAL %	MEAN WIND	MEDIAN WIND
	1-4	5-9	10-14	15-19	20-24	25-29	30-34	35-39	40-49	50-64	GE 65			
(N) 350-010	1.9	3.7	1.9									7.4	7.0	6.0
020-040	7.4											7.4	3.8	4.0
050-070		5.6										5.6	5.0	5.0
(E) 080-100	3.7	1.9										5.6	4.7	4.0
110-130	1.9											1.9	4.0	4.0
140-160														
(S) 170-190		1.9			1.9	1.9						5.6	18.0	20.0
200-220	3.7	1.9			1.9	3.7						11.1	15.2	14.0
230-250	1.9	3.7		1.9								7.4	9.0	8.0
(W) 260-280	1.9	1.9	1.9		1.9							7.4	11.3	9.5
290-310	1.9	3.7	1.9									7.4	6.5	7.0
320-340			1.9									1.9	10.0	10.0
VARIABLE														
CALM	////////////////////////////////////											31.5	////////////////////////////////	
TOTALS	24.3	24.3	7.6	1.9	5.7	5.6						100.0	6.3	6.0

TOTAL NUMBER OF OBSERVATIONS: 54

PPPPPPP	AAAAA	RRRRRRR	TTTTTTTTT	DDDDDDDD
PPPPPPPP	AAAAAAA	RRRRRRRR	TTTTTTTTT	DDDDDDDDDD
PP PP	AA AA	RR RR	TT	DD DD
PP PP	AA AA	RR RR	TT	DD DD
PPPPPPPP	AA AA	RRRRRRRR	TT	DD DD
PPPPPPPP	AAAAAAAAA	RRRRRRR	TT	DD DD
PP	AAAAAAAAA	RR RR	TT	DD DD
PP	AA AA	RR RR	TT	DD DD
PP	AA AA	RR RR	TT	DDDDDDDD
PP	AA AA	RR RR	TT	DDDDDDDD

PART D

CEILING VERSUS VISIBILITY AND SKY COVER SUMMARIES

CEILING VS VISIBILITY--PERCENT OCCURRENCE FREQUENCY (POF).

CREATED FROM HOURLY OBSERVATIONS, THIS SUMMARY IS A BIVARIATE DISTRIBUTION OF PERCENTAGE FREQUENCY BY CLASSES OF CEILING (FROM ZERO FEET TO 20,000 FEET-- "NO CEILING" IS A SEPARATE CLASS) VERSUS VISIBILITY CLASSES (FROM ZERO MILES (METERS) TO GREATER THAN OR EQUAL TO 7 STATUTE MILES (11,200 METERS)). THE TABLES SUMMARIZE THE DATA AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

BECAUSE OF THE CUMULATIVE NATURE OF THESE SUMMARIES, IT IS POSSIBLE TO DETERMINE THE PERCENTAGE OCCURRENCE FREQUENCY (POF) FOR ANY GIVEN CEILING AND/OR VISIBILITY LIMIT(S), EITHER SEPARATELY OR IN ANY COMBINATION. TOTALS PROGRESS FROM RIGHT TO LEFT AND FROM BOTTOM TO TOP. TO DETERMINE CEILING ALONE, REFER TO THE EXTREME RIGHT-HAND COLUMN (ZERO VISIBILITY). TO DETERMINE VISIBILITY ALONE, REFER TO THE BOTTOM ROW (ZERO CEILINGS). DETERMINE THE POF THAT MEETS OR EXCEEDS ANY GIVEN SET OF MAXIMA BY READING THE VALUE AT THE INTERSECTION OF THE APPROPRIATE CEILING ROW AND VISIBILITY COLUMN.

NOTE 1: IN JANUARY 1968, METAR STATIONS BEGAN REPORTING VISIBILITIES TO 6 STATUTE MILES OR 9000 METERS. VALUES EXCEEDING 9000 METERS ARE REPORTED AS "9999."

NOTE 2: FOR OVERSEAS CIVILIAN STATIONS REPORTING "CAVOK", ALL CEILINGS GREATER THAN 5000 FEET APPEAR IN THE 5000 FEET CLASS.

CONVERSIONS: 1 STATUTE MILE = 1,609.344 METERS = .868391 NAUTICAL MILES.
FOR CONVENIENCE, THE CONVERSION OFTEN USED IS 1 STATUTE MILE = 1,600 METERS.

SKY COVER--PERCENT OCCURRENCE FREQUENCY.

ALSO CREATED FROM HOURLY OBSERVATIONS, THIS SUMMARY GIVES PERCENTAGE OCCURRENCE FREQUENCY (POF) OF SKY COVER IN EIGHTHS FOR SYNOPTIC STATIONS, BUT AS CLEAR, SCATTERED, BROKEN, OVERCAST, PARTIALLY OBSCURED, OR TOTALLY OBSCURED FOR AIRWAYS STATIONS. FOR AIRWAYS STATIONS, THIS SUMMARY ALSO GIVES POF FOR SKY COVER GREATER THAN ONE-HALF (I.E., 6/10). DATA IS SUMMARIZED THE SAME AS FOR PREVIOUS TABLE.

NOTE 1. THESE SUMMARIES ARE NOT AVAILABLE FOR METAR REPORTING STATIONS.

NOTE 2. AIRWAYS STATIONS THAT HAVE REPORTED IN SYNOPTIC CODE HAVE HAD THEIR
SYNOPTIC SKY COVER REPORTS CONVERTED AS FOLLOWS:

0/8.....CLEAR

1/8 THRU 4/8.....SCATTERED

5/8 THRU 7/8.....BROKEN

8/8.....OVERCAST

NOTE 3. "PARTIAL OBSCURATION" IS A SEPARATE CATEGORY NOT INCLUDED IN
COMPUTATION OF "GREATER THAN 1/2" PERCENTAGES. "TOTAL OBSCURATIONS,"
HOWEVER, ARE INCLUDED.

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	76.1	76.1	76.1	76.2	76.4	76.4	76.4	76.4	76.4	76.4	76.4	76.4	76.4	76.4	76.4	76.4
GE 20000	81.3	81.4	81.4	81.6	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7
GE 18000	81.6	81.7	81.7	81.9	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0
GE 16000	81.7	81.9	81.9	82.0	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2
GE 14000	84.9	85.0	85.0	85.2	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4
GE 12000	87.4	87.6	87.6	87.7	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9
GE 10000	89.8	89.9	89.9	90.1	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2
GE 9000	90.6	90.7	90.7	90.9	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0
GE 8000	93.4	93.5	93.5	93.7	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9
GE 7000	94.2	94.3	94.3	94.5	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
GE 6000	95.4	95.6	95.6	95.7	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 5000	97.5	97.6	97.6	97.8	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 4500	97.5	97.6	97.6	97.8	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 4000	98.7	98.9	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 3500	98.7	98.9	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 3000	98.7	98.9	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 2500	99.1	99.2	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 2000	99.1	99.2	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1800	99.1	99.2	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1500	99.1	99.2	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1200	99.1	99.2	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1000	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.1	99.2	99.5	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 635

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 09-11

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	74.0	74.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0
GE 20000	80.4	80.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4
GE 18000	81.4	81.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4
GE 16000	81.9	81.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9
GE 14000	82.9	82.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9	83.9
GE 12000	86.5	86.5	87.4	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6
GE 10000	89.8	89.8	90.8	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0
GE 9000	90.4	90.4	91.4	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 8000	92.5	92.5	93.5	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7
GE 7000	94.2	94.2	95.2	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3
GE 6000	95.6	95.6	96.6	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 5000	96.2	96.2	97.2	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 4500	96.2	96.2	97.2	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 4000	97.0	97.2	98.2	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 3500	97.5	97.6	98.6	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
GE 3000	97.6	97.7	98.7	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 2500	97.6	97.7	98.7	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE 2000	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 1800	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 1500	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 1200	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 1000	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9
GE 900	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9
GE 800	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9
GE 700	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9
GE 600	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9
GE 500	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9
GE 400	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9
GE 300	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9
GE 200	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9
GE 100	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0
GE 000	98.2	98.3	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 709

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	72.6	72.6	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0
GE 20000	79.7	79.7	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1
GE 18000	80.5	80.5	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0
GE 16000	81.0	81.0	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4	81.4
GE 14000	82.7	82.7	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1
GE 12000	86.4	86.4	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9
GE 10000	90.3	90.3	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8
GE 9000	90.8	90.8	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
GE 8000	92.1	92.1	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5
GE 7000	93.5	93.5	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9
GE 6000	94.7	94.7	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 5000	95.7	95.7	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1
GE 4500	96.0	96.0	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4
GE 4000	97.0	97.0	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
GE 3500	97.1	97.1	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5
GE 3000	98.0	98.3	98.7	98.8	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE 2500	98.3	98.6	99.0	99.1	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 2000	98.4	98.7	99.1	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1800	98.4	98.7	99.1	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1500	98.4	98.7	99.1	99.3	99.4	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 1200	98.4	98.7	99.1	99.3	99.4	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 1000	98.6	98.8	99.3	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 900	98.6	98.8	99.3	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 800	98.6	98.8	99.3	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 700	98.6	98.8	99.3	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 600	98.6	98.8	99.3	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 500	98.6	98.8	99.3	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 400	98.6	98.8	99.3	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 300	98.6	98.8	99.3	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 200	98.6	98.8	99.3	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 100	98.6	98.8	99.4	99.6	99.7	99.7	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	98.6	98.8	99.4	99.6	99.7	99.7	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 693

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6	72.6
GE 20000	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9
GE 18000	81.2	81.2	81.2	81.2	81.2	81.2	81.2	81.2	81.2	81.2	81.2	81.2	81.2	81.2	81.2	81.2
GE 16000	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7	81.7
GE 14000	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6
GE 12000	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2
GE 10000	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2
GE 9000	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1
GE 8000	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6
GE 7000	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6
GE 6000	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9
GE 5000	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
GE 4500	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 4000	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 3500	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 3000	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 2500	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 2000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 645

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1	74.1
GE 20000	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7
GE 18000	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2
GE 16000	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2
GE 14000	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0
GE 12000	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2
GE 10000	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 9000	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0
GE 8000	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2
GE 7000	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3
GE 6000	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 5000	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 4500	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 4000	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 3500	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 3000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 424

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6
GE 20000	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
GE 18000	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
GE 16000	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
GE 14000	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7
GE 12000	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3
GE 10000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 9000	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 8000	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 7000	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 6000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 86

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	74.1	74.1	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4
GE 20000	81.2	81.2	81.5	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6
GE 18000	81.8	81.8	82.1	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2
GE 16000	82.1	82.2	82.5	82.5	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6
GE 14000	84.1	84.2	84.5	84.5	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6
GE 12000	87.2	87.2	87.5	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6
GE 10000	90.0	90.1	90.4	90.4	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5
GE 9000	90.9	90.9	91.2	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3
GE 8000	92.7	92.7	93.0	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1
GE 7000	93.9	93.9	94.2	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3
GE 6000	95.5	95.5	95.8	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 5000	96.6	96.7	97.0	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
GE 4500	96.9	96.9	97.2	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 4000	98.1	98.2	98.6	98.6	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
GE 3500	98.3	98.3	98.7	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 3000	98.7	98.8	99.2	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 2500	98.8	98.9	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 2000	99.0	99.1	99.6	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1800	99.0	99.1	99.6	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1500	99.0	99.1	99.6	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1200	99.0	99.1	99.6	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1000	99.0	99.2	99.6	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 900	99.0	99.2	99.6	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 800	99.0	99.2	99.6	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 700	99.0	99.2	99.6	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 600	99.0	99.2	99.6	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 500	99.0	99.2	99.6	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 400	99.0	99.2	99.6	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 300	99.0	99.2	99.6	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 200	99.0	99.2	99.6	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 100	99.0	99.2	99.6	99.8	99.8	99.8	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.0	99.2	99.6	99.8	99.8	99.8	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 3192

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9	78.9
GE 20000	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5
GE 18000	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7
GE 16000	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7
GE 14000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 12000	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1
GE 10000	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
GE 9000	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
GE 8000	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
GE 7000	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
GE 6000	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 5000	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3
GE 4500	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8
GE 4000	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 3500	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 3000	97.5	97.6	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 2500	98.0	98.1	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5
GE 2000	98.8	99.0	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1800	98.8	99.0	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1500	99.0	99.2	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 1200	99.0	99.2	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 1000	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.0	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 593

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 09-11

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE U
NO CEIL	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9
GE 20000	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4
GE 18000	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4
GE 16000	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6
GE 14000	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0
GE 12000	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3
GE 10000	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
GE 9000	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8
GE 8000	91.0	91.0	91.0	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
GE 7000	91.6	91.6	91.6	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7
GE 6000	93.7	93.7	93.7	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8
GE 5000	94.7	94.7	94.7	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8
GE 4500	95.0	95.0	95.0	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 4000	95.6	95.6	95.6	95.7	95.7	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 3500	96.0	96.0	96.0	96.2	96.2	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
GE 3000	97.6	97.6	97.6	97.8	97.8	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9
GE 2500	97.9	97.9	98.1	98.2	98.2	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
GE 2000	97.9	97.9	98.2	98.4	98.4	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5
GE 1800	97.9	97.9	98.2	98.4	98.4	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5
GE 1500	98.5	98.5	98.8	99.0	99.0	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 1200	98.7	98.7	99.0	99.1	99.1	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 1000	99.1	99.1	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 900	99.1	99.1	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 800	99.1	99.1	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 700	99.1	99.1	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 600	99.1	99.1	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 500	99.1	99.1	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.1	99.1	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.1	99.1	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.1	99.1	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.1	99.1	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.1	99.1	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 678

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2	72.2
GE 20000	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0	82.0
GE 18000	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	8.3	82.3	82.3	82.3	82.3
GE 16000	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5
GE 14000	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6
GE 12000	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9
GE 10000	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6
GE 9000	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3
GE 8000	91.4	91.4	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 7000	92.1	92.1	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3
GE 6000	93.6	93.6	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8
GE 5000	94.9	94.9	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0
GE 4500	95.3	95.3	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 4000	95.8	95.8	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 3500	96.1	96.1	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2
GE 3000	97.9	97.9	98.2	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 2500	98.6	98.6	98.9	99.1	99.1	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 2000	98.8	98.8	99.1	99.2	99.2	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1800	98.8	98.8	99.1	99.2	99.2	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1500	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.4	99.4	99.7	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 661

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 15-17

CEILING		VISIBILITY IN STATUTE MILES															
IN FEET	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
NO CEIL	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	69.6	
GE 20000	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	
GE 18000	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	
GE 16000	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	
GE 14000	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	
GE 12000	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	
GE 10000	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	
GE 9000	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	
GE 8000	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	
GE 7000	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	
GE 6000	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	
GE 5000	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	
GE 4500	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	
GE 4000	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	
GE 3500	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	
GE 3000	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	
GE 2500	99.5	99.5	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	
GE 2000	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1800	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1500	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1200	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1000	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 900	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 800	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 700	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 600	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 500	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 400	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 300	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 200	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 100	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 000	99.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	

TOTAL NUMBER OF OBSERVATIONS 615

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9	73.9
GE 20000	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9	82.9
GE 18000	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6
GE 16000	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5
GE 14000	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4
GE 12000	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9
GE 10000	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3
GE 9000	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 8000	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
GE 7000	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5
GE 6000	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2
GE 5000	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 4500	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4
GE 4000	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
GE 3500	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
GE 3000	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
GE 2500	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 2000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 414

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9	77.9
GE 20000	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6
GE 18000	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6	87.6
GE 16000	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5
GE 14000	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3
GE 12000	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
GE 10000	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
GE 9000	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
GE 8000	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8
GE 7000	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
GE 6000	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 5000	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 4500	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 4000	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 3500	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 3000	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 113

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: ILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8	73.8
GE 20000	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2
GE 18000	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4	83.4
GE 16000	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1
GE 14000	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2
GE 12000	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9	88.9
GE 10000	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4
GE 9000	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0
GE 8000	92.0	92.0	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1
GE 7000	92.5	92.5	92.5	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6
GE 6000	94.6	94.6	94.6	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
GE 5000	95.3	95.3	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4
GE 4500	95.7	95.7	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8
GE 4000	96.3	96.3	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4
GE 3500	96.6	96.6	96.6	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 3000	97.8	97.9	98.0	98.0	98.0	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
GE 2500	98.7	98.8	99.0	99.0	99.0	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 2000	99.0	99.0	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1800	99.0	99.0	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1500	99.3	99.3	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 1200	99.3	99.3	99.6	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1000	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.4	99.4	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 3074

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6
GE 20000	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4
GE 18000	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8
GE 16000	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1
GE 14000	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6
GE 12000	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3
GE 10000	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4
GE 9000	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0
GE 8000	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2
GE 7000	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8
GE 6000	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6
GE 5000	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6
GE 4500	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
GE 4000	99.3	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 3500	99.3	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 3000	99.4	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 2500	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 2000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 711

OPERATING LOCATION "A"
 DEATH VALLEY, ARIZONA

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
 FROM HOURLY OBSERVATIONS

STATION NUMBER 747250

STATION NAME GILA BEND ART 82
 EST TO UTC + 7

PERIOD OF RECORD JUN 79 MAY 89
 MONTH MAR APRIL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 1	GE 3	GE 5	GE 7	GE 9	GE 10-12	GE 14	GE 16-17	GE 18-19	GE 20-24	GE 25	GE 26-29	GE 30-34	GE 35-39	GE 40-49	GE 50
NO CEILING	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 20000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 18000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 16000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 14000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 12000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 10000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 8000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 6000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 4000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 3000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 2000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 1800	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 1600	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 1400	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 1200	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 1000	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 800	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 600	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 400	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 200	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 100	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 50	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8

TOTAL NUMBER OF OBSERVATIONS 357

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	76.7	76.7	76.7	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0	77.0
GE 20000	83.4	83.4	83.4	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6
GE 18000	83.9	83.9	83.9	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2
GE 16000	84.8	84.8	84.8	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0
GE 14000	85.9	85.9	85.9	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2
GE 12000	87.0	87.0	87.0	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3
GE 10000	88.6	88.6	88.6	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8
GE 9000	88.9	88.9	88.9	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2
GE 8000	89.6	89.6	89.6	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8
GE 7000	90.8	90.8	90.8	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
GE 6000	92.3	92.3	92.3	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6
GE 5000	94.3	94.3	94.3	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
GE 4500	94.8	94.8	94.8	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 4000	97.2	97.2	97.2	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5
GE 3500	97.7	97.7	97.7	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 3000	98.9	98.9	98.9	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 2500	99.0	99.0	99.0	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 2000	99.1	99.1	99.1	99.4	99.5	99.5	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 1800	99.1	99.1	99.1	99.4	99.5	99.5	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 1500	99.1	99.1	99.1	99.4	99.5	99.5	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 1200	99.2	99.2	99.2	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 1000	99.2	99.2	99.2	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 900	99.2	99.2	99.2	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 800	99.2	99.2	99.2	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 700	99.2	99.2	99.2	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 600	99.2	99.2	99.2	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 500	99.2	99.2	99.5	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.2	99.2	99.5	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.2	99.2	99.5	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.2	99.2	99.5	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.2	99.2	99.5	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.2	99.2	99.5	99.7	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 795

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	74.2	74.3	74.3	74.3	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4	74.4
GE 20000	83.3	83.4	83.4	83.4	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6
GE 18000	83.7	83.8	83.8	83.8	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0
GE 16000	85.0	85.1	85.1	85.1	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3
GE 14000	87.2	87.4	87.4	87.4	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5
GE 12000	88.1	88.2	88.2	88.2	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3
GE 10000	89.0	89.2	89.2	89.2	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3
GE 9000	89.2	89.3	89.3	89.3	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
GE 8000	89.7	89.9	89.9	89.9	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0
GE 7000	90.7	90.9	90.9	90.9	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0
GE 6000	93.4	93.5	93.5	93.5	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7
GE 5000	95.2	95.4	95.4	95.4	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 4500	96.2	96.3	96.3	96.3	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 4000	98.0	98.2	98.2	98.2	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 3500	98.5	98.6	98.6	98.6	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
GE 3000	99.0	99.2	99.2	99.2	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 2500	99.0	99.2	99.2	99.2	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 2000	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.4	99.6	99.6	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 712

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	79.8	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0
GE 20000	84.8	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0
GE 18000	85.0	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2
GE 16000	85.4	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7	85.7
GE 14000	88.6	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8
GE 12000	89.2	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4
GE 10000	90.6	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9
GE 9000	90.6	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9
GE 8000	91.3	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 7000	91.5	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7
GE 6000	95.6	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0
GE 5000	97.7	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
GE 4500	97.7	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
GE 4000	98.3	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 3500	99.0	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 3000	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.6	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 481

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7
GE 20000	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7
GE 18000	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3
GE 16000	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3
GE 14000	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7
GE 12000	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 10000	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 9000	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 8000	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 7000	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0
GE 6000	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 5000	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 4500	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 4000	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 3500	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 150

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	78.6	78.6	78.6	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7
GE 20000	84.8	84.9	84.9	84.9	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0	85.0
GE 18000	85.2	85.2	85.2	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3
GE 16000	85.8	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9
GE 14000	87.4	87.4	87.4	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5
GE 12000	89.0	89.1	89.1	89.1	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2
GE 10000	90.5	90.5	90.5	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
GE 9000	90.9	90.9	90.9	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0
GE 8000	91.9	92.0	92.0	92.0	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1
GE 7000	92.7	92.8	92.8	92.8	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
GE 6000	94.9	95.0	95.0	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 5000	96.6	96.7	96.7	96.7	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 4500	96.9	97.0	97.0	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
GE 4000	98.3	98.4	98.4	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5
GE 3500	98.6	98.7	98.7	98.8	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 3000	99.2	99.3	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 2500	99.3	99.5	99.5	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 2000	99.5	99.6	99.6	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 1800	99.5	99.6	99.6	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 1500	99.5	99.6	99.6	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 1200	99.5	99.6	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 1000	99.5	99.6	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 900	99.5	99.6	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 800	99.5	99.6	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 700	99.5	99.6	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 600	99.5	99.6	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 500	99.5	99.6	99.7	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.5	99.6	99.7	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.5	99.6	99.7	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.5	99.6	99.7	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.5	99.6	99.7	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.5	99.6	99.7	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 3661

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 06-08

CEILING		VISIBILITY IN STATUTE MILES														
IN FEET	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9
GE 20000	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9
GE 18000	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7
GE 16000	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
GE 14000	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7
GE 12000	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 10000	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 9000	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 8000	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 7000	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 6000	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 5000	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 4500	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 4000	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 3500	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 3000	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 639

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 MAY 89
MONTH: APR HOURS: 09-11

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4
GE 20000	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
GE 18000	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3	92.3
GE 16000	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6
GE 14000	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5
GE 12000	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
GE 10000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 9000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 8000	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9
GE 7000	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 6000	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 5000	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 4500	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 4000	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 500	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 3000	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 2500	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 718

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES																
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
NO CEIL	81.9	81.9	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.2	82.2	82.2	82.2
GE 20000	89.8	89.8	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.1	90.1	90.1	90.1
GE 18000	90.1	90.1	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.4	90.4	90.4	90.4
GE 16000	90.3	90.3	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.4	90.5	90.5	90.5	90.5
GE 14000	91.1	91.1	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.4	91.4	91.4	91.4
GE 12000	91.9	91.9	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.2	92.2	92.2	92.2
GE 10000	94.5	94.5	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.8	94.8	94.8	94.8
GE 9000	94.8	94.8	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	95.1	95.1	95.1	95.1
GE 8000	95.1	95.1	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.3	95.3	95.3	95.3
GE 7000	95.5	95.5	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.8	95.8	95.8	95.8
GE 6000	96.0	96.0	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.3	96.3	96.3	96.3
GE 5000	97.5	97.5	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.7	97.7	97.7	97.7
GE 4500	97.9	97.9	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.2	98.2	98.2	98.2
GE 4000	99.2	99.2	99.3	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.6	99.6	99.6	99.6
GE 3500	99.2	99.2	99.3	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.6	99.6	99.6	99.6
GE 3000	99.4	99.4	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.9	99.9	99.9	99.9
GE 2500	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 2000	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 1800	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 1500	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 1200	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 1000	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 900	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 800	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 700	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 600	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 500	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 400	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 300	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 200	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 100	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 000	99.6	99.6	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 708

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	78.6	78.6	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7	78.7
GE 20000	87.0	87.0	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2	87.2
GE 18000	87.3	87.3	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5	87.5
GE 16000	88.2	88.2	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4	88.4
GE 14000	89.6	89.6	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7
GE 12000	91.9	91.9	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0
GE 10000	93.8	93.8	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0
GE 9000	93.8	93.8	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0
GE 8000	94.3	94.3	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4
GE 7000	94.3	94.3	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4
GE 6000	94.9	94.9	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0
GE 5000	96.8	96.8	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
GE 4500	97.1	97.1	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 4000	98.9	98.9	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 3500	98.9	98.9	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 3000	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 2500	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 663

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3	82.3
GE 20000	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2
GE 18000	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2
GE 16000	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
GE 14000	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7
GE 12000	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
GE 10000	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 9000	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 8000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 7000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 6000	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2
GE 5000	98.1	98.1	98.1	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 4500	98.1	98.1	98.1	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 4000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 470

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: 21 23

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3
GE 20000	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 18000	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 16000	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 14000	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 12000	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
GE 10000	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
GE 9000	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
GE 8000	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 7000	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 6000	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 5000	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 4500	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 179

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	83.5	83.5	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6
GE 20000	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3	90.3
GE 18000	90.6	90.6	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7
GE 16000	91.0	91.0	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
GE 14000	92.1	92.1	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2
GE 12000	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.9	93.9	93.9	93.9
GE 10000	95.4	95.4	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 9000	95.5	95.5	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6
GE 8000	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.2	96.2	96.2	96.2
GE 7000	96.4	96.4	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 6000	97.0	97.0	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
GE 5000	98.2	98.2	98.2	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 4500	98.3	98.3	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
GE 4000	99.4	99.4	99.5	99.5	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 3500	99.4	99.4	99.5	99.5	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 3000	99.6	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.9	99.9	99.9	99.9
GE 2500	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 2000	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	99.8	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 3377

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 MAY 89
MONTH: MAY HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 1/3	GE 1/4	GE	GE
NO CEIL	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4
GE 20000	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4
GE 18000	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
GE 16000	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
GE 14000	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
GE 12000	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
GE 10000	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6
GE 9000	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 8000	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 7000	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 6000	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 5000	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 4500	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 645

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AC
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 09-11

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CELL	92.9	92.9	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0
GE 20000	97.3	97.3	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
GE 18000	97.4	97.4	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 16000	97.4	97.4	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 14000	98.0	98.0	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
GE 12000	98.9	98.9	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE 10000	99.4	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 9000	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 8000	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 7000	99.7	99.7	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 6000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 5000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 702

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 1/8
NO CEIL	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
GE 20000	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 18000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 16000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 14000	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
GE 12000	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
GE 10000	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 9000	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 8000	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 7000	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 6000	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 5000	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 4500	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 4000	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 3500	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 691

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0	87.0
GE 20000	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5
GE 18000	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6
GE 16000	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1
GE 14000	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7
GE 12000	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3
GE 10000	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3
GE 9000	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3
GE 8000	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3
GE 7000	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7
GE 6000	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 623

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5
GE 20000	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3
GE 18000	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9
GE 16000	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2
GE 14000	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
GE 12000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 10000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 9000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 8000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 7000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 6000	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS: 1000

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3
GE 20000	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 18000	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5
GE 16000	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5
GE 14000	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9
GE 12000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 10000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 9000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 8000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 7000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 6000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 241

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	90.6	90.6	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7	90.7
GE 20000	95.2	95.2	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3
GE 18000	95.5	95.5	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6
GE 16000	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8
GE 14000	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 12000	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 10000	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 9000	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 8000	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 7000	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
GE 6000	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 5000	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 4500	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 4000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 3372

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 20000	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
GE 18000	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
GE 16000	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
GE 14000	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 12000	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2
GE 10000	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 9000	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 8000	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 7000	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 6000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 69

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 09-11

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 1/4	GE 1/8	GE 0
NO CEIL	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.2
GE 20000	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5
GE 18000	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5
GE 16000	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 14000	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 12000	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE 10000	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 9000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 8000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 7000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 6000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 710

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 20000	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 18000	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 16000	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 14000	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
GE 12000	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 10000	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 9000	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 8000	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 7000	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 6000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 682

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9
GE 20000	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 18000	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 16000	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 14000	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 12000	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE 10000	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 9000	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 8000	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 7000	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 6000	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 623

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	88.3	88.3	88.3	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5
GE 20000	94.1	94.1	94.1	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3
GE 18000	95.3	95.3	95.3	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 16000	95.3	95.3	95.3	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 14000	96.9	96.9	96.9	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
GE 12000	98.4	98.4	98.4	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6
GE 10000	98.6	98.6	98.6	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 9000	98.6	98.6	98.6	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 8000	98.6	98.6	98.6	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 7000	98.6	98.6	98.6	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 6000	99.2	99.2	99.2	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 5000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 488

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	88.6	88.6	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3
GE 20000	93.6	93.6	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3
GE 18000	95.0	95.0	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7
GE 16000	95.0	95.0	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7
GE 14000	96.4	96.4	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2
GE 12000	97.5	97.5	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 10000	97.9	97.9	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6
GE 9000	97.9	97.9	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6
GE 8000	97.9	97.9	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6
GE 7000	97.9	97.9	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6
GE 6000	98.2	98.2	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 5000	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.3	99.3	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 281

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VESUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	92.9	92.9	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0
GE 20000	96.2	96.2	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
GE 18000	96.5	96.5	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6
GE 16000	96.6	96.6	96.6	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 14000	97.5	97.5	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 12000	98.5	98.5	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6
GE 10000	99.2	99.2	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 9000	99.3	99.3	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 8000	99.3	99.3	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 7000	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 6000	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 5000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 3434

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 85
MONTH: JUL HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4	72.4
GE 20000	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5	79.5
GE 18000	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8	79.8
GE 16000	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1	80.1
GE 14000	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4	85.4
GE 12000	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7
GE 10000	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1
GE 9000	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1
GE 8000	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 7000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 6000	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 623

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 09-11

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6	77.6
GE 20000	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0
GE 18000	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0	84.0
GE 16000	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3	84.3
GE 14000	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9
GE 12000	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 10000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 9000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 8000	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 7000	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 6000	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 5000	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4500	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4000	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 3500	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 3000	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 664

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2	80.2
GE 20000	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7	84.7
GE 18000	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1	86.1
GE 16000	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3
GE 14000	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
GE 12000	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4
GE 10000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 9000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 8000	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
GE 7000	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 6000	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 655

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3
GE 20000	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8
GE 18000	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5
GE 16000	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
GE 14000	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7
GE 12000	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
GE 10000	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1
GE 9000	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1
GE 8000	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1	96.1
GE 7000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 6000	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE 5000	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 4500	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 618

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0	81.0
GE 20000	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9
GE 18000	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9	86.9
GE 16000	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1
GE 14000	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0
GE 12000	95.3	95.3	95.3	95.3	95.3	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6
GE 10000	95.6	95.6	95.6	95.6	95.6	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8
GE 9000	95.6	95.6	95.6	95.6	95.6	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8
GE 8000	95.6	95.6	95.6	95.6	95.6	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8
GE 7000	96.7	96.7	96.7	96.7	96.7	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
GE 6000	99.1	99.1	99.3	99.3	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 5000	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 4500	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 4000	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 3500	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 3000	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 2500	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 2000	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1800	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1500	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1200	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1000	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 900	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 800	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 700	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 600	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 500	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 400	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 300	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 200	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 100	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 000	99.3	99.3	99.5	99.5	99.5	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8

TOTAL NUMBER OF OBSERVATIONS 427

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4
GE 20000	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8
GE 18000	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8	84.8
GE 16000	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2	85.2
GE 14000	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1
GE 12000	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8	93.8
GE 10000	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8
GE 9000	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8
GE 8000	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8
GE 7000	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7
GE 6000	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 5000	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.5	99.5	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 210

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 80
MONTH: JUL HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4	79.4
GE 20000	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6	84.6
GE 18000	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3
GE 16000	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5	85.5
GE 14000	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0
GE 12000	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 10000	96.4	96.4	96.4	96.4	96.4	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 9000	96.4	96.4	96.4	96.4	96.4	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 8000	96.6	96.6	96.6	96.6	96.6	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 7000	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2
GE 6000	98.9	98.9	98.9	98.9	98.9	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE 5000	99.8	99.8	99.8	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 4500	99.8	99.8	99.8	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 4000	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 3500	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 3000	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 2500	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 3197

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO TC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	79.2	79.2	79.2	79.2	79.2	79.2	79.2	79.2	79.2	79.2	79.2	79.2	79.2	79.2	79.2	79.2
GE 20000	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1
GE 18000	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1	82.1
GE 16000	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3
GE 14000	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9
GE 12000	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 10000	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
GE 9000	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
GE 8000	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 7000	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 6000	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 5000	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4500	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 663

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 09-11

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4	82.4
GE 20000	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5
GE 18000	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6	86.6
GE 16000	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3
GE 14000	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
GE 12000	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 10000	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 9000	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 8000	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 7000	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 6000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 732

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3
GE 20000	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
GE 18000	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
GE 16000	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3
GE 14000	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5
GE 12000	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
GE 10000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 9000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 8000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 7000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 6000	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 5000	99.6	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4500	99.6	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4000	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 703

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1	79.1
GE 20000	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3	87.3
GE 18000	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
GE 16000	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0
GE 14000	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9
GE 12000	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8
GE 10000	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3	95.3
GE 9000	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4
GE 8000	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6
GE 7000	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0
GE 6000	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9
GE 5000	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 4500	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 655

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
GE 20000	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5
GE 18000	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5
GE 16000	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1	83.1
GE 14000	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5
GE 12000	89.9	89.9	89.9	89.9	89.9	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1
GE 10000	92.0	92.0	92.0	92.0	92.0	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2
GE 9000	92.2	92.2	92.2	92.2	92.2	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4
GE 8000	92.6	92.6	92.6	92.6	92.6	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8
GE 7000	93.8	93.8	93.8	93.8	94.0	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2
GE 6000	97.1	97.1	97.1	97.1	97.3	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5
GE 5000	99.2	99.2	99.2	99.2	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 4500	99.2	99.2	99.2	99.2	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 4000	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.6	99.6	99.6	99.6	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 485

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3
GE 20000	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 18000	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 16000	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 14000	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 12000	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
GE 10000	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
GE 9000	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
GE 8000	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 7000	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 6000	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 224

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9	80.9
GE 20000	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3
GE 18000	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4	86.4
GE 16000	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7
GE 14000	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6
GE 12000	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2
GE 10000	96.8	96.8	96.8	96.8	96.8	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9
GE 9000	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9
GE 8000	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.1
GE 7000	97.4	97.4	97.4	97.4	97.4	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5	97.5
GE 6000	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 5000	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4500	99.7	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 4000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 3462

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5	82.5
GE 20000	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6
GE 18000	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6	85.6
GE 16000	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0	86.0
GE 14000	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8
GE 12000	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2
GE 10000	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4
GE 9000	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7
GE 8000	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0
GE 7000	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 6000	99.2	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 5000	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 605

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 09-11

CEILING		VISIBILITY IN STATUTE MILES															
IN FEET	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
NO CEIL	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	86.7	
GE 20000	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	
GE 18000	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	
GE 16000	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	
GE 14000	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	
GE 12000	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	
GE 10000	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	97.2	
GE 9000	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	
GE 8000	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	
GE 7000	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	
GE 6000	99.4	99.4	99.4	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	99.6	
GE 5000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 4500	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 4000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 3500	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 3000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 2500	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 2000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1800	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1500	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1200	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 900	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 800	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 700	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 600	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 500	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 400	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 300	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 200	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 100	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 000	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	

TOTAL NUMBER OF OBSERVATIONS 682

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	81.4	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6
GE 20000	86.3	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5	86.5
GE 18000	86.6	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 16000	87.7	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9
GE 14000	91.1	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
GE 12000	93.4	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5
GE 10000	94.0	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2
GE 9000	94.8	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9
GE 8000	94.9	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 7000	95.4	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 6000	97.7	97.8	97.8	97.8	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 5000	99.5	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 4500	99.5	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 4000	99.5	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 3500	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 651

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6
GE 20000	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	88.0	88.0	88.0	88.0
GE 18000	88.0	88.0	88.0	88.0	88.0	88.0	88.0	88.0	88.0	88.0	88.0	88.0	88.1	88.1	88.1	88.1
GE 16000	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.0	89.1	89.1	89.1	89.1
GE 14000	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.3	91.3	91.3	91.3
GE 12000	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.5	93.5	93.5	93.5
GE 10000	94.0	94.0	94.0	94.0	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.3	94.3	94.3	94.3
GE 9000	94.0	94.0	94.0	94.0	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.3	94.3	94.3	94.3
GE 8000	94.7	94.7	94.7	94.7	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	95.0	95.0	95.0
GE 7000	95.3	95.3	95.3	95.3	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.7	95.7	95.7
GE 6000	98.5	98.5	98.5	98.5	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.7	98.8	98.8	98.8
GE 5000	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 4500	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 4000	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 3500	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 3000	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 2500	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 2000	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 1800	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 1500	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 1200	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 1000	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 900	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 800	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 700	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 600	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 500	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 400	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 300	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 200	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 100	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 000	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 599

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1	87.1
GE 20000	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3	91.3
GE 18000	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
GE 16000	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
GE 14000	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
GE 12000	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
GE 10000	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 9000	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 8000	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 7000	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 6000	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 402

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: 21-23

CEILING		VISIBILITY IN STATUTE MILES															
IN FEET	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
NO CEIL	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	
GE 20000	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	
GE 18000	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	
GE 16000	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	
GE 14000	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	
GE 12000	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	
GE 10000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 9000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 8000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 7000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 6000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	

TOTAL NUMBER OF OBSERVATIONS 149

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5
GE 20000	88.4	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5
GE 18000	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.7	88.7	88.7	88.7
GE 16000	89.3	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4
GE 14000	91.7	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
GE 12000	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.7	94.7	94.7	94.7
GE 10000	95.8	95.8	95.8	95.8	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 9000	96.2	96.2	96.2	96.2	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
GE 8000	96.4	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 7000	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.9	96.9	96.9	96.9
GE 6000	98.7	98.8	98.8	98.8	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 5000	99.8	99.8	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 4500	99.8	99.8	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 4000	99.8	99.8	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0
GE 3500	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 3088

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 06-08

CEILING IN FEET	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9	84.9
GE 20000	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
GE 18000	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
GE 16000	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
GE 14000	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0	92.0
GE 12000	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1	93.1
GE 10000	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4
GE 9000	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.4
GE 8000	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 7000	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0	96.0
GE 6000	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 5000	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4500	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 649

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 09-11

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6	80.6
GE 20000	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6
GE 18000	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4
GE 16000	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7	89.7
GE 14000	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
GE 12000	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2
GE 10000	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 9000	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 8000	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6
GE 7000	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
GE 6000	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 701

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7
GE 20000	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5
GE 18000	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6
GE 16000	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
GE 14000	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4
GE 12000	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7	93.7
GE 10000	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1
GE 9000	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1
GE 8000	94.5	94.5	94.5	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
GE 7000	95.0	95.0	95.0	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 6000	96.8	96.8	96.8	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
GE 5000	99.0	99.0	99.0	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 4500	99.0	99.0	99.0	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 4000	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.7	99.7	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 694

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	78.2	78.2	78.2	78.4	78.4	78.4	78.4	78.4	78.4	78.4	78.4	78.4	78.4	78.4	78.4	78.4
GE 20000	87.6	87.6	87.6	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7
GE 18000	87.6	87.6	87.6	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7	87.7
GE 16000	89.1	89.1	89.1	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3	89.3
GE 14000	91.4	91.4	91.4	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6
GE 12000	94.0	94.0	94.0	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2
GE 10000	94.8	94.8	94.8	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9
GE 9000	94.8	94.8	94.8	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9
GE 8000	95.4	95.4	95.4	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6
GE 7000	96.0	96.0	96.0	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2
GE 6000	98.2	98.2	98.2	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 5000	99.4	99.4	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4500	99.4	99.4	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4000	99.5	99.5	99.5	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 3500	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.7	99.7	99.7	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 652

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	82.4	82.4	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6
GE 20000	89.3	89.3	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5	89.5
GE 18000	89.7	89.7	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0
GE 16000	91.5	91.5	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7	91.7
GE 14000	92.4	92.4	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6	92.6
GE 12000	94.9	94.9	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 10000	97.5	97.5	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
GE 9000	97.5	97.5	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8	97.8
GE 8000	98.2	98.2	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
GE 7000	98.2	98.2	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
GE 6000	98.9	98.9	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 5000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 448

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES														
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4
NO CEIL	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4	87.4
GE 20000	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8
GE 18000	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6	95.6
GE 16000	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
GE 14000	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
GE 12000	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 10000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 9000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 8000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 7000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 6000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 135

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	81.5	81.5	81.5	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6
GE 20000	89.5	89.5	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6
GE 18000	90.1	90.1	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2
GE 16000	90.8	90.8	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9
GE 14000	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2
GE 12000	94.1	94.1	94.1	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2
GE 10000	95.4	95.4	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 9000	95.4	95.4	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 8000	96.1	96.1	96.1	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2
GE 7000	96.5	96.5	96.5	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6
GE 6000	98.2	98.2	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 5000	99.6	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4500	99.6	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 4000	99.8	99.8	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.8	99.8	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 3279

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 06-08

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	83.4	83.4	83.5	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7	83.7
GE 20000	88.2	88.2	88.4	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6
GE 18000	88.4	88.4	88.6	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7	88.7
GE 16000	89.1	89.1	89.3	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4	89.4
GE 14000	90.5	90.5	90.6	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8
GE 12000	91.9	91.9	92.0	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2	92.2
GE 10000	93.8	93.8	93.9	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1
GE 9000	94.1	94.1	94.3	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
GE 8000	95.1	95.1	95.3	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 7000	95.1	95.1	95.3	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 6000	96.0	96.0	96.2	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4
GE 5000	97.6	97.6	97.7	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9	97.9
GE 4500	98.1	98.1	98.3	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
GE 4000	98.4	98.6	98.8	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE 3500	98.4	98.6	98.8	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE 3000	98.8	99.0	99.1	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 2500	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 2000	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1800	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1500	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1200	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1000	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 900	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 800	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 700	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 600	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 500	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 400	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.7	99.7
GE 300	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.7	99.7
GE 200	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.7	100.0
GE 100	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.7	100.0
GE 000	99.0	99.1	99.3	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.7	100.0

TOTAL NUMBER OF OBSERVATIONS 577

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 09-11

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	80.5	80.5	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7
GE 20000	87.8	87.8	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9
GE 18000	88.4	88.4	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5	88.5
GE 16000	88.7	88.7	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8
GE 14000	91.7	91.7	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
GE 12000	93.1	93.1	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2	93.2
GE 10000	94.4	94.4	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
GE 9000	94.9	94.9	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0
GE 8000	96.2	96.2	96.4	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 7000	96.2	96.2	96.4	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 6000	97.4	97.4	97.6	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 5000	97.9	97.9	98.0	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.2
GE 4500	98.0	98.0	98.2	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 4000	98.5	98.5	98.6	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 3500	98.6	98.6	98.8	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 3000	98.8	98.8	98.9	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 2500	98.9	98.9	99.1	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 2000	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1800	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1500	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1200	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1000	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 900	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 800	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 700	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 600	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 500	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 400	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 300	99.2	99.2	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 200	99.4	99.4	99.5	99.7	99.7	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 100	99.4	99.4	99.5	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.4	99.4	99.5	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 662

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 12-14

CEILING IN FEET	VISIBILITY IN STATUTE MILES														
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4
NO CEIL	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0	80.0
GE 20000	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8	90.8
GE 18000	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
GE 16000	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6
GE 14000	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0
GE 12000	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9
GE 10000	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	95.0	95.3	95.3	95.3	95.3	95.3
GE 9000	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	95.0	95.3	95.3	95.3	95.3	95.3
GE 8000	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	96.1	96.4	96.4	96.4	96.4	96.4
GE 7000	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.4	96.7	96.7	96.7	96.7	96.7
GE 6000	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.6	96.9	96.9	96.9	96.9	96.9
GE 5000	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	97.0	97.3	97.3	97.3	97.3	97.3
GE 4500	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	97.0	97.3	97.3	97.3	97.3	97.3
GE 4000	97.8	97.8	97.8	98.0	98.0	98.0	98.0	98.0	98.0	98.1	98.4	98.4	98.4	98.4	98.4
GE 3500	98.0	98.0	98.0	98.3	98.3	98.3	98.3	98.3	98.3	98.4	98.8	98.8	98.8	98.8	98.8
GE 3000	98.3	98.3	98.3	98.6	98.6	98.6	98.6	98.6	98.6	98.8	99.1	99.1	99.1	99.1	99.1
GE 2500	98.3	98.3	98.3	98.6	98.6	98.6	98.8	98.8	98.8	98.9	99.2	99.2	99.2	99.2	99.2
GE 2000	98.8	98.8	98.8	99.1	99.1	99.1	99.2	99.2	99.2	99.4	99.7	99.7	99.7	99.7	99.7
GE 1800	98.8	98.8	98.8	99.1	99.1	99.1	99.2	99.2	99.2	99.4	99.7	99.7	99.7	99.7	99.7
GE 1500	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 1200	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 1000	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 900	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 800	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 700	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 600	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 500	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 400	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 300	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 200	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 100	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0
GE 000	98.9	98.9	98.9	99.2	99.2	99.2	99.5	99.5	99.5	99.7	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 640

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9	81.9
GE 20000	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
GE 18000	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
GE 16000	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
GE 14000	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9
GE 12000	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0	95.0
GE 10000	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7
GE 9000	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7
GE 8000	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3	96.3
GE 7000	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7	96.7
GE 6000	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9	96.9
GE 5000	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7	97.7
GE 4500	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 4000	98.6	98.6	98.6	98.6	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 3500	98.6	98.6	98.6	98.6	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8	98.8
GE 3000	99.1	99.1	99.1	99.1	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.5	99.5	99.5
GE 2500	99.1	99.1	99.1	99.1	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.5	99.5	99.5
GE 2000	99.1	99.1	99.1	99.1	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.5	99.5	99.5
GE 1800	99.1	99.1	99.1	99.1	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.5	99.5	99.5
GE 1500	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 1200	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 1000	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 900	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 800	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 700	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 600	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 500	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 400	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 300	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 200	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 100	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0
GE 000	99.5	99.5	99.5	99.5	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 575

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 MAY 89
MONTH: NOV HOURS: 18-20

CEILING IN FEET	VISIBILITY IN STATUTE MILES														
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4
NO CEIL	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3	86.3
GE 20000	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
GE 18000	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
GE 16000	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9	91.9
GE 14000	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
GE 12000	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2	96.2
GE 10000	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 9000	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 8000	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
GE 7000	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1
GE 6000	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
GE 5000	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 4500	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2
GE 4000	99.2	99.2	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 3500	99.2	99.2	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 3000	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	99.5	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 371

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1
GE 20000	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 18000	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 16000	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 14000	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9	94.9
GE 12000	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6
GE 10000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 9000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 8000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 7000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 6000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 5000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 4000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 59

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	82.1	82.1	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2
GE 20000	89.7	89.7	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8
GE 18000	90.0	90.0	90.1	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2
GE 16000	90.4	90.4	90.4	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5
GE 14000	92.6	92.6	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7
GE 12000	93.9	93.9	93.9	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0
GE 10000	95.1	95.1	95.2	95.2	95.2	95.2	95.2	95.2	95.2	95.3	95.4	95.4	95.4	95.4	95.4	95.4
GE 9000	95.3	95.3	95.4	95.4	95.4	95.4	95.4	95.4	95.4	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 8000	96.3	96.3	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 7000	96.4	96.4	96.5	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.7	96.7	96.7	96.7	96.7	96.7
GE 6000	97.0	97.0	97.1	97.1	97.1	97.1	97.1	97.1	97.1	97.2	97.2	97.2	97.2	97.2	97.2	97.2
GE 5000	97.8	97.8	97.9	97.9	97.9	97.9	97.9	97.9	97.9	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 4500	98.0	98.0	98.1	98.2	98.2	98.2	98.2	98.2	98.2	98.2	98.3	98.3	98.3	98.3	98.3	98.3
GE 4000	98.5	98.5	98.6	98.7	98.8	98.8	98.8	98.8	98.8	98.8	98.9	98.9	98.9	98.9	98.9	98.9
GE 3500	98.5	98.6	98.7	98.8	98.8	98.9	98.9	98.9	98.9	98.9	99.0	99.0	99.0	99.0	99.0	99.0
GE 3000	98.9	98.9	99.0	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.3	99.3	99.3	99.3	99.3	99.3
GE 2500	98.9	99.0	99.1	99.2	99.3	99.3	99.3	99.3	99.3	99.3	99.4	99.4	99.4	99.4	99.4	99.4
GE 2000	99.1	99.2	99.3	99.4	99.4	99.4	99.5	99.5	99.5	99.5	99.6	99.6	99.6	99.6	99.6	99.6
GE 1800	99.1	99.2	99.3	99.4	99.4	99.4	99.5	99.5	99.5	99.5	99.6	99.6	99.6	99.6	99.6	99.6
GE 1500	99.2	99.3	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8
GE 1200	99.2	99.3	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8
GE 1000	99.2	99.3	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8
GE 900	99.2	99.3	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8
GE 800	99.2	99.3	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8
GE 700	99.2	99.3	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8
GE 600	99.2	99.3	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8
GE 500	99.2	99.3	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8
GE 400	99.2	99.3	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.9	99.9
GE 300	99.2	99.3	99.4	99.5	99.5	99.5	99.7	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.9	99.9
GE 200	99.2	99.3	99.4	99.5	99.6	99.6	99.7	99.7	99.7	99.8	99.8	99.8	99.9	99.9	99.9	100.0
GE 100	99.2	99.3	99.4	99.6	99.6	99.6	99.7	99.7	99.7	99.8	99.9	99.9	99.9	99.9	99.9	100.0
GE 000	99.2	99.3	99.4	99.6	99.6	99.6	99.7	99.7	99.7	99.8	99.9	99.9	99.9	99.9	99.9	100.0

TOTAL NUMBER OF OBSERVATIONS 2884

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF A2
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 06-08

CEILING		VISIBILITY IN STATUTE MILES															
IN FEET	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0	
NO CEIL	77.1	77.3	77.6	77.6	77.9	77.9	78.1	78.1	78.1	78.1	78.1	78.1	78.1	78.1	78.1	78.1	
GE 20000	83.1	83.3	83.6	83.6	83.9	83.9	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	
GE 18000	83.4	83.6	83.9	83.9	84.2	84.2	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	
GE 16000	83.4	83.6	83.9	83.9	84.2	84.2	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	
GE 14000	84.4	84.5	84.9	84.9	85.2	85.2	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	85.3	
GE 12000	87.3	87.4	87.8	87.8	88.1	88.1	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	
GE 10000	89.2	89.4	89.7	89.7	90.0	90.0	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	
GE 9000	89.5	89.7	90.0	90.0	90.3	90.3	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	
GE 8000	90.5	90.7	91.0	91.0	91.3	91.3	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	
GE 7000	91.8	92.1	92.4	92.4	92.8	92.8	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	
GE 6000	92.1	92.6	93.1	93.1	93.4	93.4	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6	93.6	
GE 5000	94.0	94.5	95.2	95.2	95.5	95.5	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	
GE 4500	94.0	94.5	95.2	95.2	95.5	95.5	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	95.7	
GE 000	95.3	95.8	96.8	96.8	97.3	97.3	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	
GE 3500	95.7	96.1	97.1	97.3	97.9	97.9	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	98.1	
GE 3000	96.3	97.1	98.1	98.2	98.9	98.9	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	99.2	
GE 2500	96.8	97.6	98.6	98.7	99.4	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	
GE 2000	96.8	97.6	98.6	98.7	99.4	99.4	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	
GE 1800	96.8	97.6	98.6	98.7	99.4	99.4	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	
GE 1500	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1200	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 1000	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 900	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 800	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 700	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 600	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 500	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 400	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 300	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 200	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 100	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	
GE 000	96.8	97.7	98.7	98.9	99.5	99.5	99.8	99.8	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	

TOTAL NUMBER OF OBSERVATIONS 621

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 09 11

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	70.8	70.8	71.0	71.0	71.0	71.0	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1	71.1
GE 20000	81.2	81.3	81.5	81.5	81.5	81.5	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6
GE 18000	82.2	82.3	82.5	82.5	82.5	82.5	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6
GE 16000	82.2	82.3	82.5	82.5	82.5	82.5	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6	82.6
GE 14000	84.1	84.2	84.3	84.3	84.3	84.3	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5	84.5
GE 12000	86.4	86.5	86.6	86.6	86.6	86.6	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8	86.8
GE 10000	88.6	88.8	89.1	89.1	89.1	89.1	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2	89.2
GE 9000	89.4	89.5	89.8	89.8	89.8	89.8	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9	89.9
GE 8000	90.4	90.5	90.8	90.8	90.8	90.8	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9	90.9
GE 7000	90.7	90.8	91.1	91.1	91.1	91.1	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
GE 6000	92.1	92.2	92.5	92.5	92.5	92.5	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7	92.7
GE 5000	94.3	94.4	94.8	94.8	95.0	95.0	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 4500	94.3	94.4	94.8	94.8	95.0	95.0	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 4000	95.8	96.0	96.4	96.4	96.7	96.7	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8	96.8
GE 3500	96.4	96.6	97.0	97.0	97.3	97.4	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
GE 3000	96.8	97.0	97.4	97.4	97.8	98.0	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 2500	96.8	97.0	97.4	97.4	97.8	98.0	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
GE 2000	97.6	97.7	98.1	98.1	98.6	98.7	99.4	99.4	99.4	99.6	99.6	99.6	99.6	99.6	99.6	99.6
GE 1800	97.6	97.7	98.3	98.3	98.7	98.9	99.6	99.6	99.6	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 1500	97.6	97.7	98.3	98.3	98.7	98.9	99.6	99.6	99.6	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 1200	97.6	97.7	98.3	98.3	98.7	98.9	99.6	99.6	99.6	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 1000	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	97.6	97.7	98.3	98.3	98.9	99.0	99.7	99.7	99.7	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 696

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 12-14

CEILING	VISIBILITY IN STATUTE MILES																
	IN FEET	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL		72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9	72.9
GE 20000		83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2	83.2
GE 18000		83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6	83.6
GE 16000		84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1	84.1
GE 14000		85.6	85.6	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8	85.8
GE 12000		88.2	88.2	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3
GE 10000		89.7	89.7	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8	89.8
GE 9000		89.8	89.8	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0	90.0
GE 8000		91.1	91.1	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
GE 7000		91.2	91.2	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4	91.4
GE 6000		91.7	91.7	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
GE 5000		93.2	93.2	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 4500		93.3	93.3	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5	93.5
GE 4000		94.2	94.2	94.4	94.4	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7	94.7
GE 3500		94.7	94.7	94.7	95.0	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 3000		95.8	95.8	95.8	96.1	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
GE 2500		96.2	96.2	96.5	96.7	97.1	97.1	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4	97.4
GE 2000		97.3	97.4	97.7	97.9	98.5	98.5	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9	98.9
GE 1800		97.4	97.6	97.9	98.0	98.6	98.6	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 1500		97.5	97.7	98.0	98.3	98.9	99.2	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1200		97.6	97.7	98.0	98.3	98.9	99.2	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1000		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000		97.6	97.7	98.0	98.3	99.1	99.4	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 660

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 15-17

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6	73.6
GE 20000	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2	82.2
GE 18000	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0	83.0
GE 16000	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3	83.3
GE 14000	85.7	85.7	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9	85.9
GE 12000	88.9	88.9	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1
GE 10000	89.4	89.4	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6	89.6
GE 9000	90.1	90.1	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2	90.2
GE 8000	90.9	90.9	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1	91.1
GE 7000	91.4	91.4	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6	91.6
GE 6000	91.6	91.6	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
GE 5000	92.3	92.3	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4	92.4
GE 4500	92.6	92.6	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9	92.9
GE 4000	93.6	93.6	93.9	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1	94.1
GE 3500	94.4	94.4	94.8	94.9	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1	95.1
GE 3000	95.6	95.6	96.1	96.5	97.0	97.1	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 2500	96.8	96.8	97.3	97.6	98.1	98.3	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5
GE 2000	97.3	97.3	97.8	98.1	99.0	99.2	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 1800	97.3	97.3	97.8	98.1	99.0	99.2	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3	99.3
GE 1500	97.8	97.8	98.3	98.7	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1200	97.8	97.8	98.3	98.7	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1000	97.8	97.8	98.3	98.7	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 900	97.8	97.8	98.3	98.7	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 800	97.8	97.8	98.3	98.7	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 700	97.8	97.8	98.3	98.7	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 600	97.8	97.8	98.3	98.7	99.5	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 500	97.8	97.8	98.3	98.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	97.8	97.8	98.3	98.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	97.8	97.8	98.3	98.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	97.8	97.8	98.3	98.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	97.8	97.8	98.3	98.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	97.8	97.8	98.3	98.7	99.7	99.8	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 594

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 18-20

CEILING	VISIBILITY IN STATUTE MILES																
	IN FEET	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL		81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5
GE 20000		87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8	87.8
GE 18000		89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1
GE 16000		89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1	89.1
GE 14000		91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2	91.2
GE 12000		91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8	91.8
GE 10000		92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1
GE 9000		92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1
GE 8000		93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 7000		93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9	93.9
GE 6000		94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2	94.2
GE 5000		94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
GE 4500		94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5
GE 4000		96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4
GE 3500		96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4	96.4
GE 3000		97.0	97.3	98.8	98.8	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1
GE 2500		97.3	97.6	99.1	99.1	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 2000		97.3	97.6	99.1	99.1	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1800		97.3	97.6	99.1	99.1	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1500		97.3	97.6	99.1	99.1	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1200		97.3	97.6	99.1	99.1	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1000		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000		97.3	97.6	99.1	99.1	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 329

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: 21-23

CEILING IN FEET	VISIBILITY IN STATUTE MILES														
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4
NO CEIL	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1	88.1
GE 20000	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0	91.0
GE 18000	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5
GE 16000	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5	92.5
GE 14000	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0
GE 12000	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0
GE 10000	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0
GE 9000	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0	94.0
GE 8000	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 7000	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
GE 6000	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
GE 5000	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
GE 4500	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0	97.0
GE 4000	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5
GE 3500	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5	98.5
GE 3000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 2000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 1000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 000	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 60

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NOCEIL	74.7	74.8	74.9	74.9	74.9	74.9	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0	75.0
GE 20000	83.2	83.2	83.4	83.4	83.4	83.4	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5	83.5
GE 18000	83.9	84.0	84.1	84.1	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2	84.2
GE 16000	84.1	84.2	84.3	84.3	84.3	84.3	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4	84.4
GE 14000	85.8	85.9	86.0	86.0	86.1	86.1	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2	86.2
GE 12000	88.2	88.3	88.5	88.5	88.5	88.5	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6	88.6
GE 10000	89.7	89.7	89.9	89.9	90.0	90.0	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1	90.1
GE 9000	90.1	90.1	90.3	90.3	90.4	90.4	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5	90.5
GE 8000	91.1	91.2	91.4	91.4	91.4	91.4	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
GE 7000	91.7	91.8	92.0	92.0	92.0	92.0	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1	92.1
GE 6000	92.2	92.4	92.6	92.6	92.7	92.7	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8	92.8
GE 5000	93.7	93.8	94.1	94.1	94.2	94.2	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3	94.3
GE 4500	93.8	93.9	94.2	94.2	94.3	94.3	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4	94.4
GE 4000	95.0	95.2	95.6	95.6	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 3500	95.5	95.7	96.1	96.2	96.5	96.5	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6	96.6
GE 3000	96.3	96.6	97.2	97.3	97.8	97.8	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0	98.0
GE 2500	96.8	97.0	97.7	97.8	98.3	98.3	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6	98.6
GE 2000	97.3	97.6	98.2	98.3	98.9	99.0	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4	99.4
GE 1800	97.3	97.6	98.3	98.4	99.0	99.1	99.4	99.4	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 1500	97.5	97.8	98.4	98.6	99.2	99.3	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1200	97.5	97.8	98.4	98.6	99.2	99.3	99.7	99.7	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8
GE 1000	97.5	97.8	98.4	98.6	99.3	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 900	97.5	97.8	98.4	98.6	99.3	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 800	97.5	97.8	98.4	98.6	99.3	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 700	97.5	97.8	98.4	98.6	99.3	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 600	97.5	97.8	98.4	98.6	99.3	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 500	97.5	97.8	98.4	98.6	99.4	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 400	97.5	97.8	98.4	98.6	99.4	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 300	97.5	97.8	98.4	98.6	99.4	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 200	97.5	97.8	98.4	98.6	99.4	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 100	97.5	97.8	98.4	98.6	99.4	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
GE 50	97.5	97.8	98.4	98.6	99.4	99.5	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS 2967

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CEILING VERSUS VISIBILITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: ALL HOURS: ALL

CEILING IN FEET	VISIBILITY IN STATUTE MILES															
	GE 7	GE 6	GE 5	GE 4	GE 3	GE 2 1/2	GE 2	GE 1 1/2	GE 1 1/4	GE 1	GE 3/4	GE 5/8	GE 1/2	GE 3/8	GE 1/4	GE 0
NO CEIL	81.5	81.5	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6	81.6
GE 20000	87.8	87.8	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9	87.9
GE 18000	88.2	88.2	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3	88.3
GE 16000	88.7	88.7	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8	88.8
GE 14000	90.5	90.5	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6	90.6
GE 12000	93.2	93.2	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3	93.3
GE 10000	94.5	94.5	94.5	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6	94.6
GE 9000	94.7	94.7	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.8	94.9	94.9	94.9	94.9
GE 8000	95.4	95.4	95.4	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5	95.5
GE 7000	95.8	95.8	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9	95.9
GE 6000	97.1	97.2	97.2	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3	97.3
GE 5000	98.1	98.1	98.2	98.2	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3	98.3
GE 4500	98.2	98.3	98.3	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4	98.4
GE 4000	98.8	98.8	98.9	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0	99.0
GE 3500	98.9	98.9	99.0	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.1	99.2	99.2	99.2	99.2
GE 3000	99.2	99.2	99.4	99.4	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5	99.5
GE 2500	99.3	99.4	99.5	99.6	99.6	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7	99.7
GE 2000	99.4	99.5	99.6	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.9	99.9	99.9	99.9
GE 1800	99.4	99.5	99.6	99.7	99.8	99.8	99.8	99.8	99.8	99.8	99.8	99.9	99.9	99.9	99.9	99.9
GE 1500	99.5	99.5	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 1200	99.5	99.5	99.7	99.8	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9	99.9
GE 1000	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0
GE 900	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0
GE 800	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0
GE 700	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0
GE 600	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0
GE 500	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0
GE 400	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0
GE 300	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0
GE 200	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0
GE 100	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0
GE 000	99.5	99.6	99.7	99.8	99.9	99.9	99.9	99.9	99.9	99.9	99.9	100.0	100.0	100.0	100.0	100.0

TOTAL NUMBER OF OBSERVATIONS: 38987

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN HOURS: ALL

HOURS (LST)	CLEAR	SCATTERED	BROKEN	OVERCAST	AIRWAY CLASSES		GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
					TOTAL	OBSCURATION			
00-02									0
03-05									0
06-08	28.7	36.5	18.7	16.1			34.8	.8	635
09-11	19.0	43.7	22.7	14.4	.1		37.2	.1	709
12-14	18.2	39.8	27.0	14.9	.1		42.0	.3	693
15-17	17.8	37.8	27.3	17.1			44.3		645
18-20	21.7	38.2	27.8	12.3			40.1		424
21-23	34.9	36.0	17.4	11.6			29.1		86
ALL HOURS	21.0	39.0	24.0	15.0	.0		39.0	.0	3192

MONTH: FEB HOURS: ALL

00-02									0
03-05									0
06-08	23.4	39.5	19.6	17.5			37.1	.2	593
09-11	18.4	36.4	24.4	20.9			45.2		681
12-14	14.9	34.4	30.0	20.7			50.7		663
15-17	15.0	31.9	30.1	23.1			53.2		615
18-20	13.8	33.6	29.5	23.2			52.7		414
21-23	27.4	29.2	24.8	18.6			43.4		113
ALL HOURS	17.6	35.0	26.5	20.9			47.4	.0	3079

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR HOURS: ALL

HOURS (LST)	CLEAR	SCATTERED	BROKEN	AIRWAY CLASSES		GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
				OVERCAST	TOTAL OBSCURATION			
00-02								0
03-05								0
06-08	26.1	41.3	20.8	11.8		32.6		712
09-11	26.0	39.8	19.6	14.7		34.2		812
12-14	18.6	42.6	23.6	15.1		38.7	.1	795
15-17	15.4	42.4	25.7	16.4		42.1		712
18-20	19.3	45.0	22.6	13.1		35.7		482
21-23	29.3	43.3	16.7	10.7		27.3		150
ALL HOURS	21.0	42.0	22.0	14.0		36.0	.0	3663

MONTH: APR HOURS: ALL

00-02								0
03-05								0
06-08	23.5	47.1	19.2	10.2		29.4		639
09-11	23.4	48.5	19.1	9.1		28.1	.1	718
12-14	13.4	53.0	24.9	8.8		33.6	.7	708
15-17	13.7	49.2	24.8	12.3		37.1	1.1	666
18-20	15.7	49.6	22.6	12.1		34.7	.2	470
21-23	27.4	43.6	19.6	9.5		29.1		179
ALL HOURS	18.6	49.2	22.0	10.3		32.2	.4	3380

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY HOURS:ALL

HOURS (LST)	AIRWAY CLASSES				GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	CLEAR	SCATTERED	BROKEN	OVERCAST			
00-02							0
03-05							0
05-08	37.5	38.1	19.7	4.7	24.3		645
09-11	34.5	44.0	17.1	4.4	21.5		702
12-14	28.5	49.6	14.8	7.1	21.9		691
15-17	30.0	44.3	18.5	7.2	25.7	.5	623
18-20	32.1	42.3	18.1	7.4	25.5	.9	470
21-23	45.6	36.9	11.6	5.8	17.4		241
ALL HOURS	33.0	43.0	17.0	6.0	23.0	.0	3372

MONTH: JUN HOURS: ALL

00-02							0
03-05							0
06-08	38.0	44.0	15.2	2.8	17.9		652
09-11	40.5	45.1	11.8	2.5	14.3		711
12-14	33.0	52.2	14.2	.6	14.8		682
15-17	28.1	57.0	13.3	1.6	14.9		623
18-20	34.4	45.3	15.0	5.3	20.3	.2	488
21-23	44.1	37.7	14.2	3.9	18.1	1.1	281
ALL HOURS	35.7	47.9	13.8	2.5	16.4	.1	3437

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL HOURS: ALL

HOURS (LST)	AIRWAY CLASSES				GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	CLEAR	SCATTERED	BROKEN	OVERCAST			
00-02							0
03-05							0
06-08	11.7	49.8	30.3	8.2	38.5		623
09-11	13.8	55.9	24.5	5.7	30.2		665
12-14	8.7	63.9	23.3	4.1	27.4		656
15-17	6.3	71.8	20.3	1.6	21.9		620
18-20	6.3	63.9	24.1	5.4	29.7	.2	427
21-23	20.9	48.8	22.7	7.6	30.3		211
ALL HOURS	10.0	60.0	24.0	5.0	29.0	.0	3202

MONTH: AUG HOURS: ALL

00-02							0
03-05							0
06-08	9.9	56.3	28.8	5.0	33.7		664
09-11	15.1	56.3	25.4	3.1	28.5		733
12-14	5.7	70.6	20.9	2.8	23.7		704
15-17	4.1	67.2	26.3	2.4	28.7		655
18-20	6.0	62.3	27.0	4.7	31.8	.2	485
21-23	10.3	58.0	21.0	2.7	23.7		224
ALL HOURS	9.1	62.2	25.2	3.5	28.7	.0	3465

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP HOURS:ALL

HOURS (LST)	CLEAR	SCATTERED	BROKEN	AIRWAY CLASSES		GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
				OVERCAST	TOTAL OBSCURATION			
00-02								0
03-05								0
06-08	23.0	54.9	16.9	5.3		22.1		605
09-11	25.1	55.6	14.2	5.1		19.4	.1	682
12-14	14.9	60.7	19.9	4.4		24.4		652
15-17	13.5	62.3	20.0	4.2		24.2	.7	599
18-20	17.4	60.8	18.1	3.7		21.8		403
21-23	40.7	50.7	7.3	1.3		8.7		150
ALL HOURS	20.0	58.0	17.0	4.0		21.0	.0	3091

MONTH: OCT HOURS: ALL

00-02									0
03-05									0
06-08	31.6	42.5	18.3	7.6			25.9		649
09-11	29.2	41.5	20.8	8.4			29.2		701
12-14	24.2	47.1	19.5	9.2			28.7		694
15-17	18.8	48.2	22.4	10.6			32.9		653
18-20	26.3	47.8	17.0	8.9			25.9		448
21-23	52.6	29.6	13.3	4.4			17.8		135
ALL HOURS	27.1	44.6	19.5	8.8			28.3		3280

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV HOURS:ALL

HOURS (LST)	AIRWAY CLASSES					GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	CLEAR	SCATTERED	BROKEN	OVERCAST	TOTAL OBSCURATION			
00-02								0
03-05								0
06-08	32.1	44.0	15.9	7.4	.5	23.8		579
09-11	25.4	46.5	19.9	8.2		28.1	.2	662
12-14	22.5	43.8	25.5	8.3		33.8	.3	640
15-17	22.6	42.3	25.2	9.9		35.1	.2	575
18-20	30.7	41.5	20.5	7.3		27.8		371
21-23	40.7	44.1	6.8	8.5		15.3		59
ALL HOURS	26.0	43.0	21.0	8.0	.0	29.0	.0	2886

MONTH: DEC HOURS: ALL

00-02								0
03-05								0
06-08	30.5	33.9	20.6	15.0		35.5	.8	622
09-11	20.3	36.9	25.3	17.5		42.8	.6	696
12-14	18.0	38.2	27.4	16.4		43.8	.5	660
15-17	18.2	38.2	26.4	17.2		43.6	.2	594
18-20	24.3	43.2	18.2	14.3		32.5		329
21-23	32.8	40.3	20.9	6.0		26.9		67
ALL HOURS	22.2	37.6	24.1	16.0		40.2	.4	2968

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF SKY COVER
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: ALL HOURS: ALL

HOURS (LST)	AIRWAY CLASSES				TOTAL OBSCURATION	GT 1/2	PARTIAL OBSCURATION	TOTAL OBS
	CLEAR	SCATTERED	BROKEN	OVERCAST				
00-02								0
03-05								0
06-08	26.3	44.0	20.4	9.2	.0	29.7	.1	7618
09-11	24.3	45.8	20.4	9.5	.0	29.9	.1	8472
12-14	18.4	49.6	22.6	9.4	.0	32.0	.2	8238
15-17	16.9	49.4	23.4	10.4		33.7	.2	7580
18-20	20.6	48.0	21.7	9.7	.0	31.4	.1	5211
21-23	34.3	42.4	16.5	6.8		23.3	.2	1896
ALL HOURS	22.0	47.1	21.4	9.5	.0	30.9	.1	39015

PPPPPPP	AAAAA	RRRRRRR	TTTTTTTTT	EEEEEEEEEE
PPPPPPP	AAAAAAA	RRRRRRRR	TTTTTTTTT	EEEEEEEEEE
PP PP	AA AA	RR RR	TT	EE
PP PP	AA AA	RR RR	TT	EE
PPPPPPP	AA AA	RRRRRRR	TT	EEEEEE
PPPPPPP	AAAAAAAAA	RRRRRRR	TT	EEEEEE
PP	AAAAAAAAA	RR RR	TT	EE
PP	AA AA	RR RR	TT	EE
PP	AA AA	RR RR	TT	EEEEEEEEEE
PP	AA AA	RR RR	TT	EEEEEEEEEE

PART E

TEMPERATURE AND RELATIVE HUMIDITY SUMMARIES

TEMPERATURE--CUMULATIVE PERCENT OCCURRENCE FREQUENCY (POF).

THESE TABLES ARE CREATED FROM SUMMARY OF DAY DATA AND GIVE CUMULATIVE POF FOR MAXIMUM, MINIMUM, AND MEAN TEMPERATURES, RESPECTIVELY. DATA IS SUMMARIZED BY MONTH FOR ALL YEARS COMBINED. TOTALS ARE GIVEN FOR THE WHOLE YEAR. DATA IS DISPLAYED USING 5-DEGREE FAHRENHEIT INCREMENTS (GE 0, GE 5, GE 10, ETC).. THERE IS ONE SPECIAL THRESHOLD FOR "GE 33" DEGREES. MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS ARE GIVEN.

NOTE 1. BEGINNING IN JANUARY 1946, DAILY MAXIMUM AND MINIMUM TEMPERATURES CAME ROUTINELY FROM HOURLY OBSERVATIONS ON AWS FORMS 10/10A OR FROM AUTOMATED DATA COLLECTION FROM ALL USAF-OPERATED STATIONS. REFER TO THE "STATION HISTORY" PAGE FOR DETAILED INFORMATION ON REPORTING PRACTICES.

MONTHLY TEMPERATURES.

ALSO FROM SUMMARY OF DAY DATA, THE TABLES GIVE MONTHLY MAXIMUM AND MINIMUM TEMPERATURES BY MONTH AND BY YEAR. MONTHLY RECORD TEMPERATURES (MAX AND MIN) ARE GIVEN, ALONG WITH TOTAL OBSERVATIONS. AN ASTERISK (*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF THE DATA ARE AVAILABLE. AN ASTERISK ALSO DENOTES A YEAR(S) WITH ONE OR MORE MISSING AND/OR INCOMPLETE MONTHS.

MEAN MONTHLY TEMPERATURE.

ALSO FROM SUMMARY OF DAY DATA, GIVES MONTHLY MEAN TEMPERATURE BY MONTH, FOR ALL MONTHS, AND FOR ALL YEARS. AN ASTERISK (*) INDICATES A VALUE FOR A MONTH FOR WHICH LESS THAN 90% OF THE DATA ARE AVAILABLE. AN ASTERISK ALSO DENOTES A YEAR(S) WITH ONE OR MORE MISSING AND/OR INCOMPLETE MONTHS.

DRY BULB, WET BULB, AND DEW POINT TEMPERATURES.

THESE TABLES ARE CREATED FROM HOURLY OBSERVATIONS--DATA IS SUMMARIZED:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS ARE GIVEN. THE MEAN NUMBER OF HOURS WITH TEMPERATURES FOR VARIOUS THRESHOLDS ALSO APPEAR AS SPECIFIED IN EACH SUMMARY AND IN ACCORDANCE WITH AFM 88-29, "ENGINEERING WEATHER DATA," AND AWSP 105-56, "METEOROLOGICAL TECHNIQUES."

NOTE 1. WINTER WET BULB AND DEW POINT MEAN TEMPERATURES FOR VERY COLD STATIONS MUST BE USED WITH CAUTION. WHEN THE DRY BULB TEMPERATURE IS BELOW -35 DEGREES F, WET BULB TEMPERATURES ARE NOT REPORTED (FMH-1B). AS A RESULT, WINTER MEAN DEW POINTS (AND MORE FREQUENTLY, WINTER MEAN WET BULB TEMPERATURES) ARE ACTUALLY LOWER THAN SHOWN IN THE TABLES. IN SOME HOUR GROUPS, IN FACT, MEAN WET BULB TEMPERATURES MAY ACTUALLY BE SHOWN AS EXCEEDING THE MEAN DRY BULB TEMPERATURES.

SPECIAL CAVEAT: DURING PART TIME PERIODS, THESE SUMMARIES REPRESENT THE "HIGH" AND "LOW" TEMPERATURES RECORDED AND NOT NECESSARILY THE ACTUAL MAXIMUM AND MINIMUM VALUES. THESE SUMMARIES ARE INFLUENCED BY THE ABSENCE OF NIGHTTIME TEMPERATURE READINGS. THEREFORE, CERTAIN SUMMARIES MAY DEPICT A SLIGHT "WARM" BIAS.

TEMPERATURE CONVERSIONS: $F = 1.8C + 32$

$C = K - 273.0$ (BEFORE 5 APRIL 77)

$C = K - 273.2$ (SINCE 5 APRIL 77)

RELATIVE HUMIDITY--CUMULATIVE PERCENT OCCURRENCE FREQUENCY (POF).

CREATED FROM HOURLY OBSERVATIONS, THESE TABLES GIVE POF OF RELATIVE HUMIDITY FOR 10% INCREMENTS. MEANS AND TOTAL OBSERVATION COUNTS ARE ALSO PROVIDED. THE DATA IS SUMMARIZED AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MAXIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

TEMP (DEG-F)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
GE 120							.1						.0
GE 115					.1	4.0	2.9	.7	.4				.7
GE 110					2.0	20.8	30.2	17.1	7.9				6.5
GE 105				.5	9.4	49.3	72.7	58.7	33.2	.7			18.6
GE 100				5.7	31.4	75.9	92.0	86.8	61.7	11.0			30.2
GE 95			1.3	17.2	57.8	89.8	97.6	96.3	83.4	33.1	.1		39.5
GE 90		.9	7.1	39.0	75.3	97.6	99.1	99.1	93.4	59.0	3.8		47.7
GE 85	.2	5.2	25.0	61.3	87.4	99.8	99.8	99.8	96.9	76.9	18.3	.3	55.8
GE 80	3.3	17.9	45.7	79.1	95.2	100.0	100.0	99.9	98.9	88.4	39.6	2.8	64.2
GE 75	17.0	40.3	65.8	88.7	98.6			99.9	99.8	95.1	60.1	16.9	73.5
GE 70	39.5	60.7	81.4	96.4	99.9			100.0	100.0	98.1	80.9	41.6	83.2
GE 65	63.9	81.5	93.3	99.3	100.0					99.4	92.4	66.6	91.4
GE 60	83.2	93.2	98.9	100.0						99.8	98.2	86.3	96.6
GE 55	93.7	97.4	100.0							100.0	99.5	95.6	98.9
GE 50	98.2	99.5									99.9	99.3	99.7
GE 45	99.9	99.9									100.0	99.7	100.0
GE 40	100.0	100.0										100.0	100.0
MEAN	66.9	71.7	77.8	86.4	94.8	103.8	106.8	104.9	100.6	90.1	76.5	67.4	87.3
SD	7.64	8.24	8.47	8.66	8.27	6.61	5.05	5.18	6.95	8.41	8.04	7.17	16.15
TOTAL OBS	879	812	913	861	882	833	873	881	849	878	873	882	10416

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MINIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTHS: ALL HOURS: ALL

TEMP (DEG-F)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
GE 105								.1					.0
GE 100						.1	.1	.2					.0
GE 95						.1	.8	.6	.2				.1
GE 90					.1	.5	2.4	1.8	.6	.1			.5
GE 85				.2	.6	3.4	20.0	11.5	3.1	.2			3.3
GE 80				.2	1.5	15.9	58.2	47.4	16.0	.3			11.6
GE 75			.1	.8	5.6	33.0	86.6	83.4	39.5	1.3			20.8
GE 70		.1	.2	2.4	16.8	57.6	98.2	96.0	66.7	8.7			28.8
GE 65	.1	.2	.5	9.8	37.6	80.7	99.8	99.7	87.0	28.2	1.3		36.9
GE 60	.5	1.2	3.0	27.6	66.2	94.8	100.0	99.9	96.3	55.1	5.3	.1	45.6
GE 55	2.5	4.6	14.6	52.3	86.5	99.5		100.0	99.1	77.0	18.0	2.5	54.6
GE 50	9.0	20.0	39.9	76.9	96.5	100.0			100.0	89.2	41.4	8.7	65.0
GE 45	22.6	40.9	69.2	92.6	99.5					96.9	66.2	24.5	76.0
GE 40	48.8	68.1	88.1	99.3	100.0					99.5	84.4	53.7	86.8
GE 35	74.7	86.7	97.5	100.0						99.8	95.3	83.4	94.8
GE 33	84.0	92.4	98.6							99.8	97.8	89.3	96.8
GE 30	91.7	96.7	99.5							100.0	99.7	94.8	98.5
GE 25	97.6	99.8	100.0								100.0	99.1	99.7
GE 20	99.9	100.0										100.0	100.0
GE 15	100.0												100.0
.....													
MEAN	39.4	43.0	47.6	55.0	62.5	71.3	80.3	79.0	72.3	59.8	47.6	40.4	58.1
SD	7.32	7.36	6.74	7.34	7.39	7.42	5.16	5.18	7.03	7.68	7.57	6.53	15.89
.....													
TOTAL OBS	879	812	913	861	882	831	873	881	849	878	873	882	10414

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF MEAN TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

TEMP (DEG-F)	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
GE 105							.1	.2					.0
GE 100						1.6	6.5	3.0	.7				1.0
GE 95					.9	16.4	46.6	30.6	8.0				8.9
GE 90				.3	5.7	42.0	86.7	75.8	36.6	.5			20.6
GE 85				1.7	22.1	72.0	97.5	94.9	64.2	7.6			29.8
GE 80			.2	11.8	50.3	87.8	99.9	99.5	87.0	29.4	.1		38.6
GE 75	.1	.6	3.2	29.5	72.4	98.1	100.0	99.9	96.7	59.2	2.2		46.6
GE 70	.3	3.0	16.0	58.3	89.2	99.9		100.0	99.6	78.0	14.3	.1	54.8
GE 65	2.3	15.3	42.8	81.1	97.3	100.0			100.0	92.1	41.9	2.2	64.5
GE 60	17.0	40.4	69.3	94.0	99.8					97.4	67.4	16.1	75.1
GE 55	45.8	70.2	89.7	100.0	100.0					99.2	86.5	49.5	86.7
GE 50	74.3	87.8	98.2							99.9	95.5	80.2	94.7
GE 45	90.4	96.4	99.9							100.0	99.2	94.6	98.4
GE 40	97.8	99.8	100.0								100.0	99.1	99.7
GE 35	99.8	100.0										100.0	100.0
GE 33	99.9												100.0
GE 30	100.0												100.0
MEAN	53.4	57.6	62.9	70.9	78.9	87.8	93.8	92.2	86.7	75.2	62.3	54.1	72.9
SD	6.44	6.73	6.52	7.06	7.16	6.39	4.08	4.32	6.08	7.17	6.87	5.63	15.59
TOTAL OBS	879	812	913	861	882	831	873	881	849	878	873	882	10414

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

MONTHLY MAXIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111, 8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
48											84	78	84*
49	66	82	87	105	109	114	116	115	113	100	93	83	116
50	80	85	94	102	104	117	115	117	118	107	89	86	118
51	84	88	89	97	115	112	115	112	108	104	82	76	115
52	75	79	85	98	106	114	115	113	115	104	89	80	115
53	82	82	96	101	102	116	116	114	110	104	91	77	116
54	83	89	92	103	102	114	117	113	110	104	88	79	117
55	78	82	90	95	106	116	114	107	115	104	89	85	116
56	81	80	97	95	109	115	115	114	111	101	87	78	115
57	75	89	91	97	104	115	118	112	110	105	80	78	118
58	77	83	84	104	114	115	121	114	112	98	90	85	121
59	80	80	89	102	101	115	114	111	112	102	86	83	115
60	77	81	94	99	111	118	116	114	110	101	90	75	118
61	77	84	89	102	103	116	115	112	104	100	81	81	116
62	78	90	90	103	104	115	113	115	111	101	91	79	115
63	79	92	91	97	108	110	115	110	110	107	88	77	115
64	75	77	91	100	105	115	114	111	107	103	89	75	115
65	80	85	88	102	104	109	114	113	106	104	95	82	114
66	75	76	96	95	104	113	112	111	108	95	91	82	113
67	81	85	94	90	108	111	113	112	101	99	93	70	113
68	78	87	92	99	109	117	111	107	109	98	85	81	117
69	80	79	96	97	109	111	115	116	112	102	86	78	116
70	81	87	87	93	112	116	113	112*	110	94	87	79	116*
71	87	87	98	98	100	111	114	108	112	97	90		114*
82							114*	116	112*	96*	83*	72*	116*
83	79*	80	87	89*	112*	108*	114*	110*	108*	95*	87*	73*	114*
84	78*	78	88	102*	111*	111*	113*	112*	107*	91*	85*	73*	113*
85	71*	79*	86	102*	102*	114*	115*	114*	101*	97*	86*	73*	115*
86	82*	92*	98	96*	107*	112*	114*	112*	112*	94*	84*	77*	114*
87	80*	83*	88	101*	101*	111*	113*	111*	108*	105*	86*	79*	113*
88	78*	85*	96	102*	108*	114*	112*	112*	108*	107*	94*	80*	114*
89	78*	88*	94	105*	110*								110*

MONTHLY MAXIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

MONTHLY MINIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
48											29	27	27*
49	18	25	36	40	49	56	72	65	68	37	41	26	18
50	20	30	33	43	48	54	72	71	56	55	36	35	20
51	27	32	29	42	46	56	70	68	66	46	36	27	27
52	25	30	34	49	51	61	69	70	57	53	33	31	25
53	33	26	36	39	45	58	73	68	59	44	30	27	26
54	25	35	32	47	49	58	71	70	66	42	40	20	20
55	29	24	29	39	48	55	65	63	59	45	32	33	24
56	33	25	32	42	56	67	67	67	67	40	28	25	25
57	35	33	42	46	52	63	74	64	61	50	32	30	30
58	30	31	33	41	57	64	73	74	58	51	33	29	29
59	29	32	37	49	50	63	77	74	60	47	37	32	29
60	26	30	40	43	52	68	73	71	60	48	35	22	22
61	30	36	41	46	54	61	71	69	61	42	34	29	29
62	22	28	33	49	51	56	71	70	65	52	36	34	22
63	21	37	36	43	54	58	71	72	64	56	40	28	21
64	20	25	30	40	45	60	75	69	57	49	31	30	20
65	32	28	31	42	43	53	70	67	50	48	37	33	28
66	29	30	28	45	54	59	70	70	63	41	34	22	22
67	20	32	35	43	41	57	73	74	60	43	42	30	20
68	30	39	39	41	49	57	61	57	52	46	32	24	24
69	28	30	34	43	48	60	64	74	61	42	39	30	28
70	24	32	37	37	46	55	73	74*	50	40	38	36	24*
71	20	28	25	41	48	54	69	68	53	31	34		20*
82							65*	77	58*	44*	42*	33*	33*
83	31*	37	40	39*	49*	59*	72*	72*	66*	58*	32*	35*	31*
84	28*	36	35	48*	58*	68*	75*	72*	66*	47*	31*	35*	28*
85	32*	27*	36	50*	54*	63*	73*	72*	54*	49*	30*	34*	27*
86	39*	31*	43	49*	51*	69*	71*	74*	56*	50*	41*	32*	31*
87	29*	36*	41	47*	55*	70*	68*	73*	64*	59*	39*	28*	28*
88	31*	39*	35	44*	42*	63*	77*	76*	59*	63*	36*	24*	24*
89	29*	31*	41	53*	56*								29*

MONTHLY MINIMUM TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

PERIOD OF RECORD: 4811-7111,8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
LEAST	18	24	25	37	41	53	61	57	50	31	28	20	18
TOTAL OBS	879	812	913	861	882	831	873	881	849	878	873	882	10414

THE LEAST VALUE OF 18 OCCURRED ON 01/04/49

NOTE: *THE VALUE IS B O ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION 'A'
USAFETAC, ASHEVILLE NC

MONTHLY MEAN TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: +07

PERIOD OF RECORD: 4811-7111, 8207-8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
48											56	51	54*
49	45	52	61	73	77	88	93	91	90	70	66	52	72
50	51	60	65	75	78	87	91	93	84	81	66	59	74
51	52	57	62	70	79	86	95	90	88	75	60	52	72
52	51	56	57	69	82	87	93	94	90	80	58	52	72
53	56	55	64	69	72	87	95	93	89	75	64	51	73
54	53	63	61	75	81	86	94	91	89	77	65	54	74
55	49	52	63	68	77	87	89	90	88	79	61	57	72
56	57	52	64	69	80	91	93	92	91	74	59	54	73
57	55	63	65	70	76	91	96	93	88	73	58	56	74
58	54	60	60	70	85	91	96	94	88	78	63	57	75
59	55	56	65	76	77	92	97	91	87	76	64	55	74
60	50	54	67	72	79	93	96	94	89	73	63	52	74
61	56	59	64	72	78	91	94	91	84	73	59	53	73
62	52	58	59	76	77	87	94	96	88	76	66	57	74
63	50	64	62	67	81	84	95	91	89	78	63	54	73
64	49	52	59	68	77	86	94	90	84	78	58	55	71
65	56	57	59	68	74	80	92	91	82	77	65	55	71
66	51	54	64	72	81	87	93	92	86	73	64	55	73
67	53	59	65	65	77	84	93	93	84	76	67	50	72
68	56	63	63	69	77	87	91	87	85	74	62	51	72
69	59	57	60	71	79	83	94	95	88	70	63	56	73
70	54	61	62	66	80	86	95	93*	84	71	63	54	72*
71	54	58	64	69	74	85	94	90	85	69	60		73*
82							94*	94	85*	73*	62*	53*	77*
83	55*	58	63	65*	79*	88*	96*	91*	89*	77*	64*	56*	73*
84	55*	59	65	72*	85*	90*	93*	91*	89*	70*	60*	53*	73*
85	53*	54*	62	76*	82*	92*	94*	93*	81*	73*	59*	54*	72*
86	59*	60*	68	73*	80*	91*	91*	95*	84*	74*	65*	55*	75*
87	54*	59*	63	74*	80*	91*	92*	92*	86*	81*	63*	53*	74*
88	54*	60*	64	73*	82*	91*	96*	94*	86*	81*	65*	55*	75*
89	53*	58*	68	80*	83*								69*

MONTHLY MEAN TEMPERATURES IN FAHRENHEIT
FROM SUMMARY OF DAY DATA

PERIOD OF RECORD: 4811-7111,8207 8905
MONTH: ALL HOURS: ALL

YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANNUAL
MEAN	53.4	57.6	62.9	70.9	78.9	87.8	93.8	92.2	86.7	75.2	62.3	54.1	72.9
TOTAL OBS	879	812	913	861	882	831	873	881	849	878	873	882	10414

NOTE: *THE VALUE IS BASED ON A MONTH WITH LESS THAN 90% OF THE DATA AVAILABLE FOR THE MONTH

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 0	LE 32	GE 65	GE 80	GE 93	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	43.9	6.560	635	0	24	0	0	0	635
09-11	53.9	6.892	709	0	0	45	0	0	709
12-14	63.8	6.510	693	0	0	323	1	0	693
15-17	66.4	6.842	645	0	0	397	10	0	645
18-20	58.1	6.118	424	0	0	65	0	0	424
21-23	50.5	6.170	86	0	0	0	0	0	86
ALL HOURS	57.1	10.436	3192	0	24	830	11	0	3192

MONTH: FEB

00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	47.1	6.933	593	0	14	4	0	0	593
09-11	58.0	8.043	681	0	0	145	2	0	681
12-14	68.0	8.874	663	0	0	451	62	0	663
15-17	70.8	9.342	615	0	0	475	94	0	615
18-20	64.0	8.486	414	0	0	196	16	0	414
21-23	57.4	6.091	113	0	0	16	0	0	113
ALL HOURS	61.4	11.837	3079	0	14	1287	174	0	3079

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL
				LE 0	LE 32	GE 65	GE 80	GE 93	HOURS
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	53.0	6.365	711	0	0	29	0	0	711
09-11	65.5	7.643	812	0	0	420	33	0	812
12-14	73.5	8.549	795	0	0	676	212	6	795
15-17	76.1	8.405	711	0	0	649	249	17	711
18-20	70.7	7.728	482	0	0	377	65	0	482
21-23	63.8	5.554	150	0	0	70	0	0	150
ALL HOURS	67.5	11.179	3661	0	0	2221	559	23	3661

MONTH: APR

00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	62.1	8.310	639	0	0	260	7	0	639
09-11	75.5	9.033	718	0	0	620	260	11	718
12-14	83.0	9.651	708	0	0	682	468	121	708
15-17	85.2	10.333	666	0	0	643	482	182	666
18-20	80.5	9.659	470	0	0	436	276	44	470
21-23	72.8	8.091	179	0	0	149	39	0	179
ALL HOURS	77.0	12.393	3380	0	0	2790	1532	358	3380

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 0	LE 32	GE 65	GE 80	GE 93	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	71.1	8.714	645	0	0	489	121	1	645
09-11	84.3	8.404	702	0	0	694	512	117	702
12-14	91.3	8.328	691	0	0	691	623	329	691
15-17	93.4	8.226	623	0	0	623	585	359	623
18-20	88.4	8.490	470	0	0	468	399	152	470
21-23	80.0	7.304	241	0	0	234	124	11	241
ALL HOURS	85.2	11.451	3372	0	0	3199	2364	969	3372

MONTH: JUN

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 0	LE 32	GE 65	GE 80	GE 93	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	80.3	7.354	651	0	0	641	364	25	651
09-11	93.6	6.052	710	0	0	710	698	424	710
12-14	101.1	5.703	682	0	0	682	682	625	682
15-17	103.7	5.661	623	0	0	623	623	599	623
18-20	98.5	6.584	488	0	0	488	486	401	488
21-23	89.2	5.798	281	0	0	281	263	92	281
ALL HOURS	94.8	10.319	3435	0	0	3425	3116	2166	3435

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 0	LE 32	GE 65	GE 80	GE 93	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	85.4	5.636	623	0	0	623	528	64	623
09-11	95.6	5.613	665	0	0	665	658	504	665
12-14	102.1	5.981	656	0	0	656	655	611	656
15-17	105.0	5.760	620	0	0	620	618	598	620
18-20	101.3	6.053	427	0	0	427	425	395	427
21-23	94.8	4.286	210	0	0	210	210	155	210
ALL HOURS	97.5	8.857	3201	0	0	3201	3094	2327	3201

MONTH: AUG

00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	83.5	5.527	664	0	0	664	502	26	664
09-11	94.1	5.283	733	0	0	733	730	473	733
12-14	100.8	5.643	704	0	0	704	701	639	704
15-17	102.5	6.381	655	0	0	655	651	601	655
18-20	97.7	7.269	485	0	0	485	477	376	485
21-23	91.4	5.891	224	0	0	224	214	112	224
ALL HOURS	95.3	8.985	3465	0	0	3465	3275	2227	3465

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 0	LE 32	GE 65	GE 80	GE 93	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	76.3	7.240	605	0	0	578	212	3	605
09-11	88.5	7.444	682	0	0	682	596	229	682
12-14	96.1	7.764	652	0	0	652	624	486	652
15-17	97.9	8.113	599	0	0	599	577	475	599
18-20	92.1	7.751	403	0	0	403	373	206	403
21-23	85.6	5.770	150	0	0	150	135	21	150
ALL HOURS	89.9	10.752	3091	0	0	3064	2517	1420	3091

MONTH: OCT

00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	63.5	7.663	649	0	0	312	6	0	649
09-11	77.2	8.079	701	0	0	663	283	26	701
12-14	85.8	8.153	694	0	0	691	546	121	694
15-17	87.0	8.394	653	0	0	650	534	150	653
18-20	78.7	8.308	448	0	0	426	215	20	448
21-23	72.8	7.080	135	0	0	121	27	0	135
ALL HOURS	78.3	11.715	3280	0	0	2863	1611	317	3280

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 0	LE 32	GE 65	GE 80	GE 93	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	50.9	8.073	579	0	5	28	0	0	579
09-11	63.6	8.549	662	0	0	314	19	0	662
12-14	73.0	8.415	640	0	0	530	157	3	640
15-17	74.6	8.556	575	0	0	496	184	6	575
18-20	65.3	8.647	371	0	1	207	12	0	371
21-23	61.2	6.422	59	0	0	20	0	0	59
ALL HOURS	65.5	11.973	2886	0	6	1595	372	9	2886

MONTH: DEC

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 0	LE 32	GE 65	GE 80	GE 93	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	43.9	6.160	622	0	20	0	0	0	622
09-11	54.0	6.856	696	0	1	42	0	0	696
12-14	64.0	7.145	660	0	0	324	5	0	660
15-17	66.4	7.422	594	0	0	362	14	0	594
18-20	57.0	6.186	329	0	0	37	0	0	329
21-23	51.7	6.247	67	0	0	0	0	0	67
ALL HOURS	56.8	10.669	2968	0	21	765	19	0	2968

OPERATING LOCATION "A".
USAFETAC, ASHEVILLE NC

DRY BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: ALL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 0	LE 32	GE 65	GE 80	GE 93	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	63.6	16.540	7616	0	63	3628	1740	119	7616
09-11	75.3	16.949	8471	0	1	5733	3791	1784	8471
12-14	83.5	16.022	8238	0	0	7062	4736	2941	8238
15-17	85.8	16.068	7579	0	0	6792	4621	2987	7579
18-20	80.3	17.094	5211	0	1	4015	2744	1594	5211
21-23	78.0	15.128	1895	0	0	1475	1012	391	1895
ALL HOURS	77.6	18.199	39010	0	65	28705	18644	9816	39010

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN LE 32	NUMBER OF HOURS WITH TEMPERATURES GE 50	GE 67	GE 73	GE 80	DEG F	TOTAL HOURS
00-02	.0	.000	0	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0	0
06-08	39.9	6.166	635	75	41	0	0	0	0	635
09-11	45.9	5.563	709	5	189	0	0	0	0	709
12-14	50.8	4.644	693	0	456	0	0	0	0	693
15-17	51.7	4.438	645	0	463	0	0	0	0	645
18-20	48.0	4.637	424	0	159	0	0	0	0	424
21-23	43.5	5.524	86	2	9	0	0	0	0	86
ALL HOURS	47.2	6.721	3192	82	1317	0	0	0	0	3192

MONTH: FEB

00-02	.0	.000	0	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0	0
06-08	41.8	6.631	593	63	66	0	0	0	0	593
09-11	47.9	6.328	681	9	292	0	0	0	0	681
12-14	52.1	5.695	663	0	458	0	0	0	0	663
15-17	53.0	5.328	615	0	449	0	0	0	0	615
18-20	50.8	5.277	414	0	253	0	0	0	0	414
21-23	47.4	5.488	113	1	44	0	0	0	0	113
ALL HOURS	49.0	7.149	3079	73	1562	0	0	0	0	3079

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240 STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 32	GE 50	GE 67	GE 73	GE 80	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	45.3	5.531	711	13	150	0	0	0	711
09-11	51.6	4.860	812	0	548	0	0	0	812
12-14	54.6	4.394	795	0	683	0	0	0	795
15-17	55.1	4.130	711	0	642	1	0	0	711
18-20	53.1	3.976	482	0	400	0	0	0	482
21-23	50.4	3.630	150	0	82	0	0	0	150
ALL HOURS	51.8	5.782	3661	13	2505	1	0	0	3661

MONTH: APR

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 32	GE 50	GE 67	GE 73	GE 80	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	48.9	5.454	639	0	303	0	0	0	639
09-11	55.3	4.591	718	0	626	0	0	0	718
12-14	57.9	4.463	708	0	673	5	0	0	708
15-17	58.4	4.558	666	0	638	4	0	0	666
18-20	56.5	4.472	470	0	428	0	0	0	470
21-23	53.5	4.190	179	0	146	0	0	0	179
ALL HOURS	55.3	5.777	3380	0	2814	9	0	0	3380

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 32	GE 50	GE 67	GE 73	GE 80	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	53.8	5.471	644	0	502	5	0	0	644
09-11	59.8	4.329	702	0	694	42	3	0	702
12-14	62.1	4.303	691	0	690	107	9	0	691
15-17	62.4	4.150	623	0	623	110	8	0	623
18-20	60.2	4.233	470	0	470	30	3	0	470
21-23	56.9	4.194	241	0	232	0	0	0	241
ALL HOURS	59.5	5.521	3371	0	3211	294	23	0	3371

MONTH: JUN

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 32	GE 50	GE 67	GE 73	GE 80	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	58.8	5.478	651	0	629	59	5	0	651
09-11	64.4	4.141	710	0	710	210	28	0	710
12-14	66.9	3.861	682	0	682	349	62	0	682
15-17	67.5	3.822	623	0	623	374	66	0	623
18-20	65.3	4.195	488	0	488	189	23	0	488
21-23	61.5	4.558	281	0	281	39	3	0	281
ALL HOURS	64.3	5.413	3435	0	3413	1220	187	0	3435

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 32	GE 50	GE 67	GE 73	GE 80	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	68.3	5.622	623	0	621	440	148	0	623
09-11	71.8	3.806	665	0	665	585	368	0	665
12-14	73.5	3.168	656	0	656	633	465	1	656
15-17	73.7	3.018	620	0	620	610	429	2	620
18-20	72.3	3.298	426	0	426	399	246	0	426
21-23	69.8	4.514	209	0	209	158	70	0	209
ALL HOURS	71.8	4.405	3199	0	3197	2825	1726	3	3199

MONTH: AUG

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 32	GE 50	GE 67	GE 73	GE 80	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	69.7	4.713	664	0	664	529	194	0	664
09-11	72.6	3.430	733	0	733	685	420	2	733
12-14	74.2	3.099	704	0	704	684	517	4	704
15-17	74.2	3.043	655	0	655	632	491	13	655
18-20	72.7	3.542	485	0	485	447	288	5	485
21-23	70.5	4.260	224	0	224	190	74	0	224
ALL HOURS	72.5	4.106	3465	0	3465	3167	1984	29	3465

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 32	GE 50	GE 67	GE 73	GE 80	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	62.4	6.562	605	0	590	177	30	0	605
09-11	67.1	5.228	682	0	682	384	103	0	682
12-14	69.3	4.583	652	0	652	463	164	0	652
15-17	69.5	4.525	598	0	598	446	155	0	598
18-20	67.2	4.559	403	0	403	230	56	0	403
21-23	64.4	4.781	150	0	150	55	2	0	150
ALL HOURS	67.0	5.791	3090	0	3075	1755	510	0	3090

MONTH: OCT

00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	53.0	7.273	649	0	433	11	0	0	649
09-11	59.6	6.079	701	0	650	78	2	0	701
12-14	62.6	5.230	694	0	692	176	6	0	694
15-17	62.3	5.092	652	0	648	148	2	0	652
18-20	58.9	5.784	448	0	414	30	0	0	448
21-23	55.9	5.926	135	0	112	3	0	0	135
ALL HOURS	59.2	6.899	3279	0	2949	446	10	0	3279

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 32	GE 50	GE 67	GE 73	GE 80	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	43.7	7.517	579	38	132	0	0	0	579
09-11	50.7	6.532	662	0	369	0	0	0	662
12-14	54.8	5.581	640	0	519	3	0	0	640
15-17	55.0	5.489	575	0	477	4	0	0	575
18-20	51.1	6.364	370	0	214	0	0	0	370
21-23	48.9	6.626	58	0	23	0	0	0	58
ALL HOURS	51.1	7.573	2884	38	1734	7	0	0	2884

MONTH: DEC

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 32	GE 50	GE 67	GE 73	GE 80	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	39.6	5.663	622	54	32	0	0	0	622
09-11	46.1	5.094	696	6	186	0	0	0	696
12-14	51.2	4.341	660	0	465	0	0	0	660
15-17	52.0	4.292	594	0	445	0	0	0	594
18-20	47.3	4.387	329	0	113	0	0	0	329
21-23	43.2	4.829	67	2	6	0	0	0	67
ALL HOURS	47.1	6.639	2968	62	1247	0	0	0	2968

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

WET BULB TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: ALL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F					TOTAL HOURS
				LE 32	GE 50	GE 67	GE 73	GE 80	
00-02	.0	.000	0	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0	0
06-08	52.2	11.902	7615	243	4163	1221	377	0	7615
09-11	57.7	10.533	8471	20	6344	1984	924	2	8471
12-14	60.8	9.338	8238	0	7330	2420	1223	10	8238
15-17	61.2	9.101	7577	0	6881	2329	1151	15	7577
18-20	59.1	9.735	5209	0	4253	1325	616	5	5209
21-23	58.4	9.717	1893	5	1518	445	149	0	1893
ALL HOURS	58.2	10.671	39003	262	50489	9724	4440	32	39003

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
				LE 27	GE 37	LE 55	GE 65	
00-02	.0	.000	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0
06-08	34.7	8.051	635	129	259	634	0	635
09-11	36.9	8.216	709	92	352	707	0	709
12-14	37.4	8.853	693	98	374	691	0	693
15-17	36.6	8.795	645	109	328	644	0	645
18-20	37.2	8.382	424	60	218	421	0	424
21-23	35.0	8.048	86	15	33	85	0	86
ALL HOURS	36.5	8.552	3192	503	1564	3182	0	3192

MONTH: FEB

00-02	.0	.000	0	0	0	0	0	663
03-05	.0	.000	0	0	0	0	0	663
06-08	34.9	9.595	593	141	301	588	0	663
09-11	36.6	10.256	681	155	387	672	0	663
12-14	35.9	10.368	663	159	351	656	0	663
15-17	35.2	9.804	615	149	317	612	0	663
18-20	37.1	9.250	414	72	237	409	0	663
21-23	36.1	10.284	113	26	59	113	0	663
ALL HOURS	35.9	9.983	3079	702	1652	3050	0	3079

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
				LE 27	GE 37	LE 55	GE 65	
00-02	.0	.000	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0
06-08	36.2	10.020	711	143	401	706	0	711
09-11	37.3	10.148	812	164	487	805	0	812
12-14	36.1	10.001	795	175	433	787	0	795
15-17	34.5	9.792	711	174	317	709	0	711
18-20	35.3	9.821	482	100	219	478	0	482
21-23	36.1	9.351	150	26	74	148	0	150
ALL HOURS	36.0	10.014	3661	782	1931	3633	0	3661

MONTH: APR

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
				LE 27	GE 37	LE 55	GE 65	
00-02	.0	.000	0	0	0	0	0	708
03-05	.0	.000	0	0	0	0	0	708
06-08	34.8	7.948	639	104	238	636	0	708
09-11	36.6	7.813	718	111	354	715	0	708
12-14	35.4	8.209	708	124	310	707	0	708
15-17	34.1	8.301	666	143	249	665	0	708
18-20	33.9	7.915	470	105	165	468	0	708
21-23	34.7	6.971	179	30	70	177	0	708
ALL HOURS	35.0	8.068	3380	575	1372	3368	0	3380

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
				LE 27	GE 37	LE 55	GE 65	
00-02	.0	.000	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0
06-08	37.3	8.589	644	79	314	634	0	644
09-11	39.6	7.847	702	29	439	682	0	702
12-14	38.6	7.892	691	47	399	681	0	691
15-17	36.8	7.957	623	73	304	615	0	623
18-20	36.1	7.702	470	58	217	467	0	470
21-23	35.7	7.618	241	33	104	239	0	241
ALL HOURS	37.7	8.135	3371	319	1777	3318	0	3371

MONTH: JUN

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
				LE 27	GE 37	LE 55	GE 65	
00-02	.0	.000	0	0	0	0	0	682
03-05	.0	.000	0	0	0	0	0	682
06-08	40.6	10.164	651	67	432	597	6	682
09-11	42.5	9.235	710	37	513	648	6	682
12-14	41.3	9.177	682	44	466	646	0	682
15-17	40.0	9.599	623	57	392	595	2	682
18-20	39.3	9.658	488	58	295	465	3	682
21-23	38.8	9.917	281	37	167	265	2	682
ALL HOURS	40.7	9.679	3435	300	2265	3216	19	3435

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
				LE 27	GE 37	LE 55	GE 65	
00-02	.0	.000	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0
06-08	57.9	11.139	623	7	591	204	220	623
09-11	58.4	9.669	665	4	647	201	204	665
12-14	57.3	9.272	656	3	648	215	169	656
15-17	55.8	9.315	620	3	605	244	108	620
18-20	55.1	9.913	426	6	401	166	66	426
21-23	54.4	11.096	209	5	194	87	37	209
ALL HOURS	56.9	10.067	3199	25	5086	1117	804	3199

MONTH: AUG

00-02	.0	.000	0	0	0	0	0	704
03-05	.0	.000	0	0	0	0	0	704
06-08	62.0	8.133	664	0	662	133	282	704
09-11	61.3	7.736	733	0	728	150	266	704
12-14	59.9	7.887	704	0	699	171	204	704
15-17	58.8	8.391	655	1	640	195	163	704
18-20	58.7	8.702	485	4	475	150	130	704
21-23	58.7	8.960	224	2	220	71	57	704
ALL HOURS	60.1	8.324	3465	7	3424	870	1102	3465

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
				LE 27	GE 37	LE 55	GE 65	
00-02	.0	.000	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0
06-08	52.5	10.326	605	2	554	351	73	605
09-11	53.6	9.359	682	0	651	375	92	682
12-14	52.6	8.973	652	0	622	396	71	652
15-17	51.4	9.174	598	1	570	388	50	598
18-20	51.1	9.048	403	0	381	272	30	403
21-23	49.7	8.907	150	0	137	108	6	150
ALL HOURS	52.2	9.445	3090	3	2915	1890	322	3090

MONTH: OCT

00-02	.0	.000	0	0	0	0	0	694
03-05	.0	.000	0	0	0	0	0	694
06-08	43.1	11.114	649	57	438	567	6	694
09-11	45.7	10.573	701	40	549	583	10	694
12-14	45.0	10.279	694	36	544	584	6	694
15-17	43.3	10.249	652	52	480	576	4	694
18-20	42.4	10.233	448	41	308	405	5	694
21-23	40.8	9.975	135	12	84	129	0	694
ALL HOURS	43.9	10.591	3279	238	2403	2844	31	3279

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
				LE 27	GE 37	LE 55	GE 65	
00-02	.0	.000	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0
06-08	34.7	11.180	579	175	236	563	0	579
09-11	37.1	10.899	662	145	329	630	0	662
12-14	37.4	10.786	640	128	324	611	0	640
15-17	36.2	10.632	575	145	263	555	0	575
18-20	36.3	10.683	370	85	166	354	0	370
21-23	34.5	12.863	58	21	21	54	0	58
ALL HOURS	36.3	10.946	2884	697	1339	2767	0	2884

MONTH: DEC

00-02	.0	.000	0	0	0	0	0	660
03-05	.0	.000	0	0	0	0	0	660
06-08	33.8	8.297	622	132	242	622	0	660
09-11	37.2	8.177	696	87	378	694	0	660
12-14	38.3	8.521	660	67	375	654	0	660
15-17	37.5	8.740	594	83	299	587	0	660
18-20	36.3	8.793	329	62	160	328	0	660
21-23	32.3	9.276	67	28	24	67	0	660
ALL HOURS	36.6	8.675	2968	459	1478	2952	0	2968

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

DEW POINT TEMPERATURE SUMMARY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: ALL

HOURS LST	MEAN	STANDARD DEVIATION	TOTAL OBS	MEAN NUMBER OF HOURS WITH TEMPERATURES DEG F				TOTAL HOURS
				LE 27	GE 37	LE 55	GE 65	
00-02	.0	.000	0	0	0	0	0	0
03-05	.0	.000	0	0	0	0	0	0
06-08	41.9	13.588	7615	1036	4668	6235	587	7615
09-11	43.5	12.714	8471	824	5814	6862	578	8471
12-14	42.8	12.494	8238	881	5553	6799	450	8238
15-17	41.6	12.512	7577	988	4764	6385	327	7577
18-20	41.7	12.395	5209	649	3240	4383	234	5209
21-23	42.2	12.881	1893	235	1187	1543	102	1893
ALL HOURS	42.4	12.791	39003	4613	25226	32207	2278	39003

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO										TOTAL OBS
	10%	20%	30%	40%	50%	60%	70%	80%	90%	MEAN	
00-02										.0	0
03-05										.0	0
06-08	100.0	100.0	99.4	96.5	88.5	75.4	57.2	35.1	13.7	71.0	635
09-11	100.0	99.7	93.2	79.7	60.5	38.9	20.5	8.2	1.6	54.7	709
12-14	100.0	93.5	70.9	45.9	25.5	13.7	5.3	2.2	.9	40.1	693
15-17	100.0	87.9	60.0	35.5	17.5	8.5	4.7	2.2	.2	36.0	645
18-20	100.0	98.6	86.1	63.7	43.2	26.7	13.0	7.1	1.4	48.4	424
21-23	100.0	100.0	97.7	84.9	64.0	41.9	19.8	9.3	1.2	56.7	86
ALL HOURS	100.0	95.9	82.0	64.8	47.6	33.0	20.3	10.9	3.5	56.7	3192

MONTH: FEB

00-02										.0	0
03-05										.0	0
06-08	100.0	100.0	98.5	89.4	76.7	53.3	40.1	26.7	10.3	64.4	593
09-11	100.0	95.9	81.6	61.4	43.0	26.1	15.3	8.7	2.5	47.9	681
12-14	99.0	88.4	59.5	29.1	15.2	9.0	4.6	2.7	1.2	33.9	663
15-17	99.2	79.6	42.8	19.3	11.4	6.5	4.0	2.9	1.1	30.2	615
18-20	100.0	88.6	70.3	44.7	26.6	15.7	9.2	5.8	1.9	40.6	414
21-23	100.0	98.2	82.3	64.6	43.4	25.7	14.2	8.0	2.1	47.7	113
ALL HOURS	99.8	87.4	69.3	49.3	35.0	23.3	14.7	9.1	3.5	47.7	3079

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 MAY 89
MONTH: MAR

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO										TOTAL OBS
	10%	20%	30%	40%	50%	60%	70%	80%	90%	MEAN	
00-02										.0	0
03-05										.0	0
06-08	100.0	98.0	88.0	74.4	60.5	44.3	27.1	17.7	3.3	56.1	711
09-11	99.9	84.9	65.3	44.7	27.0	14.0	6.9	3.2	.6	38.9	312
12-14	97.7	67.4	40.4	21.1	10.7	5.2	3.3	1.9	.9	29.1	795
15-17	94.2	57.8	28.4	12.9	6.6	3.2	1.8	1.0	.4	24.9	711
18-20	98.8	69.7	41.3	24.3	14.3	8.7	4.4	2.1	1.0	30.9	482
21-23	100.0	88.0	65.3	40.0	23.3	16.0	8.7	3.3	2.0	39.1	150
ALL HOURS	98.2	76.5	53.5	36.3	24.2	15.3	8.8	5.2	1.4	39.1	3661

MONTH: APR

00-02										.0	0
03-05										.0	0
06-08	100.0	93.9	68.9	40.8	17.7	7.7	4.1	1.6	.5	38.1	639
09-11	98.1	68.9	31.3	12.3	5.0	2.1	.7	.3		26.6	718
12-14	91.0	43.1	13.6	5.1	2.5	1.8	.4	.1		20.2	708
15-17	86.5	31.1	9.9	3.9	3.2	2.4	2.3	.8	.2	18.3	666
18-20	94.5	41.9	13.2	5.7	3.4	2.6	1.9	1.5		20.8	470
21-23	100.0	70.4	21.8	11.2	6.7	5.0	3.4	1.7		26.8	179
ALL HOURS	94.3	57.1	27.5	13.6	6.4	3.4	1.9	.8	.1	26.8	3380

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO									MEAN	TOTAL OBS
	10%	20%	30%	40%	50%	60%	70%	80%	90%		
00-02										.0	0
03-05										.0	0
06-08	100.0	82.0	46.4	23.6	.6	3.4	1.6	.5		31.1	644
09-11	98.0	51.3	21.5	4.4	.9	.1				22.2	702
12-14	89.1	31.1	5.8	.4						17.0	691
15-17	82.3	21.2	2.4	1.0	.6	.2				14.9	623
18-20	91.1	28.9	5.1	1.5	.6	.4				16.9	470
21-23	99.6	48.5	12.4	5.8	2.1					21.5	241
ALL HOURS	92.8	44.1	16.6	6.3	2.0	.8	.3	.1		21.5	3371

MONTH: JUN

00-02										.0	0
03-05										.0	0
06-08	99.2	71.6	30.3	10.6	2.0	.6	.5			25.9	653
09-11	93.7	35.6	8.3	1.0	.3	.1	.1			18.3	710
12-14	80.1	13.8	1.6							13.9	582
15-17	67.7	8.7	.8	.3	.3					12.3	623
18-20	77.7	13.9	2.9	.6	.6	.4				14.1	488
21-23	94.7	27.4	8.2	2.5	1.1					18.1	281
ALL HOURS	85.1	29.5	9.0	2.7	.7	.2	.1			18.1	3435

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO										TOTAL OBS
	10%	20%	30%	40%	50%	60%	70%	80%	90%	MEAN	
00-02										.0	0
03-05										.0	0
06-08	100.0	92.9	74.6	52.8	31.8	15.9	7.9	2.9	1.3	42.5	623
09-11	99.2	79.7	53.1	25.1	11.3	4.4	1.8	.6	.2	32.0	665
12-14	97.9	64.9	30.2	11.0	4.1	1.2	.5			25.4	656
15-17	94.2	55.2	19.4	5.6	1.8	.5	.3	.3		22.1	620
18-20	94.8	63.8	26.8	8.0	3.5	1.4	.5			24.1	425
21-23	96.7	70.3	41.6	15.3	5.3	1.9				28.2	209
ALL HOURS	97.4	71.8	41.8	20.9	10.5	4.7	2.1	.8	.3	28.2	3199

MONTH: AUG

00-02										.0	0
03-05										.0	0
06-08	100.0	99.8	93.1	73.3	46.4	28.0	17.5	6.8	1.8	51.2	664
09-11	100.0	92.2	62.8	33.2	15.7	7.0	1.8			36.0	733
12-14	99.7	78.0	36.8	16.3	5.3	.6	.4	.3		28.2	704
15-17	98.5	69.8	29.9	13.3	4.9	1.7	.8	.3		26.2	655
18-20	98.8	80.0	38.4	23.1	12.2	6.2	3.3	1.0		30.7	485
21-23	99.1	95.5	57.6	30.4	18.3	8.9	6.3	2.7		36.3	224
ALL HOURS	99.4	85.1	53.3	32.1	17.1	8.7	4.8	1.7	.3	36.3	3465

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP

HOURS LST	10%	20%	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO							90%	MEAN	TOTAL OBS
	30%	40%	50%	60%	70%	80%						
00-02										.0		0
03-05										.0		0
06-08	100.0	99.3	86.6	61.7	35.9	16.2	8.3	3.8	.8	45.8		605
09-11	99.9	87.1	51.9	24.2	10.1	3.8	1.8	.9	.6	32.7		682
12-14	99.4	64.4	27.0	8.4	4.6	2.3	1.3	.6		25.3		652
15-17	98.7	52.0	18.2	3.7	4.7	3.7	1.0	.3	.2	23.3		598
18-20	100.0	68.2	30.5	12.4	7.4	4.7	2.2	.7	.2	27.4		403
21-23	100.0	88.7	42.7	21.3	4.0	4.0	1.3			30.6		150
ALL HOURS	99.6	75.5	43.7	23.5	12.3	6.0	2.9	1.2	.4	30.6		3090

MONTH: OCT

00-02										.0		0
03-05										.0		0
06-08	100.0	99.5	90.1	67.0	46.7	27.3	13.6	6.3	2.2	49.6		649
09-11	99.9	89.3	60.5	34.1	14.6	6.0	2.0	.6		35.1		701
12-14	98.3	64.6	33.9	12.5	4.6	1.9	1.2	.9	.6	26.5		694
15-17	97.4	56.6	24.4	8.3	3.1	2.0	1.5	1.1	.5	24.0		652
18-20	99.8	78.8	43.1	15.4	6.5	2.9	2.0	1.1	.7	29.6		448
21-23	100.0	90.4	54.8	25.2	8.9	2.2	1.5	.7		33.2		135
ALL HOURS	99.1	78.2	50.9	28.0	15.2	8.0	4.0	2.0	.7	33.2		3279

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO										TOTAL OBS
	10%	20%	30%	40%	50%	60%	70%	80%	90%	MEAN	
00-02										.0	0
03-05										.0	0
06-08	100.0	99.7	91.0	75.6	57.7	40.8	28.3	15.7	7.8	56.3	579
09-11	100.0	92.9	66.8	44.7	28.1	15.3	8.2	3.8	1.5	40.5	662
12-14	98.4	74.5	42.8	22.7	10.9	5.5	3.0	1.1	.6	30.3	640
15-17	96.7	68.0	34.4	15.0	8.0	4.0	2.1	1.0	.5	27.5	575
18-20	99.5	88.6	62.2	35.7	18.1	10.0	4.6	3.0	.5	36.7	370
21-23	100.0	87.9	63.8	44.8	31.0	17.2	8.6	3.4		39.9	58
ALL HOURS	98.9	84.6	59.2	38.9	25.0	15.3	9.4	4.9	2.2	39.9	2884

MONTH: DEC

00-02										.0	0
03-05										.0	0
06-08	100.0	100.0	98.6	91.0	79.6	70.6	57.6	37.8	18.5	69.8	622
09-11	100.0	99.1	91.1	78.3	61.6	43.7	27.4	13.2	4.5	56.3	696
12-14	100.0	91.7	73.0	49.5	30.0	17.1	7.9	4.5	3.2	42.1	660
15-17	99.8	87.2	61.1	37.5	22.1	13.5	7.1	4.5	2.7	38.0	594
18-20	100.0	98.2	81.5	60.2	43.8	31.9	19.8	11.2	4.3	49.4	329
21-23	100.0	97.0	79.1	65.7	50.7	34.5	26.9	13.4	1.5	51.0	67
ALL HOURS	100.0	95.1	81.3	64.1	48.7	35.8	24.5	14.5	6.7	51.0	2968

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

CUMULATIVE PERCENTAGE FREQUENCY OF OCCURRENCE OF RELATIVE HUMIDITY
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: ALL

HOURS LST	RELATIVE HUMIDITY GREATER THAN OR EQUAL TO									MEAN	TOTAL OBS
	10%	20%	30%	40%	50%	60%	70%	80%	90%		
00-02										.0	0
03-05										.0	0
06-08	99.9	94.6	80.2	62.8	45.7	32.2	21.8	14.0	5.0	50.0	7615
09-11	99.0	81.3	57.1	37.0	23.1	13.4	7.2	3.2	.9	36.7	8471
12-14	95.9	63.8	35.6	18.4	9.4	4.8	2.3	1.2	.6	27.6	8238
15-17	92.9	55.3	27.5	13.3	6.9	3.8	2.1	1.2	.5	24.7	7577
18-20	95.9	66.4	39.7	23.1	14.0	8.5	4.6	2.5	.7	30.0	5209
21-23	98.7	73.0	42.8	25.5	14.8	8.7	4.9	2.3	.4	31.7	1893
ALL HOURS	96.9	72.8	48.3	31.1	19.9	12.5	7.6	4.1	1.5	33.9	39003

PPPPPPPP	AAAAAA	RRRRRRRR	TTTTTTTTT	FFFFFFFFF
PPPPPPPP	AAAAAAA	RRRRRRRR	TTTTTTTTT	FFFFFFFFF
PP PP	AA AA	RR RR	TT	FF
PP PP	AA AA	RR RR	TT	FF
PPPPPPPP	AA AA	RRRRRRRR	TT	FFFFF
PPPPPPPP	AAAAAAAAA	RRRRRRRR	TT	FFFFF
PP	AAAAAAAAA	RR RR	TT	FF
PP	AA AA	RR RR	TT	FF
PP	AA AA	RR RR	TT	FF
PP	AA AA	RR RR	TT	FF

PART F

PRESSURE SUMMARIES

ALL PRESSURE DATA IN PART F IS TAKEN FROM HOURLY OBSERVATIONS. IT IS SUMMARIZED:

- BY EIGHT 3-HOUR STANDARD SYNOPTIC REPORTING TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).

SEA LEVEL PRESSURE.

IN MILLIBARS, TABLES GIVE MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS. THIS SUMMARY IS NOT AVAILABLE FOR METAR REPORTING SITES.

ALTIMETER SETTING.

IN INCHES OF MERCURY (HG), TABLES GIVE MEANS, STANDARD DEVIATIONS, AND TOTAL OBSERVATION COUNTS.

STATION PRESSURE.

IN INCHES OF MERCURY (HG), TABLES GIVE MEANS, STANDARD DEVIATIONS AND TOTAL OBSERVATION COUNTS.

PRESSURE CONVERSIONS ARE: 1 MILLIBAR = 0.02953 INCHES OF MERCURY (HG).

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

SEA LEVEL PRESSURE IN MILLIBARS
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89

HOURS (LST)	STATS	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
0200	MEAN	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
	SD	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
	TOT OBS	0	0	0	0	0	0	0	0	0	0	0	0	0
0500	MEAN	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
	SD	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
	TOT OBS	0	0	0	0	0	0	0	0	0	0	0	0	0
0800	MEAN	1018.6	1016.7	1014.4	1012.6	1010.6	1009.4	1010.8	1010.8	1010.7	1013.4	1016.7	1018.3	1013.6
	SD	4.533	4.474	4.219	3.383	2.820	2.167	2.404	2.545	2.803	3.395	4.183	4.588	4.754
	TOT OBS	228	210	260	224	225	230	214	234	214	227	203	224	2693
1100	MEAN	1019.5	1017.5	1014.8	1012.9	1010.4	1009.1	1010.6	1010.7	1010.9	1013.5	1016.9	1019.0	1013.8
	SD	4.313	4.346	4.148	3.331	2.824	2.222	2.396	2.601	2.810	3.452	4.158	4.540	4.964
	TOT OBS	236	229	272	239	236	233	222	242	227	232	223	231	2822
1400	MEAN	1016.7	1015.0	1012.7	1010.8	1008.4	1007.3	1008.6	1008.7	1008.6	1011.1	1014.5	1016.3	1011.5
	SD	4.246	4.312	4.092	3.342	2.885	2.180	2.413	2.592	2.871	3.402	4.011	4.441	4.732
	TOT OBS	231	216	259	231	225	220	216	229	213	225	209	213	2687
1700	MEAN	1016.1	1013.9	1011.3	1008.9	1006.6	1005.5	1006.4	1006.7	1007.0	1010.2	1013.9	1015.9	1010.2
	SD	4.119	4.359	4.054	3.235	2.888	2.192	2.453	2.739	2.969	3.387	3.847	4.409	5.068
	TOT OBS	204	194	229	212	201	197	199	207	191	208	181	185	2408
2000	MEAN	1017.1	1014.8	1011.9	1009.5	1007.2	1005.9	1006.8	1007.6	1007.9	1011.3	1015.7	1016.8	1010.6
	SD	3.918	4.312	3.785	2.977	2.718	2.206	2.549	2.793	2.840	3.422	3.749	4.427	5.064
	TOT OBS	122	122	142	144	150	154	130	152	121	132	103	86	1558
2300	MEAN	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0
	SD	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
	TOT OBS	0	0	0	0	0	0	0	0	0	0	0	0	0
ALL HOURS	MEAN	1017.7	1015.7	1013.2	1011.1	1008.8	1007.6	1008.8	1009.1	1009.2	1012.0	1015.6	1017.4	1012.1
	SD	4.464	4.574	4.323	3.641	3.225	2.699	3.047	3.109	3.241	3.672	4.220	4.668	5.128
	TOT OBS	1021	971	1162	1050	1037	1034	981	1064	966	1024	919	939	12168

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

ALTIMETER SETTING IN INCHES
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 76 - MAY 89

HOURS (LST)	STATS	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
0200	MEAN	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
	SD	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
	TOT OBS	0	0	0	0	0	0	0	0	0	0	0	0	0
0500	MEAN	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
	SD	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
	TOT OBS	0	0	0	0	0	0	0	0	0	0	0	0	0
0800	MEAN	30.09	30.04	29.98	29.94	29.88	29.86	29.90	29.90	29.89	29.96	30.04	30.08	29.96
	SD	.130	.131	.124	.098	.080	.063	.071	.075	.082	.096	.119	.133	.130
	TOT OBS	228	210	259	224	224	232	215	233	214	227	203	224	2693
1100	MEAN	30.12	30.07	29.99	29.94	29.88	29.85	29.90	29.90	29.90	29.97	30.06	30.11	29.97
	SD	.126	.127	.122	.097	.082	.064	.070	.075	.082	.100	.120	.133	.137
	TOT OBS	236	229	271	239	236	235	222	243	227	231	223	232	2824
1400	MEAN	30.04	29.99	29.93	29.88	29.82	29.79	29.83	29.84	29.83	29.90	29.98	30.03	29.91
	SD	.124	.126	.120	.097	.083	.063	.071	.075	.082	.099	.116	.130	.131
	TOT OBS	231	216	259	230	225	219	216	230	214	225	209	213	2687
1700	MEAN	30.02	29.96	29.89	29.83	29.77	29.74	29.77	29.78	29.78	29.87	29.96	30.02	29.86
	SD	.120	.128	.120	.094	.083	.064	.072	.079	.086	.099	.110	.129	.141
	TOT OBS	204	194	230	212	201	197	199	207	191	208	181	185	2409
2000	MEAN	30.05	29.99	29.91	29.85	29.78	29.75	29.78	29.80	29.81	29.90	30.01	30.04	29.88
	SD	.113	.125	.111	.084	.078	.064	.074	.080	.081	.098	.105	.129	.138
	TOT OBS	122	122	142	144	150	154	130	151	120	132	103	86	1556
2300	MEAN	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
	SD	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
	TOT OBS	0	0	0	0	0	0	0	0	0	0	0	0	0
ALL HOURS	MEAN	30.07	30.02	29.95	29.89	29.83	29.80	29.84	29.85	29.85	29.94	30.01	30.06	29.92
	SD	.129	.133	.127	.106	.094	.080	.090	.090	.094	.107	.121	.136	.142
	TOT OBS	1021	971	1161	1049	1036	1037	982	1064	966	1023	919	940	12169

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

STATION PRESSURE IN INCHES
FROM HOURLY OBSERVATIONS

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89

HOURS (LST)	STATS	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
0200	MEAN	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
	SD	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
	TOT OBS	0	0	0	0	0	0	0	0	0	0	0	0	0
0500	MEAN	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
	SD	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
	TOT OBS	0	0	0	0	0	0	0	0	0	0	0	0	0
0800	MEAN	29.17	29.12	29.06	29.02	28.96	28.94	28.98	28.98	28.97	29.04	29.12	29.16	29.04
	SD	.126	.127	.122	.097	.079	.062	.071	.074	.081	.097	.116	.130	.128
	TOT OBS	228	210	259	224	224	232	215	233	214	227	203	224	2693
1100	MEAN	29.20	29.15	29.07	29.02	28.96	28.93	28.98	28.98	28.98	29.05	29.13	29.18	29.05
	SD	.122	.123	.120	.095	.081	.063	.070	.074	.081	.098	.116	.129	.134
	TOT OBS	236	229	271	239	236	235	222	243	227	231	223	232	2824
1400	MEAN	29.12	29.07	29.01	28.96	28.90	28.88	28.92	28.92	28.91	28.98	29.06	29.11	28.99
	SD	.121	.124	.118	.096	.080	.060	.069	.073	.080	.097	.113	.127	.129
	TOT OBS	231	216	259	230	225	219	216	230	214	225	209	213	2687
1700	MEAN	29.10	29.04	28.97	28.91	28.85	28.83	28.85	28.86	28.87	28.95	29.04	29.10	28.95
	SD	.118	.125	.118	.091	.079	.059	.068	.075	.082	.097	.108	.126	.138
	TOT OBS	204	194	230	212	201	197	199	207	191	208	181	185	2409
2000	MEAN	29.13	29.06	28.99	28.93	28.87	28.84	28.87	28.89	28.89	28.98	29.09	29.12	28.96
	SD	.110	.123	.109	.082	.075	.060	.070	.076	.078	.097	.103	.126	.135
	TOT OBS	122	122	142	144	150	154	130	151	120	132	103	86	1556
2300	MEAN	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
	SD	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000	.000
	TOT OBS	0	0	0	0	0	0	0	0	0	0	0	0	0
ALL HOURS	MEAN	29.15	29.09	29.03	28.97	28.91	28.89	28.92	28.93	28.93	29.00	29.09	29.14	29.00
	SD	.126	.130	.125	.104	.092	.075	.088	.088	.092	.105	.118	.132	.139
	TOT OBS	1021	971	1161	1049	1036	1037	982	1064	966	1023	919	940	12169

PPPPPPPP	AAAAAA	RRRRRRRR	TTTTTTTTTT	GGGGGG
PPPPPPPP	AAAAAAA	RRRRRRRR	TTTTTTTTTT	GGGGGGGG
PP PP	AA AA	RR RR	TT	GG GG
PP PP	AA AA	RR RR	TT	GG
PPPPPPPP	AA AA	RRRRRRRR	TT	GG
PPPPPPPP	AAAAAAAAA	RRRRRRRR	TT	GG GGGG
PP	AAAAAAAAA	RR RR	T*	GG GGGG
PP	AA AA	RR RR	TT	GG GG
PP	AA AA	RR RR	TT	GGGGGGGG
PP	AA AA	RR RR	TT	GGGGGG

PART G

CROSSWIND SUMMARY

CROSSWIND SUMMARIES.

THESE TABLES ARE CREATED FROM HOURLY AND SPECIAL OBSERVATIONS (INCLUDING PEAK GUST REMARKS). THE TABLES ARE SUMMARIZED AS FOLLOWS:

- BY EIGHT 3-HOUR STANDARD TIME PERIODS FOR EACH MONTH (ALL YEARS COMBINED).
- BY MONTH (ALL YEARS AND ALL HOURS COMBINED).
- BY MONTH (ALL YEARS AND THE HOURS 0600-2000 LST COMBINED).
- BY YEAR (ALL YEARS AND ALL HOURS COMBINED).
- BY YEAR (ALL YEARS AND THE HOURS 0600-2000 LST COMBINED).

THE TABLES GIVE PERCENT OCCURRENCE FREQUENCY (POF) OF THE "CROSS-RUNWAY WIND COMPONENT" FOR THE WIND SPEED CLASSES SPECIFIED IN THE TABLE HEADINGS. THERE ARE TWO COMPONENT CATEGORIES:

THE FIRST COMPONENT IS COMPUTED FROM THE REPORTED WIND DIRECTION AND WIND SPEED FROM HOURLY RECORD OR RECORD-SPECIAL OBSERVATIONS.

THE SECOND COMPONENT IS COMPUTED FROM THE HIGHEST REPORTED WIND SPEED AND DIRECTION FROM ALL OBSERVATIONS INCLUDING REMARKS, GUSTS, AND SPECIAL OBSERVATIONS.

OBSERVATION COUNTS INCLUDE CALM WINDS.

VARIABLE WINDS ARE CONSIDERED A DIRECT CROSSWIND IF THE SPEED EQUALS OR EXCEEDS THE SPECIFIED THRESHOLD WIND SPEED VALUE(S).

A TOTAL OBSERVATION COUNT IS INCLUDED.

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JAN

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	1.1			635	3.7	.1		708
CATEGORY B				0				0	1.1			635	4.0	.6		708

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	7.4	.6		692	5.6	.8		644	1.9	.9		424				86
CATEGORY B	8.5	1.7	.1	692	6.5	2.0	.2	644	2.1	.9		424				86

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	4.1	.5		3103	4.0	.4		3189
CATEGORY B	4.7	1.1	.1	3103	4.5	1.0	.1	3189

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: FEB

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	.5			592	2.8			681
CATEGORY B				0				0	.7	.5		592	3.4	1.0	.1	631

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	4.4	.5		663	3.9	.2		614	.7			414	.9			113
CATEGORY B	5.7	1.4		663	4.9	2.0		614	1.4	.5		414	.9	.9		113

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	2.6	.1		2964	2.6	.1		3077
CATEGORY B	3.4	1.1	.0	2964	3.3	1.1	.0	3077

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAR

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	.6			712	3.8	.6		811
CATEGORY B				0				0	.8	.1		712	5.	1.8		811

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	8.8	.9		795	11.8	.7		712	5.4	1.2		482	2.7	2.0		150
CATEGORY B	13.3	5.4	.3	795	15.3	6.6		712	6.4	2.3	.6	482	3.3	2.0	1.3	150

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	6.1	.7		3512	6.0	.7		3662
CATEGORY B	8.5	3.3	.1	3512	8.2	3.3	.2	3662

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: APR

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	1.4	.2		638	6.5	.6		718
CATEGORY B				0				0	1.7	.3		638	9.7	4.0		718

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	8.6	1.4		707	12.8	2.0		666	5.0	.9		470	2.8	.6		179
CATEGORY B	14.1	5.7		707	17.3	6.9		567	12.9	3.2	.6	470	4.5	2.1	.6	179

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	7.2	1.0		3199	7.0	1.0		3378
CATEGORY B	10.5	4.1	.2	3199	10.2	4.0	.2	3378

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: MAY

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	1.4			645	3.0	.6		702
CATEGORY B				0				0	1.6	.2		645	5.0	2.0		702

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	3.9	.1		691	13.8	1.8		623	9.8	.9		469	.4			241
CATEGORY B	9.6	2.3		691	20.9	7.7	.2	623	12.6	4.7		469	.4			241

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	6.0	.6		3130	5.6	.6		3371
CATEGORY B	9.6	3.2	.0	3130	8.9	3.0	.0	3371

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUN

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	1.1			652	2.1	.1		711
CATEGORY B				0				0	1.1			652	2.8	.4		711

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	4.7	.4		679	11.6	.6		623	8.8	1.0		483	.7			281
CATEGORY B	8.7	2.1		679	16.4	4.8		623	9.8	2.3	.4	483	.7	.4		281

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	5.4	.4		3153	5.0	.4		3434
CATEGORY B	7.5	1.8	.1	3153	8.9	1.7	.1	3434

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF A7
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: JUL

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	.5			623	1.1	.3		665
CATEGORY B				0				0	.5	.2		623	1.4	.3		665

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	2.3			656	6.6			619	5.9	1.2	.2	426	1.9			211
CATEGORY B	4.3	.9		656	9.4	1.9		619	7.7	2.3	.7	426	3.3	1.9		211

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	3.0	.2	.0	2989	3.0	.2	.0	3200
CATEGORY B	4.4	1.0	.1	2989	4.3	1.1	.1	3200

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: AUG

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	.8			664	.8			732
CATEGORY B				0				0	.9			664	.8			732

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	1.9	.4		702	5.2	.3		655	4.1	.4		484	.9	.4		224
CATEGORY B	2.6	.7	.1	702	6.9	1.5	.2	655	5.2	1.0	.4	484	1.3	1.3		224

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	2.4	.2		3237	2.3	.2		3461
CATEGORY B	3.1	.6	.1	3237	3.0	.7	.1	3461

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: SEP

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	3.0			605	5.6	.1		682
CATEGORY B				0				0	3.0	.3		605	7.2	2.1		682

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	4.3	.3		652	5.0	.7		599	1.7			403	1.3	.7		149
CATEGORY B	6.6	1.5		652	7.3	1.7		599	2.2	.7		403	1.3	.7		149

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	4.1	.2		2941	4.0	.3		3090
CATEGORY B	5.5	1.3		2941	5.3	1.3		3090

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: OCT

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	.3			648	5.7	.6		701
CATEGORY B				0				0	.3			648	6.1	1.3		701

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	6.1	1.2		693	6.0	.9		653	1.3			446				135
CATEGORY B	8.1	2.7	.3	693	6.6	2.0		653	1.3			446				135

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	4.1	.6		3141	3.4	.5		3276
CATEGORY B	4.8	1.3	.1	3141	4.6	1.3	.1	3276

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF A7
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: NOV

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	.7			579	4.5			66
CATEGORY B				0				0	.7	.2		579	5.1	.5		66

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	6.7	.2		640	6.1	1.0		574	.5	.3		370				5
CATEGORY B	8.4	1.6		640	6.8	1.7		574	.5	.3		370				5

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	4.0	.3		2825	4.0	.3		2884
CATEGORY B	4.7	.9		2825	4.6	.9		2884

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AFB AZ
LST TO C: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: DEC

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	1.8	.3		621	3.5	.7		694
CATEGORY B				0				0	1.9	1.0		621	4.3	1.7		694

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	5.3	.9		659	4.4	.3		594	1.5	.6		329				67
CATEGORY B	6.1	1.7	.2	659	5.1	.8		594	1.5	.9		329				67

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	3.5	.6		2397	3.5	.6		1964
CATEGORY B	4.0	1.3	.3	2397	3.9	1.2		1964

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

PERCENTAGE FREQUENCY OF OCCURRENCE OF CROSSWINDS
FROM HOURLY OBSERVATIONS

MAGNETIC RUNWAY HEADING: 170-350

STATION NUMBER: 747240

STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JUN 79 - MAY 89
MONTH: ALL

CATEGORY A: ANY CEILING OR VISIBILITY (HOURLY OBS ONLY)

CATEGORY B: HIGHEST WINDS REPORTED WITHIN THE HOUR (HOURLIES + SPECIALS)

TIME (LST)	0000 - 0200				0300 - 0500				0600 - 0800				0900 - 1100			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A				0				0	1.1	.6		7614	3.6	.3		8467
CATEGORY B				0				0	1.2	.2		7614	4.6	1.3	.0	8467

TIME (LST)	1200 - 1400				1500 - 1700				1800 - 2000				2100 - 2300			
SPEED (KTS)	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	5.4	.6		8229	7.8	.3		7576	4.2	.6	.0	5205	1.1	.3		1895
CATEGORY B	8.1	2.4	.1	8229	10.4	3.4	.1	7576	5.2	1.7	.2	5205	1.6	.9	.2	1895

TIME (LST)	0600 - 2000				ALL HOURS			
SPEED KTS	GE10	GE15	GE25	OBS	GE10	GE15	GE25	OBS
CATEGORY A	4.4	.5	.0	37091	4.3	.5	.0	38986
CATEGORY B	6.0	1.8	.1	37091	5.7	1.8	.1	38986

PPPPPPPP	AAAAAA	RRRRRRRR	TTTTTTTTTT	HH	HH
PPPPPPPP	AAAAAAA	RRRRRRRR	TTTTTTTTTT	HH	HH
PP PP	AA AA	RR RR	TT	HH	HH
PP PP	AA AA	RR RR	TT	HH	HH
PPPPPPPP	AA AA	RRRRRRRR	TT	HHHHHHHHHH	
PPPPPPPP	AAAAAAAAA	RRRRRRRR	TT	HHHHHHHHHH	
PP	AAAAAAAAA	RR RR	TT	HH	HH
PP	AA AA	RR RR	TT	HH	HH
PP	AA AA	RR RR	TT	HH	HH
PP	AA AA	RR RR	TT	HH	HH

PART H

DEGREE DAY SUMMARIES

DEGREE DAYS.

CREATED FROM HOURLY OBSERVATIONS (MAX+MIN/2 WHEN AVAILABLE), THESE TABLES GIVE THE THE NUMBER OF DEGREE DAYS FOR EACH MONTH IN EACH YEAR OF THE AVAILABLE PERIOD OF RECORD.

INCLUDED BENEATH EACH SUMMARY ARE STATISTICS BASED ON A 30-YEAR (1951-1980) POR (IF AVAILABLE). THE 30-YEAR POR PROVIDES AWS USERS WITH A SUMMARY CONSISTENT WITH OTHER STANDARD CLIMATIC PUBLICATIONS, NOTABLY THOSE OF THE NATIONAL CLIMATIC DATA CENTER (NCDC). NOTE THAT THE 30-YEAR POR WILL CHANGE TO 1961-1990 AS SOON AS DATA FOR DECEMBER 1990 HAS BEEN PROCESSED.

MONTHS WITH NO AVAILABLE DATA AND MONTHS WITH A VALUE OF ZERO APPEAR AS BLANKS IN THESE TABLES. ASTERISKS (****) DENOTE AN INCOMPLETE MONTH WITH A DAY (OR DAYS) THAT CANNOT BE CALCULATED (FILLED IN) AUTOMATICALLY.

HEATING DEGREE DAYS.

ONE "HEATING DEGREE DAY" IS ASSIGNED TO REPRESENT EACH DEGREE THAT THE MEAN TEMPERATURE FALLS BELOW A DESIGNATED "BASE TEMPERATURE" OF 65 DEGREES* FAHRENHEIT. FOR EXAMPLE, IF THE MEAN TEMPERATURE ON A GIVEN DAY IS 57 DEGREES, THAT DAY IS SAID TO HAVE 8 HEATING DEGREE DAYS.

COOLING DEGREE DAYS.

ONE "COOLING DEGREE DAY" IS ASSIGNED TO REPRESENT EACH DEGREE THAT THE TEMPERATURE RISES ABOVE A DESIGNATED "BASE TEMPERATURE" OF 65 DEGREES* FAHRENHEIT. FOR EXAMPLE, IF THE MEAN TEMPERATURE FOR A GIVEN DAY IS 73 DEGREES, THAT DAY IS SAID TO HAVE 8 COOLING DEGREE DAYS.

*65 DEGREES FAHRENHEIT HAS BEEN SELECTED AS THE NATIONWIDE STANDARD "BASE TEMPERATURE" AT WHICH (AT LEAST THEORETICALLY) NO HEATING OR COOLING IS REQUIRED. IF ANOTHER BASE TEMPERATURE IS USED IN THESE TABLES, IT WAS SPECIALLY REQUESTED BY THE STATION, AND IS NOTED.

NOTE 1. THESE SUMMARIES ARE NOT AVAILABLE FOR EARLY TIME PERIODS.

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

HEATING DEGREE DAYS
FROM HOURLY OBSERVATIONS

BASE TEMPERATURE 65

STATION NUMBER: 747240 STATION NAME: GILA BEND AAF AZ
LST TO UTC: + 7

PERIOD OF RECORD: JAN 49 - DEC 54

YEARS	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN
1949	619	325	116	24						47	14	373	1518
1950	416	121	62	3	1						50	178	831
1951	373	228	113	29	4					7	126	364	1244
1952	426	244	262	20							215	370	1537
1953	246	262	86	29	1					7	111	401	1143
1954	348	74	130							12	21	271	856
MEAN	404	209	128	17	1					12	89	326	
SD	123.22	93.62	69.93	12.88	1.55					17.68	76.1	85.02	

OPERATING LOCATION "A"
USAFETAC, ASHEVILLE NC

COOLING DEGREE DAYS
FROM HOURLY OBSERVATIONS

BASE TEMPERATURE 65

STATION NUMBER: 747240

STATION NAME: GILA DEND. AA. AD
LSF TO UTCL: 4 7

PERIOD OF RECORD: 1949 - 1954

YEARS	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	TOTAL
1949		1	17	285	409	735	854	840	759	257	75	8	4071
1950		3	70	311	405	720	820	871	591	428	107	2	4531
1951	2	11	34	184	461	630	929	795	700	318	7		4071
1952		1	22	165	567	682	874	917	768	497	38		4531
1953		1	73	179	260	702	954	900	727	347	107		4250
1954		44	37	339	522	669	917	832	741	417	59	3	4580
MEAN	0	11	42	243	437	679	898	859	714	385	66	2	
SD	.82	16.72	23.91	76.50	107.55	32.35	47.19	45.79	65.06	104.09	38.76	3.13	

A W S CLIMATIC BRIEF	STATION NAME: GILA BEND AAF A2	FIELD ELEV: 858 FT
	LATITUDE/LONGITUDE: 32 53 N 112 43 W	STATION MSC: 747240
	HOURLY OBS POR: JUN 79 - MAY 89	CALL SIGN: KGBN
	SUMMARY OF DAY POR: 4811-6302 (FULL TIME), 6303-7111, 8207-8905 (PART TIME)	
NOV 89	HOURS SUMMARIZED: 00-23 LST (4811-6302), 06-22 LST (6303-7111, 7906-8905)	
	LST TO UTC: +07	SUPERSEDES: DEC 75

MONTH	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN	YOR
@ EXTRM MAX TEMP (F)	87	92	98	110	115	118	121	120	118	114	96	87	121	30
@ MEAN MAX TEMP (F)	68.1	73.0	78.0	86.7	95.9	105.6	109.3	106.5	102.9	91.8	77.6	69.1	88.7	30
@ MEAN TEMP (F)	53.0	57.1	61.8	69.2	78.2	87.3	94.0	91.8	86.4	74.8	61.8	53.9	72.4	30
@ MEAN MIN TEMP (F)	37.9	41.1	45.4	51.7	60.4	68.9	78.7	77.0	69.9	57.8	45.9	38.6	56.1	30
@ EXTRM MIN TEMP (F)	18	24	25	37	40	53	61	57	49	31	28	20	18	39
D/W TEMP GE 100 (F)	0	0	0	2	10	23	29	27	19	3	0	0	113	39
D/W TEMP GE 90 (F)	0	1	2	12	23	29	31	31	28	18	1	0	176	39
D/W TEMP LT 40 (F)	16	9	4	1	0	0	0	0	0	1	5	14	50	39
D/W TEMP LT 33 (F)	5	2	1	0	0	0	0	0	0	#	1	3	12	39
@ HEATING DEGREE DAYS	376	242	150	33	6	0	0	0	0	11	132	351	1301	30
@ COOLING DEGREE DAYS	#	20	50	159	415	669	899	831	642	315	36	7	4043	30
MEAN DEWPOINT TEMP (F)	36.5	35.9	36.0	35.0	37.7	40.7	56.9	60.1	52.2	43.9	36.3	36.6	42.4	10
MEAN WET BULB TEMP (F)	47.2	49.0	51.8	55.3	59.5	64.3	71.8	72.5	67.0	59.2	51.1	47.1	58.2	10
99.95% WCPA (FT)	1100	1150	1200	1200	1200	1200	1200	1200	1200	1200	1150	1150	1300	10
MEAN REL HUM 07 LST(%)	71.0	64.4	56.1	38.1	31.1	25.9	42.5	51.2	45.8	49.6	56.3	69.8	50.0	10
MEAN REL HUM 13 LST(%)	40.1	33.9	29.1	20.2	17.0	13.9	25.4	28.2	25.3	26.5	30.3	42.1	27.6	10
@ MAX 24HR PRECIP (IN)	1.73	1.35	1.63	.60	.93	.40	1.43	3.00	2.75	1.10	1.58	1.23	3.00	39
@ MAX PRECIP (IN)	2.61	1.83	2.55	1.89	1.33	.57	2.05	5.61	2.85	1.88	2.15	3.81	10.56	39
MEAN PRECIP (IN)	.66	.48	.47	.15	.10	.03	.67	1.36	.60	.41	.39	.64	6.03	39
MIN PRECIP (IN)	.00	.00	.00	.00	.00	.00	#	.03	.00	.00	.00	.00	1.30	39
D/W PRECIP GE .01 (IN)	4	2	3	1	1	1	4	5	2	2	2	3	30	39
D/W PRECIP GT .50 (IN)	1	1	1	#	#	0	1	1	1	1	1	1	9	39
@ MAX 24HR SNFL (IN)	0	.1	0	0	0	0	0	0	0	0	0	2.5	2.5	39
@ MAX SNFL (IN)	0	.1	0	0	0	0	0	0	0	0	0	2.5	2.5	39
@ MEAN SNFL (IN)	0	#	0	0	0	0	0	0	0	0	0	.1	.1	39
@ D/W SNFL GE .1 (IN)	0	#	0	0	0	0	0	0	0	0	0	#	#	39
@ D/W SNFL GE 1.5 (IN)	0	0	0	0	0	0	0	0	0	0	0	#	#	39
MAX DLY SNO DEPTH (IN)	0	0	0	0	0	0	0	0	0	0	0	#	#	39
MEAN SFC WND DIR (DEG)	\$030	\$030	\$240	\$240	\$240	\$240	\$240	\$240	\$270	\$030	\$030	\$030	\$240	10
MEAN WND SPD (KTS)	3.5	3.6	4.4	5.0	5.1	4.7	4.4	3.7	3.9	3.5	3.6	3.3	4.1	10
@@ MAX WND SPD (KTS)	42	38	50	40	38	46	52	48	42	40	40	34	52	29
SKY COVER GT 1/2 (%)	39.0	47.4	36.0	32.2	23.0	16.4	29.0	28.7	21.0	28.3	29.0	40.2	30.9	10
D/W THUNDERSTORMS	1	1	1	1	1	1	6	6	2	1	1	1	23	30
D/W FOG (VSBY LT 7 MI)	1	1	#	0	0	0	#	1	#	#	1	1	5	30

LEGEND: ANN = ANNUAL

D/W = MEAN NUMBER OF DAYS WITH

& = BASED ON LESS THAN FULL MONTHS

** = INSTANTANEOUS PEAK WINDS

* = DATA NOT AVAILABLE

POR/YOR = PERIOD/YEARS OF RECORD

WCPA = WORST CASE MAXIMUM PRESSURE ALTITUDE

= LESS THAN 0.5 DAYS OR TRACE AS APPLICABLE

\$ = PERCENTAGE OF CALM WINDS GREATER THAN OR EQUAL TO MEAN WIND DIRECTION

		PERCENT OCCURRENCE FREQUENCY OF CEILING AND VISIBILITY															
MONTH		JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	ANN	YDR		
CIG LT 3000 FT AND/OR VSBY LT 3 MI	LST																
	00 - 05	*	*	*	*	*	*	*	*	*	*	*	*	*	*	10	
	06 - 08	.5	2.0	.4	.0	.0	.0	.0	.0	.0	.0	.7	1.1	.4	10		
	09 - 11	1.1	2.2	.5	.4	.0	.0	.2	.0	.0	.0	.9	2.2	.6	10		
	12 - 14	1.0	1.7	.9	.3	.0	.0	.0	.0	.0	.0	1.4	3.5	.7	10		
	15 - 17	.3	2.0	.7	.2	.0	.0	.0	.0	.2	.2	.7	3.0	.6	10		
	18 - 20	.0	2.2	.0	.0	.0	.0	.5	.2	.0	.0	.0	.9	.3	10		
	21 - 22	.0	.9	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.1	10		
	ALL	.6	2.0	.5	.2	.0	.0	.1	.0	.0	.0	.8	2.2	.5	10		
CIG LT 1500 FT AND/OR VSBY LT 3 MI	00 - 05	*	*	*	*	*	*	*	*	*	*	*	*	*	*	10	
	06 - 08	.2	.3	.0	.0	.0	.0	.0	.0	.0	.0	.5	.5	.1	10		
	09 - 11	.	1.0	.1	.0	.0	.0	.0	.0	.0	.0	.5	1.1	.3	10		
	12 - 14	.6	.2	.5	.1	.0	.0	.0	.0	.0	.0	.8	1.1	.3	10		
	15 - 17	.0	.0	.0	.0	.0	.0	.0	.0	.2	.2	.3	.5	.1	10		
	18 - 20	.0	.0	.0	.0	.0	.0	.5	.2	.0	.0	.0	.6	.1	10		
	21 - 22	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	10		
	ALL	.2	.3	.1	.0	.0	.0	.1	.0	.0	.0	.5	.8	.2	10		
CIG LT 1000 FT AND/OR VSBY LT 2 MI	00 - 05	*	*	*	*	*	*	*	*	*	*	*	*	*	*	10	
	06 - 08	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.5	.2	.1	10		
	09 - 11	.3	.1	.1	.0	.0	.0	.0	.0	.0	.0	.5	.3	.1	10		
	12 - 14	.3	.0	.1	.1	.0	.0	.0	.0	.0	.0	.5	.0	.1	10		
	15 - 17	.0	.0	.0	.0	.0	.0	.0	.0	.2	.0	.2	.2	.0	10		
	18 - 20	.0	.0	.0	.0	.0	.0	.2	.0	.0	.0	.0	.0	.0	10		
	21 - 22	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	10		
	ALL	.1	.0	.1	.0	.0	.0	.0	.0	.0	.0	.3	.1	.1	10		
CIG LT 200 FT AND/OR VSBY LT 1/2 MI	00 - 05	*	*	*	*	*	*	*	*	*	*	*	*	*	*	10	
	06 - 08	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.5	.0	.0	10		
	09 - 11	.1	.0	.0	.0	.0	.0	.0	.0	.0	.0	.2	.0	.0	10		
	12 - 14	.3	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	10		
	15 - 17	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	10		
	18 - 20	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	10		
	21 - 22	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	.0	10		
	ALL	.1	.0	.0	.0	.0	.0	.0	.0	.0	.0	.1	.0	.0	10		

HURRICANES/TROPICAL STORMS OBSERVED FOR THE PERIOD 1965 - 1986:

HR/TS	JUL	AUG	SEP	OCT	ANN
60NM	0/0	0/0	0/0	0/0	0/0
120NM	0/0	0/1	0/0	0/0	0/1
240NM	0/0	1/1	0/1	0/0	1/2

REMARKS @ : SUMMARY OF THE DAY (SOD) AND HEATING/COOLING DEGREE DAY DATA WERE SUPPLEMENTED FROM:

CLIMATOGRAPHY OF THE UNITED STATES (NO. 20) FOR GILA BEND AZ; SOD POR: JAN 51 - DEC 80.

@@ : MAX WND SPD DATA WERE DERIVED FROM HOURLY OBSERVATIONS (GUSTS) FOR POR 4811-5412, 6809-8601 AND FROM SOD DATA (PEAK WINDS) FOR POR 8602-8905.

DISTRIBUTION

5WW/DN, Langley AFB, VA 23665-5524	1
25WS/DON, Bergstrom AFB, TX 78743-5000	1
Det15, 25WS, Luke AFB, AZ 85309-5000	1
OL-A, Det 15, 25WS, Gila Bend AAF, AZ 85337-5000	1
USAFETAC/LDD, Scott AFB, IL 62225-5438	1
OL-A, USAFETAC, Federal Building, Asheville, NC 28801-2723	1
DTIC-FDAC, Cameron Station, Alexandria, VA 22304-6145	2
AWSTL, Scott AFB, IL 62225-5458	10